

Objekttyp: **Advertising**

Zeitschrift: **IABSE structures = Constructions AIPC = IVBH Bauwerke**

Band (Jahr): **6 (1982)**

Heft C-21: **Recent structures**

PDF erstellt am: **29.04.2024**

Nutzungsbedingungen

Die ETH-Bibliothek ist Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Inhalten der Zeitschriften. Die Rechte liegen in der Regel bei den Herausgebern.

Die auf der Plattform e-periodica veröffentlichten Dokumente stehen für nicht-kommerzielle Zwecke in Lehre und Forschung sowie für die private Nutzung frei zur Verfügung. Einzelne Dateien oder Ausdrucke aus diesem Angebot können zusammen mit diesen Nutzungsbedingungen und den korrekten Herkunftsbezeichnungen weitergegeben werden.

Das Veröffentlichen von Bildern in Print- und Online-Publikationen ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Die systematische Speicherung von Teilen des elektronischen Angebots auf anderen Servern bedarf ebenfalls des schriftlichen Einverständnisses der Rechteinhaber.

Haftungsausschluss

Alle Angaben erfolgen ohne Gewähr für Vollständigkeit oder Richtigkeit. Es wird keine Haftung übernommen für Schäden durch die Verwendung von Informationen aus diesem Online-Angebot oder durch das Fehlen von Informationen. Dies gilt auch für Inhalte Dritter, die über dieses Angebot zugänglich sind.



Whenever Structural Safety is the Point... Kern Precision Instruments are the Right Choice


For measuring distances up to 2500 m:

Mekometer ME 3000

Electro-optical Precision Distance Meter with the extremely high accuracy of $\pm(0.2 \text{ mm} + 1 \text{ ppm})$ and a range of 2.5 km. Digital distance display to 0.1 mm.

Universal application: structural deformation measurements, large area slip and displacement measurements, precision layout work and fundamental surveying.

The Mekometer used for dam control measurements



For measuring length variations within a distance range of 50 m:

Distometer ISETH

Precision instrument for accurate determination of length variations by means of Invar wires. Measuring accuracy $\pm 1 \text{ ppm}$; length of the Invar wire 1—50 m; measuring range for length variations 100 mm. Special advantages: lengths of any inclination including vertical may be measured; simple layout of the measuring arrangement. Application: structural deformation measurements.

The Distometer ISETH used for tunnel wall deformation measurement

Kern & Co. Ltd.
Mechanical, Optical and
Electronic Precision Instrument
CH-5001 Aarau, Switzerland
Telex 68 106


Please send me your detailed documentation on:

- Mekometer ME 3000
- Distometer ISETH



Name: _____

Occupation: _____



Address: _____




Belags-Sickerwasser-Ableiter
Subsurface Seepage.
Evacuations des eaux et aérations.
Ductos de agua de filtración para calzadas.




Entwässerungs-Systeme
Surface drainage
Evacuations des eaux
Pozos de drenaje




Hohlraumschalungen
Einstiegsluken + Türen
Formwork + Moulds
Access openings
Ouvertures d'entrée
Aberturas de entrada



Auflager
Structural Bearings
Appuis
Apoyos




Pressen + Pumpen
Hydraulic jacks
Verins + Pompes
Prensas + bombas



heinz honegger ag

CH-8427 Rorbas ZH Switzerland
Tel. 01 - 865 11 77, Telex 52844


Vertretungs- und Lizenzvergabe:
Honel-Holding SA
Sonnmatstrasse 6
CH-8180 Bülach, Switzerland
Phone 01/860 89 43




**The Wild DI4/DI4L Distomats are the world's
smallest reducing distancers
... to make it even easier for you.**



**And the Citation CI410/CI450 infra-red distancers
have the unique SCAN program
... to give you even better control.**



**And the Wild DI20 Distomat measures over great
distances with millimetre accuracy
... to make your measured values even more accurate.**



**And the Wild TC1/TC1L Tachymats measure, reduce
and record completely electronically
... to make you even faster.**



If you want to know more about the leading range of electronic infra-red distance-measuring equipment and tacheometers, or if you want to learn more about new solutions for automated further processing of data, ask for our detailed literature.









We shall be glad to send you full documentation ■

Please send your technical literature on Wild EDM to:
Address

Send to your nearest Wild representative
or to Wild Heerbrugg Ltd
CH-9435 Heerbrugg
Switzerland

IVB 5.2

WILD
HEERBRUGG
Your Systems Partner



1
RESTON Pot Sliding Bearings
are highly suitable for installation in bridge structures. They feature a low-profile design, low weight and high loading capacity.

2
RESTON Linear Tilting and Sliding Bearings
are a combination of normal linear tilting bearings and PTFE sliding bearings and are suitable for installation in bridge structures.

PROCEQ SA
Riesbachstrasse 57
CH-8034 Zurich

3
LASTO-BLOCK Bearings
are suitable for building, civil engineering and bridge construction applications. Their simple form allows easy installation.

4
LASTO-STRIP Bearings for Buildings
were especially developed for building constructions. They are particularly suitable for movement compensation between concrete slabs and load-supporting walls and prevent structural cracking.

5
TENSA-ACME Roadway Construction Joints
are highly suitable for installation in traffic levels (parking lots, bridges, airport areas etc.). Dilatation up to 60 mm.

6
TENSA-LASTIC Roadway Construction Joints
meet all the requirements that can be made in bridge engineering of a modern joint design. They are rugged and watertight. Dilatation range 60 mm and bigger.

proceq

Phone: 01/477800
Telex 53357 proce ch