

**Zeitschrift:** IABSE congress report = Rapport du congrès AIPC = IVBH  
Kongressbericht

**Band:** 3 (1948)

**Artikel:** Lateral stability of I-beams

**Autor:** Ingerslev, Eric

**DOI:** <https://doi.org/10.5169/seals-4090>

#### Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

#### Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

#### Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

**Download PDF:** 22.08.2025

**ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>**

# Id1

## **Stabilité latérale des poutres à âme pleine** (Méthode par superposition)

## **Kipperscheinungen von I-Trägern** (Eine Superpositions-methode)

## **Lateral stability of I-beams** (Method of super-position)

ERIC INGERSLEV  
London

The problem I am going to tackle is not a new one in technical literature, as it dates back to 1899, when it was first treated simultaneously by A. G. Michell and Ludwig Prandtl.

Further development rests mainly upon works of S. Timoshenko, presenting the special features of the rolled steel joist, and of H. Wagner, who described the phenomenon, which he called "Drillknickung", i.e., buckling by twist.

The problem is to-day fully solved mathematically, but the exact solution is normally so involved that it has no practical bearing — which brings us to the point of this discussion, the approximate methods.

Our joist with I Section has the following leading features :

Maximum flexural rigidity	$A = EI_1$
Minimum flexural rigidity	$B = EI_2$
Torsional rigidity	$C = GI_t$
Flexural rigidity of one flange	$D \sim \frac{1}{2} B$ .

Its deflections will be measured from a system of co-ordinate axes  $x$ ,  $y$ ,  $u$ ;  $x$  along the centre line of the undeflected beam;  $y$  at right angles to  $x$  in the web; and  $u$  at right angles to both  $x$  and  $y$ . The deflected beam will at the point  $(x, y, u)$  be twisted an angle  $\beta$ .

If vertical moments (i.e., acting in the plane of the web)  $M$  and horizontal moments  $M_h$  are applied to the centre line of the beam and if

they are just sufficient to make the beam buckle, then the leading equations will be :

$$-A \frac{d^2y}{dx^2} = M + \frac{A-B}{B} \beta M_h , \quad (1)$$

$$-B \frac{d^2u}{dx^2} = M_h + \frac{A-B}{A} \beta M , \quad (2)$$

$$MM_h + (A-B) \left( \frac{M^2}{A} - \frac{M_h^2}{B} \right) + \frac{AB}{A-B} \frac{d}{dx} \left[ C \frac{d\beta}{dx} - \frac{d}{dx} \left( \frac{1}{2} Dh^2 \frac{d^2\beta}{dx^2} \right) \right] . \quad (3)$$

If the maximum value of  $M$  be  $M_1$ , we will write our solution as :

$$M_1 = \frac{k}{l} \frac{A}{A-B} \sqrt{BC}$$

$k$  is a constant characteristic of the case of loading, and  $l$  is the span.

We will here confine ourselves to an I-cross-section, symmetrical about both its axis constant along its length, and free to rotate around a vertical axis over the supports. Our first case shall consist of vertical moments only.

$$\text{Introducing } m = \frac{M}{M_1} \text{ and } \alpha^2 = \frac{\frac{1}{2} Dh^2}{Cl^2} \text{ and } l \frac{d\beta}{dx} = \beta' .$$

Equation (3) becomes :

$$\beta m^2 k^2 + \beta'' - \alpha^2 \beta''' = 0 . \quad (4)$$

An exact solution is arrived at by a "trial and error" method : guessing  $\beta$  in  $\beta m^2 k^2$  and integrating this expression.

A satisfactory approximation, however, is found by inserting the average  $\beta$ ,  $\beta_{av} \sim 0.8 \beta_{max}$  and solving the following two equations :

$$0.8 \beta_{max} m^2 k_{M_1}^2 = -\beta''$$

$$0.8 \beta_{max} \frac{m^2 k_{M_1}^2}{\alpha^2} = \beta'''$$

and then using

$$k = \sqrt{k_{M_1}^2 + k_m^2}$$

$\frac{1}{k_{M_1}^2}$  is found as the maximum bending moment in a simple supported beam with the distributed load  $0.8 m^2$  and  $\frac{\alpha^2}{k_{M_1}^2}$  will be the maximum deflection of the same beam ( $EI=1$ , length=1).

If the distributed load  $p$  and the single forces  $P$  of our rolled steel joist do not act at the centre line of the beam but at a distance  $a$  above the centre line, then we should load our simply supported beam once more

— this time with  $\frac{\beta}{\beta_{max}} \cdot (pl^2 + Pl) \frac{a}{C}$ . The maximum moment should be 1 (producing  $k_{P1}$ ) and the maximum deflection should be  $\alpha^2$  (producing  $k_{P2}$ ).

The final factor  $k$ , including for all the effects we have now dealt with, is found as the solution to the equation :

$$\left(\frac{1}{k_{M_1}}\right)^2 + \frac{k}{k_{P_1}} + \left(\frac{1}{k_{M_2}}\right)^2 + \frac{k}{k_{P_2}} = 1 .$$

We have not yet taken any longitudinal forces in the beam into account. If we disregard them, I have just shewn how to find  $k$ , and this value we will call  $k_M$ . If, on the other hand, we only let the longitudinal force  $N$  (which we will write as  $N = \frac{xB}{l^2}$ ) act, we will then get from the normal Euler formula  $x_E = \pi^2$ .

If we finally include for both longitudinal force and bending moments, our result will be found from the following equation :


$$\frac{x}{x_E} + \left(\frac{k}{k_M}\right)^2 = 1 .$$

Time does not permit the full proof of the various formulae I have given. It must be sufficient to mention that they are based upon the shape of the deflection being the same type for all the parts into which we split the load and the beam. If the types differ, the result will be too small values of  $x$  and  $k$ , which only means that we are on the safe side. It is possible, however, in some of these special cases to give special formulae taking this into account.


Finally I will show you an example of how to use our formulae.

I choose a rolled steel joist subject to a longitudinal force  $N = \frac{xB}{l^2}$  and a single force  $P$  acting at the centre of the beam on top of the upper flange.

$m$  is then simply a triangle :



0.8  $m^2$  will consist of two 2nd degree parabolas :



This is used as load on a simply supported beam.

$$\text{Maximum moment} = \frac{1}{k_{M_1}^2} = \frac{1}{20} ; \quad k_{M_1} = 4.5 .$$

$$\text{Maximum deflection} = \frac{\alpha^2}{k_{M_1}^2} = \frac{7}{1440} ; \quad k_{M_1} = 14.3 \alpha .$$

This beam should next be loaded with —

$$\frac{\beta}{\beta_{\max}} (pl^2 + Pl) \frac{a}{C} = Pl \frac{a}{C} = 4M_1 \frac{h}{2C} = 2 \frac{k}{l} \frac{A}{A-B} \sqrt{BC} \frac{h}{C} = 4k \frac{A}{A-B} \alpha$$

i.e., a single force  $\frac{4kA\alpha}{A-B}$  acting at the centre.

$$\text{Maximum moment} = l = \frac{1}{4} \times \frac{4 k A \alpha}{A - B}; \quad k_p = \frac{A - B}{A \alpha}.$$

$$\text{Maximum deflection} = \alpha^2 = \frac{1}{12} \times \frac{k A \alpha}{A - B}; \quad k_p = \frac{12 (A - B) \alpha}{A}.$$

The result of P only is then —

$$\frac{1}{\left(\frac{k_M}{4.5}\right)^2 + \frac{k_M}{A - B}} + \frac{1}{\left(\frac{k_M}{14.3 \alpha}\right)^2 + \frac{k_M}{12(A - B) \alpha}} = 1$$

and P and N together gives

$$\frac{\alpha}{\pi^2} + \left(\frac{k}{k_M}\right)^2 = 1.$$

Assuming  $\frac{A - B}{A} \sim 1$ ,  $\alpha \sim \frac{1}{2}$  (as a special case) one gets

$$\frac{1}{\left(\frac{k_M}{4.5}\right)^2 + \frac{k_M}{2}} + \frac{1}{\left(\frac{k_M}{7.15}\right)^2 + \frac{k_M}{6}} = 1 \quad k_M = 5.1$$

$$\frac{\alpha}{\pi^2} + \left(\frac{k}{5.1}\right)^2 = 1$$

$$\begin{array}{ccccccc} \alpha & = & -\pi^2 & -5 & 0 & +5 & +\pi^2 \\ k & = & 7.2 & 6.3 & 5.1 & 3.6 & 0 \end{array}$$

### Literature

- A. G. M. MICHELL, *Phil. Mag.*, 1899, vol. XLVIII.  
 Ludwig PRANDTL, *Kipperscheinungen*, Nürnb., 1899 and Diss. München, 1901.  
 K. G. MELDAHL, *Schiffbautech. Ges. Berl.*, Nov., 1902. — *Ingeniören*, Copenhagen, 1903, p. 331.  
 T. PRESCOTT, *Phil. Mag.*, 6th Ser., vol. XXXVI, 1918, p. 297.  
 H. REISZNER, *Sitz. Ber. d. Berl. Math. Ges.*, III, 1904, p. 53.  
 M. K. GROBER, *Physik. Zeitschr.*, XV, 1914, pp. 460, 889.  
 E. CHWALLA, *Forsch. h. aus d. Geb. d. Stahlb.*, Berlin, 1939, and *Stahlbau*, Bd. 8, p. 46, 1935.  
 S. TIMOSHENKO, *Bull. Polyt. Inst.*, Petersburg, 1905, *Ztschr. f. Math. u. Ph.*, Bd. LVIII, 1910, *Sur la stab. des syst. élast.*, 1910 (*Ann. Ponts et Chaussées*, IV, 1. P., p. 73, Paris, 1913, and *Theory Elast. Stab.*, Lond. and N. Y., 1936, pp. 249, 264, 267).  
 H. WAGNER, *Verdreh. Knick. off. Prof. (Festschr. 25 Jah. T. H. Danz)*, 1929.  
 H. WAGNER u. PRETSCHNER, *Luftf. Forschg.*, Bd. 11, p. 174, Berlin, 1937.  
 R. KAPPUS, *Luftf. Forschg.*, Bd. 14, p. 444, Berlin, 1937.  
 E. E. LUNDQUIST, *Journ. Aeron. Sci.*, vol. 4, No. 6, April, 1947, U. S. A., p. 249.  
 H. NYLANDER, *Die Einw. Aussteif a. Dreh. vorg., etc.*, Diss. Sthlm., 1942.  
 H. HENCKY, *Eisenbau*, 11, 1920, p. 437.  
 F. STÜSSI, *Mém. de l'A. I. P. C.*, vol. 3, p. 401, Zurich, 1935.  
 F. HARTMANN, *Knick. Kipp. Beul.*, Leipzig and Wien, 1937.  
 A. ENGELUND, *Staalkstr.*, I, p. 233, Copenhagen, 1943.  
 K. FEDERHOFER, *Sitzungsber. Akad. Wiss. Wien*, Abt. IIa, Bl. 140, H. 5 u. 6, p. 237, Wien, 1931.

**Résumé**

L'auteur de ce mémoire établit les équations fondamentales de la stabilité au renversement latéral. Il établit des solutions approchées pour différents cas simples, par exemple : charges verticales ou charges normales; l'effet de la poutre elle-même (considérée comme une poutre rectangulaire de faible épaisseur) ou l'effet des semelles; et même l'influence des charges appliquées au-dessus de la ligne des centres. Finalement, l'auteur indique des formules applicables au cas où plusieurs influences agissent simultanément.

**Zusammenfassung**

Es werden die Hauptgleichungen des Kipproblems dargestellt. Eine Näherungslösung wird gefunden, indem eine Reihe von Spezialfällen untersucht wird, wie z.B.: lotrechte Belastung oder Normalkräfte; die Wirkung des Balkens an sich selber (idealisiert als schmaler Rechteckquerschnitt), contra die Wirkung der Flansche und ferner der Einfluss von Kräften, die oberhalb der Verbindungsleitung der Schwerpunkte des Trägers angreifen. Schliesslich werden Formeln angegeben für den Fall, dass mehrere oder alle der Einzelfälle gleichzeitig wirken.

**Summary**

The leading differential equations governing the lateral stability of beams are put forward. An approximate solution is found by dividing the process into a series of "plain cases" such as vertical loading or longitudinal force; further the effect of the beam itself (corresponding to that of a narrow rectangular beam) against the special effect of the flanges; also the effect produced by the loading acting above the centreline of the web. Finally, formulae are produced giving the joint effect of several or all "plain cases" acting simultaneously.

**Leere Seite**  
**Blank page**  
**Page vide**