Zeitschrift:	IABSE congress report = Rapport du congrès AIPC = IVBH Kongressbericht
Band:	5 (1956)
Artikel:	The behaviour of a symmetrical piched roof portal loaded to collapse
Autor:	Horne, M.R.
DOI:	https://doi.org/10.5169/seals-6080

### Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. <u>Mehr erfahren</u>

### **Conditions d'utilisation**

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. <u>En savoir plus</u>

### Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. <u>Find out more</u>

### Download PDF: 11.08.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch

# I a 3

## The behaviour of a symmetrical pitched roof portal loaded to collapse Discussion

# Das Verhalten eines symmestrischen Portalrahmens mit geneigten Dachflächen bei einer Beanspruchung die um zum Bruch führt Diskussion

Ensaio de rotura de um pórtico simétrico de duas águas Discussão

## Essai à la rupture d'un portique symétrique à deux pans Discussion

# M. R. HORNE Sc. D., A. M. I. C. E. Cambridge University Cambridge

The authors give the calculated deflections of their portal frame when it is just on the point of collapse, obtained by the method described by Symonds and Neal [9]. In practice, it may be of greater interest to be able to calculate the deflections before this stage is reached, but after plastic deformation has occurred at certain sections. Unfortunately, such calculations are difficult, since it is not known *a priori* at which sections plastic hinges occur at a given load. Hence several analyses may have to be made before the correct solution is obtained. It is thus desirable to use a rapid method for setting down the equations for the general case, making no assumptions regarding the positions of the hinges. A convenient procedure based on an adaptation of the elastic traverse method of analysis [10] will be described, and illustrated by reference to the portal frame discussed by Baker and Eickhoff.

The principle of the traverse method for elastic members is shown in Fig. 1 (b). The prismatic member AB [Fig. 1 (a)] is subjected to transverse loads, together with terminal moments  $M_A$  and  $M_B$ . The actual deformation of the centre line may be replaced by two angular discontinuities at the third points, as shown in Fig. 1 (b). The values of the discontinuities are  $-\frac{1}{2 \text{ E I}}(M_A - M_{FA})$  and  $-\frac{1}{2 \text{ E I}}(M_B - M_{FB})$  where  $M_{FA}$  and  $M_{FB}$  are the fixed-end moments due to the transverse loads, 1 is the length of the member, and E I is its flexural rigidity.

Suppose that the bending moment at some point C in the member, distance x from A, reaches the full plastic value M<sub>P</sub> [Fig. 1 (c)]. It will



be assumed that the shape factor of the member is unity, so that all plastic deformation is confined to the sections at which full plasticity occurs. The total deformation of the member then includes a plastic hinge rotation  $\theta_{\rm C}$  [Fig. 1 (d)], and this must be added to the usual angular discontinuities corresponding to elastic flexure to obtain the total equivalent deformation [Fig. 1 (e)]. In general, it will be sufficiently accurate to add the plastic hinge rotation  $\theta_{\rm C}$  to the nearest third point of the member (including the ends), thus simplifying the calculations when the member forms part of a rigid frame.

The generalised rotations which are assumed when analysing the pitched roof frame described by Baker and Eickhoff are shown in Fig. 2. Since the loads W and H are applied at joints, no fixed-end moments



O ELASTIC FLEXURE ROTATIONS.

• POTENTIAL PLASTIC HINGES .

FIG. 2

occur in the expressions for the elastic flexure rotations. The bending moments at A, B etc. are denoted by  $M_A$ .  $M_B$ . etc., moments being accounted positive when they produce tension on the inside of the frame. Potential plastic hinge positions are at the five joints, and arbitrary rotations  $\theta_A$ ,  $\theta_B$ , etc. are ascribed to these sections. These rotations are accounted positive when they produce deformation convex to the inside of the frame. The symbols E I<sub>1</sub> and E I<sub>2</sub> denote the flexural rigidities of the frame and base beam respectively, 1 is the span, h<sub>1</sub> the height to eaves, h<sub>2</sub> the height from eaves to apex, and s is the length of a rafter.

The requirements of frame continuity lead to three equations, as shown in Fig. 3. Taking l = 192 inches,  $h_1 = 96$  inches,  $h_2 = 37.2$  inches, s = 102.9 inches,  $E I_1 = 5.73 \times 10^5$  tons inches and  $E I_2 =$ 

 $=34.0\times10^{_5}$  tons inches, and expressing the bending moments in tons inches, the equations become

$$0.645 \text{ M}_{A} + \text{M}_{B} + 1.035 \text{ M}_{D} + \text{M}_{F} + 0.645 \text{ M}_{G} + 5.76 \times 10^{3} (\theta_{A} + \theta_{B} + \theta_{D} + \theta_{F} + \theta_{G}) = 0$$
(1)

$$0.649 \text{ M}_{A} + \text{M}_{B} - \text{M}_{F} = 0.649 \text{ M}_{G}$$
  
+ 6.96×10<sup>3</sup> ( $\theta_{A} + \theta_{B} - \theta_{F} - \theta_{G}$ ) = 0 (2)

$$1.525 \text{ M}_{A} + \text{M}_{B} + 0.278 \text{ M}_{D} + \text{M}_{F} + 1.525 \text{ M}_{G} + 4.64 \times 10^{3} (3.58 \theta_{A} + \theta_{B} + \theta_{F} + 3.58 \theta_{G}) = 0$$
(3)

In addition to these equations, there are two equations of equilibrium relating the bending moments to the applied loads. These may be obtained



by considering the virtual work equations for two independent mechanisms, as shown in Fig. 4. When numerical values for dimensions are inserted, it is found that

$$-M_{A} + M_{B} - M_{F} + M_{G} = 96 H$$
(4)

$$-M_{B}+2M_{D}-1.775M_{F}+0.775M_{G}=96W+74.4H$$
 (5)

The above five equations are sufficient to determine all the moments and rotations at any given values of W and H.

193

At each joint in the frame, there is either no plastic hinge and the members are elastic, that is

$$\theta = 0$$
 and  $-M_P < M < M_P$ 

or full plasticity occurs, in which case,

if 0 > 0, then  $\mathbf{M} = \mathbf{M}_{P}$  and if 0 < 0, then  $\mathbf{M} = -\mathbf{M}_{P}$ .

Hence, whatever the loads, there are five unknown numerical quantities. When performing an analysis, the assumption has to be made regarding



which joints have become fully plastic. The correct assumptions will lead to a solution in which all the above inequalities are satisfield. It is evident that a moment in excess of  $M_P$  denotes a hinge position where none has been assumed, while a hinge rotation of the wrong sign denotes that a hinge has been inserted where the frame is actually still elastic. The correct solution may thus be obtained by trial and error, or alternatively by tracing the formation of the hinges as the loads are increased.

13

The solutions of equations (1) to (5) for the pitched roof frame of Baker and Eickhoff are summarised in Table I for each load at which a new plastic hinge just forms. The theoretical and experimental load deflection relations are compared in Fig. 5, the loads at which the various sections first become plastic being indicated. The theoretical deflections are less than the actual values, due presumably to

- 1) the incomplete rigidity of the joints, and
- 2) the spreading of the plastic zones either side of the fully plastic sections.

The calculated deflections at the point of collapse are in agreement with the authors' values. It is interesting to note that, whereas the



FIG. 5. Experimental and theoretical deflections of portal frame

order in which the resin cracks were observed was F, B, D, G, the theoretical order for the formation of the plastic hinges was D, F, B, G. The late recording of yield at D may have been due to the difficulties of observation (see Fig. 4 of authors' paper), and it is probable that yield did occur first at that section.

# TABLE I

Horizontal Load H (tons)		1.70	1.70	1.70	1.70	1.70
Vertical Load V (tons)		0	11.02	11.66	12.93	12.95
Positions of Plastic Hinges		-	D	D.F	D, F, B,	D, F, B, G
Bending Moments (Tons. Inches)	M <sub>A</sub>	- 43.5	56.7	69.0	81.0	83.8
	Мв	21.0	- 164.2	- 182.9	- 247.0	- 247.0
	Мъ	13 9	247.0	247.0	247.0	247.0
(Tons Thenes)	M <sub>F</sub>	- 43.2	- 228.4	- 247.0	- 247.0	- 247.0
	M G	55.5	155.7	168-0	244.0	247.0
	θΑ	0	0	0	0	0
	Øв	0	0	0	0	- 0.92
Hinge Rotations (Radians × 10 - <sup>2</sup> )	θD	0	0	3.74	20.12	21.38
	ØF	0	0	0	- 15.14	- 16.14
	ØG	0	0	0	0	0
Vertical Deflection at D (inches)		0.049	0.857	0.983	1.678	1.736
Horizontal Deflection at B (inches)		0.206	- 0.107	-0.156	-0.140	-0.162
Horizontal Deflection at F (inches)		0.243	0.556	0.605	1.161	1.185

Summary of elastic-plastic analysis for pitched portal frames

### REFERENCES

10. STEWART, R. W. — Analysis of Continuous Structures by Traversing the Elastic Curves. Trans. Amer. Soc. Civ. Engrs. 1936. Vol. 101, p. 105.

### SUMMARY

The elastic traverse method of structural analysis is adapted to the calculation of deflections in rigid-jointed elastic-plastic structures at all stages up to plastic collapse. Theoretical results are obtained for the portal frame described by Baker and Eickhoff, and are compared with the experimental values.

### ZUSAMMENFASSUNG

Die elastische Methode der Baustatik wird auf die Berechnung der Durchbiegungen von elastisch- plastichen Konstruktionen mit biegesteifen Stössen auf allen Stufen bis zum plastischen Bruchzustand angewendet. Die theoretischen Ergebnisse für einen Portalrahmen werden verglichen mit den experimentellen Werten.

#### RESUMO

Aplica-se o método de cálculo elástico à determinação das flechas de estruturas elasto-plásticas com nós rigidos em todos os estados de equilíbrio até à rotura plástica. Comparam-se os resultados teóricos obtidos para o pórtico descrito por Baker e Eickhoff com os valores experimentais correspondentes.

### RÉSUMÉ

Les auteurs appliquent la méthode de calcul élastique à la détermination des flèches de charpentes elasto-plastiques à noeuds rigides dans tous les stades d'équilibre jusqu'à la rupture plastique. Ils comparent les résultats théoriques obtenus pour le portique décrit par Baker et Eickhoff avec les valeurs expérimentales correspondantes.