

**Zeitschrift:** IABSE congress report = Rapport du congrès AIPC = IVBH  
Kongressbericht

**Band:** 10 (1976)

**Artikel:** Prepondernace of idealization in strucutral optimization

**Autor:** Maquoi, René / Rondal, Jacques

**DOI:** <https://doi.org/10.5169/seals-10508>

#### Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

#### Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

#### Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

**Download PDF:** 08.08.2025

**ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>**

### Preponderance of Idealization in Structural Optimization

Prépondérance de l'idéalisation dans les problèmes d'optimisation structurale

Die überragende Bedeutung der Idealisierungen bei der Optimierung von Tragwerken

RENÉ MAQUOI

National Foundation for Belgian Scientific Research  
(F.N.R.S.)  
Liège, Belgium

JACQUES RONDAL

Assistant  
University of Liège  
Liège, Belgium

The optimal design of a structure may be divided in two steps.

In the first one - the *idealization* - the structural problem is put in following mathematical formulation :

→

"Find  $X$  such that :

$$\begin{aligned} \stackrel{\rightarrow}{f_k}(X) &< 0 \quad \text{for } k = 1, 2, \dots, m ; \\ \stackrel{\rightarrow}{h_j}(X) &= 0 \quad \text{for } j = 1, 2, \dots, l ; \end{aligned} \tag{1}$$

and :

→

$$F(X) = \text{minimum (maximum)}$$

where  $X$  is a vector which contains the design variables,

$f$  and  $h$  are the constraints of the problem,

and  $F$  is the objective function to optimize.

The second step - the *solution process* implies (a) the choice of the solving procedure and (b) the search of the solution of the problem formulated as in (1).

In the opinion of the authors, a good idealization is the basic condition for obtaining a good value of the solution, while a more or less refined mathematical treatment of it plays a rather secondary role [1].

In many papers of the literature, emphasis is too often brought on the choice of the solution procedure rather than on that of a heuristic which does not modify in anyway the sense of the actual problem.

So long as the structural problem is small - about ten variables and constraints - many methods are available in the literature. However, various numerical experiments have shown that the choice of a method depends on the problem to be solved, for most of the algorithms cannot be used economically in all cases [2]. As a consequence, conclusions concerning the use range and the efficiency of an algorithm for a structural problem can rarely be extended to another one.

If emphasis is almost brought on the idealization, the designer may be sure of obtaining a realistic solution of the problem and, in addition, important simplifications in the mathematical treatment of the second step become possible. Indeed, on one way, a judicious choice of variables or an ingenious variable transformation often enable to present the complex problem in a more simple form, and, on another way, by means of a previous evaluation of the several variables, the designer can establish a hierarchy of the variables and divide the complex problem into smaller ones, which are then more easier to solve quickly.

For example, in [3], MYLANDER demonstrates that a rather simple variable transformation changes a mathematical non-linear and non-convex problem into a linear programming system. It is worthwhile to recall the following basic non-linear problem which is considered as a very difficult one. The objective function is :

$$f(x) = b_0 + a_{01} x_1 + \left( \sum_{j=2}^5 a_{0j} x_j \right) x_1 \rightarrow \min$$

subject to constraints :

$$0 < a_{i1} x_1 + \left( \sum_{j=2}^5 a_{ij} x_j \right) x_1 < b_i \quad i = 1, 2, 3 \quad (2)$$

$$x_1 > 0 ; 1.2 < x_2 < 2.4 ; 20.0 < x_3 < 60$$

$$9.0 < x_4 < 9.3 ; 6.5 < x_5 < 7.0.$$

where the values of the constants are :

$a_{01}$	= -	8,720,288.795	$a_{21}$	= -	155,011.1055
$a_{02}$	= -	150,512.524	$a_{22}$	=	4,360.5334
$a_{03}$	= -	156.695	$a_{23}$	=	12.9492
$a_{04}$	= -	476,470.319	$a_{24}$	=	10,236.8839
$a_{05}$	= -	729,482.825	$a_{25}$	=	13,176.7859
$a_{11}$	= -	145,421.4004	$a_{31}$	= -	326,669.5059
$a_{12}$	=	2,931.1506	$a_{32}$	=	7,390.6840
$a_{13}$	= -	40.4279	$a_{33}$	= -	27.8987
$a_{14}$	=	5,106.1920	$a_{34}$	=	16,643.0759
$a_{15}$	=	15,711.3600	$a_{35}$	=	30,988.1459
$b_0$	= -	24,345.0	$b_2$	=	294,000.0
$b_1$	=	294,000.0	$b_3$	=	277,200.0

By putting, according to MYLANDER

$$y_i = x_1 \cdot x_i \quad i = 2, 3, 4, 5$$

and

$$y_1 = x_1$$

above non-linear problem takes following linear formulation :

$$\begin{aligned} g(y) &= b_0 + \sum_{j=1}^5 a_{0j} y_j \rightarrow \min \\ 0 &< \sum_{j=1}^5 a_{ij} y_j \leq b_i \quad i = 1, 2, 3 \\ y_i &\geq 0 \quad i = 1, 2, \dots, 5 \end{aligned} \quad (5)$$

$$\begin{aligned}
 y_2 - 1.2 y_1 &\geq 0 ; \quad 2.4 y_1 - y_2 \geq 0 \\
 y_3 - 20.0 y_1 &\geq 0 ; \quad 60.0 y_1 - y_3 \geq 0 \\
 y_4 - 9.0 y_1 &\geq 0 ; \quad 9.3 y_1 - y_4 \geq 0 \\
 y_5 - 6.5 y_1 &\geq 0 ; \quad 7.0 y_1 - y_5 \geq 0 .
 \end{aligned}$$

which may directly solved by means of the classical simplex routine.

The optimal solution, obtained after six iterations, is given by :

$$g = - 5,280,344.9$$

$$\begin{aligned}
 y_1 &= 4.53743 ; \quad y_2 = 10.88983 ; \quad y_3 = 272.24584 \\
 y_4 &= 42.19811 ; \quad y_5 = 31.76202
 \end{aligned} \tag{6}$$

which in terms of the original variables gives  $f = - 5,280,344.9$

$$\begin{aligned}
 x_1 &= 4.53743 ; \quad x_2 = 2.40000 ; \quad x_3 = 60.00000 \\
 x_4 &= 9.30000 ; \quad x_5 = 7.00000 .
 \end{aligned} \tag{7}$$

The solution of the original problem by means of non-linear programming methods [4, 5] lead, after a lot of iterations, to values of  $f$  which are 2 or 3 % below the true optimum but, in some cases, with value of the variable  $x_3$  which is about 50 % erroneous.

In [6], the authors show how a suitable choice of the behaviour model for a complex structural design - indeterminate prestressed bridges - leads to a benefit similar to that obtained by MYLANDER.

The idealization of the problem is based on an approach with sensitivity coefficients, as that proposed by GURUJEE [7], and on a variable transformation; it is then allowed to solve this complex design problem by means of linear programming, without the actual problem be denatured and taking account of all the technological requirements (cover thickness, anchorage dimensions, redundant effects of prestressing, friction losses, anchorage slippage,...). After the variable transformation, the problem remains partially non-linear but the authors have shown in [8] that the non-linear term, being of the order of 1 % with respect to its corresponding linear component, may be neglected in practice.

The authors would like to conclude by saying that for optimum design, as for all the other engineering activities, mathematics are a good servant but a bad master.

## REFERENCES.

1. C. MASSONNET and J. RONDAL : Structural Mechanics and Optimization.  
16th Solid Mechanics Conference, Krynica, Poland, August 1974.
2. A.B. TEMPLEMAN : Optimization Concepts and Techniques in Structural Design.  
IABSE, Tenth Congress, Introductory Report, Tokyo, September 1976.
3. W.C. MYLANDER : Nonlinear Programming Test Problems.  
The Computer Journal, Vol. 8, N° 4, January 1966.

4. H.H. ROSEN BROCK : An Automatic Method for Finding the Greatest or Least value of a function. The Computer Journal, Vol. 3, p.175, 1960.
5. M.J. BOX : A New Method of Constrained Optimization and a Comparison with other Methods. The Computer Journal, Vol. 8, N° 1, April 1965.
6. R. MAQUOI and J. RONDAL : Optimal Layout of Cables in Prestressed Indeterminate Bridges. 18th Solid Mechanics Conference, Wista, Poland, September 1976.
7. C.S. GURUJEE : Structural Optimization through Sensitivity Coefficients. IABSE Tenth Congress, Preliminary Report, Tokyo, September 1976.
8. R. MAQUOI and J. RONDAL : Approche réaliste du dimensionnement optimal des ponts précontraints hyperstatiques. To be published in Annales des Travaux Publics de Belgique, Bruxelles.

#### SUMMARY

In structural optimization problems, it is nearly always observed that, in the search for a realistic solution, the suitability of idealization is more important than the choice of the solving algorithm.

#### RESUME

Dans les problèmes de dimensionnement optimal, il est généralement constaté que la recherche d'une solution réaliste dépend davantage de l'idéalisierung du problème que du choix de l'algorithme de résolution.

#### ZUSAMMENFASSUNG

Bei der Optimierung von Tragwerken wird allgemein festgestellt, dass die Suche nach einer realistischen Lösung mehr von der Idealisierung des Problems als von der Auswahl des Lösungsalgoritmus abhängt.