

Zeitschrift: IABSE congress report = Rapport du congrès AIPC = IVBH
Kongressbericht

Band: 12 (1984)

Artikel: Innovative design for main towers of long span suspension bridges

Autor: Nakayama, Yoshiaki

DOI: <https://doi.org/10.5169/seals-12259>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 10.08.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



Innovative Design for Main Towers of Long Span Suspension Bridges

Yoshiaki NAKAYAMA

Nippon Kokan K.K.
Tokyo, Japan

Erection of main shaft

Generally speaking, when larger unit blocks are used to reduce the construction period of a main shaft or to speed up the work, not only is the unit weight increased but also larger manufacturing, transportation and erection equipment or facilities are required. The larger erection cranes (creeper cranes) which become necessary, in particular, will prove to be inconvenient.

It is proposed that the construction period be reduced by assigning many general-purpose cranes of relatively small capacity to each main shaft (for example, four 30t jib cranes for each main shaft).

As sufficient flexibility can be obtained by selecting an appropriate rigidity ratio for columns and beams even if a slender shaft is used, a wider space which makes the work easier is produced.

Top saddle

The vertical loads of main cables concentrated on the center of the saddle must be distributed on the columns around a main shaft. If a saddle beam of which the supporting point is on the periphery of a main shaft is used instead of a saddle and several cross beams made of steel plates are installed at right angles to the saddle beam to support it, the reaction forces of the saddle beam made of steel plates are installed at right angles to the saddle beam to support it, the reaction forces of the saddle beam are transferred to the periphery of the main shaft. In this case, it is necessary to distribute uniformly the reaction forces of the saddle beam on the periphery of the main shaft through the cross beam. This can be made possible by changing the size of the cambers which are fitted to the cross beams --- larger cambers near the periphery of the main shaft and smaller ones near the center of the cross beam.

Observation tower

As the inside of the main shaft is very large, it may be used as an observation tower, leisure facility, or for some other purpose.

Struts and its connection


Although the width of a strut is necessarily large to match the width of the main shaft, struts should be of a rigid frame structure. When members are connected, the transmission of each members stress must be made certain.

Components of main shaft


The main members constituting a main shaft are called columns or column members. Since heavy H-shaped steel sections for columns are used as main members.

As the vertical loads of main cables working on the top saddles of a long span suspension bridge are very large, columns with a large cross-section are necessary. Some catalogue size typical heavy H-shaped steel sections for columns are used.


DESIGN OF MAIN TOWER FOR LONG SPAN SUSPENSION BRIDGE



(C) OBSERVATION TOWER




(B) TOP SADDLE




(G) CHARACTERISTICS OF FRAME STRUCTURE
EQUIVALENT TORSIONAL RIGIDITY OF FRAMES






(D) STRUTS AND ITS CONNECTION



EQUIVALENT FLEXURAL RIGIDITY OF FRAMES



(E) COMPONENTS OF MAIN SHAFT



(F) SHAFT BASE (A) ERECTION OF MAIN SHAFT