

**Zeitschrift:** IABSE congress report = Rapport du congrès AIPC = IVBH  
Kongressbericht

**Band:** 12 (1984)

**Rubrik:** Poster session 6: Concrete structures

### **Nutzungsbedingungen**

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

### **Conditions d'utilisation**

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

### **Terms of use**

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

**Download PDF:** 13.01.2026

**ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>**



## **POSTER SESSION 6**

**Concrete Structures**

**Structures en béton**

**Betontragwerke**

Coordinator: R.S. Stilwell, Canada



## New Column for Tall Reinforced Concrete Buildings

Kiyoshi MUTO, Kuniaki SATO, Satoshi BESSHO  
Minoru FUKUSHIMA et al.  
Kajima Corporation  
Tokyo, Japan

A twenty-five story condominium constructed by Kajima Corp. is the highest reinforced concrete building in Japan, meeting the structural requirements for earthquake resistance. However, demand for the construction of taller buildings, particularly in urban reconstruction, is increasing. Therefore it has become necessary to develop new structural systems, especially a column system applicable to high-rise buildings taking into account earthquake resistance, economy and execution of works.

Now, in the twenty-five story condominium, the special lateral reinforcement which combines a circular spiral hoop and conventional lateral hoop is used. Since the concrete is effectively restrained by this special lateral reinforcement, it was proved that the restoring force is slightly reduced by cyclic lateral loading as shown in Fig.2.

So, for 30~40 story buildings, we have devised a new column system using high-strength concrete, small-size H-shaped steel and special lateral reinforcements, as shown in Fig.1.

And many specimens were tested to investigate the structural characteristics of the column system. The central compressive force was applied to test specimens as shown in Fig.3. As a result of this test, the maximum load capacity and its reduction ratio for the KS-type column compared to the central compressive force are the same or more than those for the conventional H-type column which uses H-shaped steel with a large sectional area.

The bending and shearing force was applied to test specimens as shown in Fig.4. As a result of these tests, the special lateral reinforcement is superior to the conventional lateral reinforcement on the capacity of restoring force after the maximum load. And the load capacity and ductility of this column are sufficient performance comparing with the conventional column under high compressive or tensile axial load. In addition, this new column has restoring characteristics regardless of the internal H-shaped steel load direction.

As a result of our research, design range of the column has been setting up like Fig.5. And the construction of economical forty-story buildings has been made possible.

# NEW COLUMN FOR TALL REINFORCED CONCRETE BUILDINGS

## BACKGROUND

In Japan, demand for the construction of 30~40 story condominium is growing. So it has become necessary to develop new column system taking into account earthquake resistance, economy and execution of works.




Fig.1 Newly Devised Column




Fig.2 Effects of Special Lateral Reinforcements on Restoring Force for Cyclic Loading

## RESEARCH AND DEVELOPMENT





Fig.3 Axial Loading Tests







Fig.4 Bending and Shear Tests under Constant Axial Load

## DESIGN




Fig.5 Design range of Column




Fig.6 Perspective of First Building in which System to be Applied



**Cable Stays for Bridges**

**H. SCHAMBECK**

Civil Eng.  
Dyckerhoff & Widmann  
München, FR Germany

DYWIDAG POSTTENSIONING SYSTEMS

| Type of steel | Steel grade | (mm) | Nominal ultimate load kN |     |     |      |      | Bell anchorage | OR plate anchorage | Square ribbed plate anchorage | Rectangular ribbed pl. anchorage | Square solid plate anchorage | Rectangular solid plate anchorage | LO-plate anchorage | Ring plate anchorage | Multi area anchorage | Bond head anchorage | Loop anchorage | Coupler (movable) | Coupler (fixed) | Unbonded tendon |      |
|---------------|-------------|------|--------------------------|-----|-----|------|------|----------------|--------------------|-------------------------------|----------------------------------|------------------------------|-----------------------------------|--------------------|----------------------|----------------------|---------------------|----------------|-------------------|-----------------|-----------------|------|
|               |             |      | 100                      | 200 | 400 | 1000 | 2000 |                |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                |                   |                 |                 | 5000 |
| Smooth bar    | 1420/1570   | 10   | ●                        |     |     |      |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
|               |             | 12,2 | ●                        |     |     |      |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
|               | 835/1230    | 26   |                          | ●   |     |      |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
|               |             | 32   |                          |     | ●   |      |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
|               |             | 36   |                          |     |     | ●    |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
|               | 1080/1230   | 26   |                          |     | ●   |      |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
| 32            |             |      |                          |     | ●   |      | ●    |                |                    |                               |                                  |                              |                                   |                    |                      |                      |                     | ●              | ●                 | ●               |                 |      |
| 36            |             |      |                          |     |     | ●    | ●    |                |                    |                               |                                  |                              |                                   |                    |                      |                      |                     | ●              | ●                 | ●               |                 |      |
| Thread bar    | 885/1080    | 15   |                          | ●   |     |      |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
|               |             | 16   |                          |     | ●   |      |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
|               | 835/1030    | 26,5 |                          |     | ●   |      |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
|               |             | 32   |                          |     |     | ●    |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
|               |             | 36   |                          |     |     |      | ●    | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
|               | 1080/1230   | 26,5 |                          |     | ●   |      |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
| 32            |             |      |                          |     | ●   |      | ●    |                |                    |                               |                                  |                              |                                   |                    |                      |                      |                     | ●              | ●                 | ●               |                 |      |
| 36            |             |      |                          |     |     | ●    | ●    |                |                    |                               |                                  |                              |                                   |                    |                      |                      |                     | ●              | ●                 | ●               |                 |      |
| Strand        | 1570/1770   | 10,6 |                          | ●   |     |      |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
|               |             | 3    |                          |     | ●   |      |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
|               |             | 4    |                          |     |     | ●    |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                | ●                 | ●               | ●               |      |
|               |             | 5    |                          |     |     | ●    |      | ●              |                    |                               |                                  |                              |                                   |                    |                      |                      |                     |                |                   | ●               | ●               | ●    |
|               |             | 7    |                          |     |     |      | ●    |                | ●                  |                               |                                  |                              |                                   |                    |                      |                      |                     |                |                   | ●               | ●               | ●    |
|               |             | 9    |                          |     |     |      |      | ●              |                    | ●                             |                                  |                              |                                   |                    |                      |                      |                     |                |                   | ●               | ●               | ●    |
|               |             | 11   |                          |     |     |      |      |                | ●                  |                               |                                  |                              |                                   |                    |                      |                      |                     |                |                   | ●               | ●               | ●    |
|               |             | 12   |                          |     |     |      |      |                |                    | ●                             |                                  |                              |                                   |                    |                      |                      |                     |                |                   | ●               | ●               | ●    |
| 15            |             |      |                          |     |     |      |      |                | ●                  |                               |                                  |                              |                                   |                    |                      |                      |                     | ●              | ●                 | ●               |                 |      |
| 19            |             |      |                          |     |     |      |      |                |                    | ●                             |                                  |                              |                                   |                    |                      |                      |                     | ●              | ●                 | ●               |                 |      |

DYWIDAG CABLES

| Cable type   | STRAND CABLE   | BAR CABLE   |
|--|--|---|
| <b>LOAD BEARING</b><br>1 CABLE (Static+Dynamic)    | STRAND (7-wire stress-relieved)<br>Grade St 1570/1770<br>Diameter 0,6" (Low relaxation)                        | THREADED BARS   STEEL TUBES<br>Grade St 835/1030   Grade St 37<br>Dia. 32, 36 mm   (DIN 17 100) |
| <b>2 ANCHORAGE</b><br>Static<br>Dynamic<br>Bending | WEDGE ANCHORAGE<br>Combined WEDGE+BOND ANCHOR<br>STEEL TUBES   | NUT ANCHORAGE<br>BOND ANCHORAGE<br>STEEL TUBES  |
| <b>CORROSION PROTECTION</b>                        | Multiple anti-corrosion barriers to meet different requirements<br>eg SHEATHING, GROUT, COATING OF STRANDS etc | eg STEEL TUBES, GROUT etc   |
| <b>PRESTRESSING</b>                                | SINGLE and MULTIPLE STRAND-JACKS   | SINGLE BAR-JACKS  |
| <b>CABLE ERECTION</b>                              | Different procedures to fit into various construction demands<br>eg Erection on site, Prefabrication           |   |
| <b>ADDITIONAL FEATURES</b>                         | FULLY REPLACABLE<br>ADJUSTABLE before and after grouting   | REPLACABLE<br>ADJUSTABLE before grouting  |

# CABLE STAYS FOR BRIDGES

| CABLE STAYS  |  | EXAMPLES (STRUCTURE AND CONSTRUCTION METHOD)   |   |  |  |
|--|--|--|---|--|--|
| <p><b>PRESTRESSED CONCRETE</b></p> <p><b>TYPICAL CROSS SECTION</b><br/>           CONCRETE GRADE B 45-160/135 CM<br/>           56 STRANDS TENDONS-19 <math>\phi</math> 0,6<br/>           STIRRUP<br/>           PROTECTIVE CONCR. LAYER WITH ADDIT. REINFORCEMENT IN VEHICLE IMPACT ZONE OF THE CONCRETE STAY<br/>           CONSTRUCTION ON SCAFFOLDING WITH POST-TENSIONED PRESTRESSING</p> <p><b>STRUCTURAL CRITERIA</b><br/>           THE CONCR. STAY IS DESIGNED AS BEAM WITH FIXED ENDS STRESSED BY AXIAL TENSION FORCE AND STRESSED BY BENDING MOMENTS DUE TO DEAD WEIGHT OF STAY AND DUE TO WIND LOAD<br/>           CHECK OF STRESSES FOR PRESTR. CONCRETE MEMBERS ACC. TO GERMAN CODE DIN 4227</p> <p><b>CHARACTERISTICS</b><br/>           - ALLOW TENS. FORCE/SQM OF CONCR. STAY-55 MN<br/>           - UNIFORM PRESTR. CONCR. DESIGN FOR TOTAL STRUCTURE INCL. STAY AND ANCHOR BLOCK<br/>           - STRUCTURE WITH SMALL DEFLECTIONS<br/>           - PERFECT PROTECTION AGAINST CORROSION<br/>           - RELIABLE RESISTANCE AGAINST VEHICLE IMPACT AND SIMILAR DAMAGES<br/>           - NO MAINTENANCE<br/>           - POSSIBILITIES FOR INDIVID. ARCHITECT. DESIGN<br/>           - LIM. OF GIRDER SPAN AT 250 M APPROX. DUE TO DEAD WEIGHT OF CONCRETE STAY</p> | <p><b>DANUBE RIVER BRIDGE, METTEN, FRG.</b></p> <p>ELEVATION<br/>145,0<br/>30,0<br/>DETAIL C'<br/>DETAIL D'<br/>DETAIL E-E</p>   | <p><b>CONSTRUCTION STAGES</b></p> <p>INCREMENTAL LAUNCHING<br/>CASTING OF STAY ON SCAFFOLDING</p>  |   |  |  |
|  |  | <p><b>FLOSSER BRIDGE, FRANKFURT/M. FRG.</b></p> <p>ELEVATION<br/>106,5<br/>20,4<br/>DETAIL A'<br/>DETAIL B-B<br/>DETAIL C-C</p>  | <p><b>CONSTRUCTION STAGES</b></p> <p>FREE CANTILEVER WITH TEMPORARY STEEL CABLES<br/>CASTING OF STAY ON SCAFFOLDING<br/>ARRANGEM. OF FREE CANTILEVER SEGMENTS</p> |  |  |
|  |  | <p><b>DESIGN WITH CABLE STAYS ARRANGED BELOW GIRDER</b></p> <p>ELEVATION<br/>98,8</p>  | <p><b>CONSTRUCTION STAGES</b></p> <p>SIMULTANEOUS SEGMENTAL CONSTRUCTION</p>  |  |  |
|  |  | <p><b>MAIN RIVER BRIDGE, HOECHST AG, FRG.</b></p> <p>ELEVATION<br/>148,2<br/>30,9<br/>ANCHORAGE IN GIRDER<br/>ANCHORAGE IN TOWER<br/>TOP VIEW<br/>C-C<br/>D-D</p>                          | <p><b>CONSTRUCTION STAGES</b></p> <p>SIMULTANEOUS SEGMENTAL CONSTRUCTION</p>  |  |  |
| <p><b>PRESTRESSING STEEL</b></p> <p><b>COMPOSITE CROSS SECTION</b><br/>           WIRES ST 1325/1470, DIA. 16 MM (W)<br/>           + STEEL TUBE (ST)</p> <p><b>FIXED END: STEEL TUBE WITH INCREASED WALL THICKNESS</b></p> <p><b>LOAD TRANSFER AT ANCHORAGE:</b><br/>           DEAD LOAD VIA THREADS OF WIRE (I)<br/>           FATIGUE LOADS VIA BOND ANCHORAGE ZONE II</p>   | <p><b>PENANG BRIDGE, MALAYSIA</b></p> <p>ELEVATION<br/>107,5<br/>225,0<br/>107,5<br/>25,3<br/>ANCHORAGE IN GIRDER<br/>ANCHORAGE IN TOWER<br/>TOP VIEW<br/>A-A</p>  | <p><b>CONSTRUCTION STAGES</b></p> <p>SEGMENTAL CONSTRUCTION</p>  |   |  |  |
|  | <p><b>COMPOSITE CROSS SECTION:</b><br/>           STRANDS ST 1580/1860, DIA. 0,6 (S)</p> <p><b>FIXED END: ANCHOR STEEL TUBE</b></p> <p><b>LOAD TRANSFER AT ANCHORAGE:</b><br/>           DEAD LOAD VIA WEDGES OF STRANDS (I)<br/>           FATIGUE LOADS VIA BOND ANCHORAGE ZONE II</p> | <p><b>FA ROUTE 63 OVER MISSISSIPPI RIVER QUINCY, ILLINOIS, U.S.A.</b></p> <p>ELEVATION<br/>134,1<br/>274,3<br/>134,1<br/>ANCHORAGE IN GIRDER<br/>ANCHORAGE IN TOWER<br/>CONSTR. STAGES</p> | <p><b>CONSTRUCTION STAGES</b></p> <p>CONSTR. STAGES</p>   |  |  |



## Rehabilitation of Post-Tensioned Bridge Deck

**Klaus H. OSTENFELD**

Head of Bridge Dep.  
Cowiconsult

Virum, Denmark

**Leif JONSEN**

Chief Bridge Eng.  
Cowiconsult

Virum, Denmark

The bridge was constructed in 1967 and hereafter regular routine inspections were carried out. In 1981 a major examination took place. Larger zones of deteriorated concrete were found in one of the cantilevered flanges, especially in areas near the abutments.

The bridge deck surface has a cross slope of 6% and consequently damage had only taken place in the lower cantilever, and fortunately not in the central part of the girder where the longitudinal main tendons are positioned. This distribution of the damage made repair possible. A full replacement of the superstructure would have resulted in an expenditure of more than 250% of the repair cost and almost total closure of one of the major motorways in Denmark.

The deterioration had started due to a leak in the waterproofing membrane. Unfortunately, the underneath concrete was not resistant against alkaline reactions.

- \* - \* - \* - \* - \* -

After removal of the bridge deck pavement and water proofing, the deteriorated areas were surveyed by core drilling.

The deteriorated concrete was removed, however, in such a way that the reinforcement and prestressing tendons were not harmed. In this context it was very important that the transverse prestressing in the cantilevers could be reestablished. The transverse prestressing tendons consist of 12 dia. 5 mm wires. In order to protect these wires, the original sheath and grout were not removed until just before the new sheathing was ready to be installed. As it can be seen from the original transverse tendon arrangement, it was not possible to reuse the existing anchorages.


A new system was developed by Skandinavisk Spændbeton. A simple bar anchorage with thread and nut was connected to the wires. The details are shown on the poster. After casting the deck the wires were re-stressed and grouted.

Due to the repair work the longitudinal prestressing forces were lost in the cantilever. Consequently, it was necessary to place some additional ordinary reinforcement in the longitudinal direction, especially at the end of the bridge deck.

# REHABILITATION OF POST-TENSIONED BRIDGE DECK

## Bridge data

Year of construction: 1967  
 Year of repair: 1982  
 Post-tensioned concrete superstructure:  
 Ultimate cylinder strength,  $\sigma_c \geq 45$  MPa  
 Longitudinal prestressing:  
 12 x 0.5 strands, grade 160/180  
 Transverse prestressing:  
 12 x 5 mm wires, grade 150/170  
 System Freyssinet  
 New waterproofing and pavement:




Bridge before repair




Deteriorated concrete has been removed


## Motorway Bridge, Denmark



Plan




Plan section



Existing transverse and longitudinal prestressing. The 12 x 5 mm transverse prestressing wires were re-used, but cut off at the edge of the bridge deck.

## Cross section




Cantilever section




After cut-off, the 12 x 5 mm bars were prepared for coupling with simple bar anchorages. The 5 mm bars were provided with button heads on site.



Re-established transverse prestressing.



Coupler and anchorage principle. (System developed by Skandinavisk Spåndbeton).



Section through coupler and anchorage.





## Wind Structure Interaction on 235 m Tall RCC TV Tower in Delhi

H.R. VISWANATH, B.R. NIRMALA, H.R. Surya PRAKASH

Bangalore University  
Bangalore, India

All India Radio has started the construction of an RCC TV tower, the first of its kind in India, 235 M height with revolving restaurant and viewing gallery at top, in the North - West suburban parts of Delhi, surrounded by industrial and residential area.


In connection with the above design Indian Meteorological Department (IMD) was requested to undertake analysis of surface and pilot balloon winds at Delhi air-port, to obtain wind escalation law. Utilising available surface upper wind and temperature data spread over long periods, IMD obtained the extreme values of wind and return period with different confidence limits. IMD further correlated the IS code wind figures with the extreme values obtained by their study, indicating the probabilities of occurrence of tornado and storms with return period, by determining maximum wind causing collapse of the structure.

The highest wind value recorded was 159 km/h in 1960. Wind speed for return period 100 years was determined at 175 km/h. For this, with confidence level (95%) and correction (31) wind speed was obtained as 206 km/h for the design. Since Delhi was affected by severetornado in 1978 with damaging wind speed of 250 km/h, the value of the power law co-efficient was worked out to be  $1/9$  under unstable and neutral conditions and  $1/3$  for stable conditions.


The power-law co-efficient  $1/7$  suitable for the change of gust speed with height was used for deriving wind profile.

Wind profile and a few structural details of pile cap, shaft and mast of this unique tower are shown in the photograph.

# WIND STRUCTURE INTERACTION ON 235 M TALL RCC TV TOWER




**ELEVATION**  
 THE RCC TV TOWER OF HEIGHT 235 MTS. IS THE FIRST OF ITS KIND IN INDIA WITH REVOLVING RESTAURANT AND VIEWING GALLERY AT TOP. THE TOWER IS COMING UP IN NEW DELHI.



WIND PROFILE IN THE REGION OF DELHI BASED ON CONFIDENCE LIMIT 95% FOR THE HIGHEST WIND SPEED AT SURFACE WITH RETURN PERIOD. WIND SPEED FOR RETURN PERIOD 100 YEARS WAS DETERMINED AT 175 KM/H. FOR THIS WITH CONFIDENCE LEVEL 95% AND CORRECTION 31 WIND SPEED WAS OBTAINED AS 206 KM/H FOR DESIGN.




**STEEL DETAILS IN SHAFT**




**TYP DETAIL OF JOINT-MAST**  
 WIND VELOCITY 162 KM/H AT 10M HT. POWER LAW INDEX  $1/\alpha = 1/7$ , GUST FACTOR 1.35; DRAG CO-EFF OF 1.1 FOR MAST & SKYPOD AND 0.7 FOR SHAFT IS CONSIDERED FOR DESIGN.

SKYPOD IS DESIGNED AS COMPOSITE SECTION WHICH IS A COMBINATION OF STRUCTURAL STEEL AND REINFORCED CONCRETE.



**PLAN DETAILS OF REINFORCEMENT FOR 1, 4, 7, 10 & 13TH LAYER AT BOTTOM AND 16TH LAYER AT TOP. CONCRETE MIX M 250. THERE ARE TOTALLY 15 LAYERS AT BOTTOM AND 3 LAYERS AT TOP**



**PLAN DETAILS OF REINFORCEMENT FOR LAYERS 2, 5, 8, 11 & 14 AT BOTTOM AND LAYER 17 AT TOP. ALL OTHER LAYERS ARE TANGENTIAL BARS. PINS OF LAYER 1 ARE BENT UP TO FORM PINS OF LAYER 2 AND HENCE CONTINUOUS.**



## Continuous Reinforced Concrete Pavement on Bridges

### Ch. Van BEGIN

Civil Eng.  
Public Works Ministry, Bridges Office  
Brussels, Belgium

Continuous reinforced concrete pavement is widely used in Belgium since 1970. It consists of a 20 cm thick slab lying on an adequate foundation.

The longer the segments are, without transversal joints, the better. It is therefore very useful to pass over the under bridges and to avoid expansion joints.

The problem is important in Belgium because of the high density of the highway network and the short intervals between bridges.

Small frame bridges (10-20 m span) can be overpassed without problem.

More complex is the case of bridges with precast girders, the pavement lying on the deck slab with a friction interface.

The last evolution is to use the pavement as bridge slab, supported on the superstructure frame by "neopreen" bearings. Steel beams are incorporated in the pavement.

The main problems are :



- behaviour of the pavement between the embankments, behind the abutments, and the bridge (differential settling)
- interaction between pavement and bridge deck (deflection, expansion)

1400 Km continuous reinforced concrete pavement (2 ways) are in service in Belgium. The longest bridge overpassed is 136 m long and the greatest span is 65 m long.

# CONTINUOUS REINFORCED CONCRETE PAVEMENT ON BRIDGES


## I Revêtement routier en béton armé continu

béton armé 0,20m  
 enrobé hydrocarboné 0,05m  
 béton maigre 0,20m  
 matériau drainant



## II Le franchissement des ponts


### Ponts inférieurs rigides et massifs




### Coupe B-B




### Détail A




### Coupe D-D





### Détail E




### Ponts à poutres et dalle




### Détail E




### Coupe F-F




### Ponts de grande portée



### Coupe G-G



### Détail I




### Coupe H-H








## III Particularités, problèmes

### Transition remblai-tablier



### Interaction revêtement-tablier



## Saudi Arabia – Bahrain Causeway

### D.W. BILDERBEEK

Civil Eng.  
Ballast Nedam Groep  
Amstelveen, the Netherlands

### K.B. SVENSSON

Civil Eng.  
Ballast Nedam Groep  
Amstelveen, the Netherlands

#### General

The Causeway incorporates 5 bridges and 7 embankments. The superstructure of the bridges consists of 2 separate boxgirders, each 12,3 m wide, prestressed in both longitudinal and transverse direction.

The bridges have a spanlength of 50 m and are constructed as a "Gerber" structure: alternatively cantilever girders of 66 m and drop in spans (suspende girders) of 34 m. Both cantilever and suspended girders have been prefabricated on shore and are placed in position as a complete unit.

The substructure consists of prefabricated hollow prestressed piles with an outer diameter of 3,5 m. Bridge no. 5 has been founded on caissons due to the presence of an aquifer. Bridge no. 3 incorporates the main navigation span. This navigation span has been constructed in accordance with the prefabricated segmental system.

Spanlengths: 80-150-80 m. The cast in situ piers rest on direct foundations.

#### Durability

Special measures have been taken because of the very aggressive environment:

- Blast furnace Portland cement (slag content 70-80%) has been used. This cement has a high sulphate resistance and a high impermeability.
- A max  $Cl^-$  ion content of 0,1% by weight of cement has been prescribed for the concrete. As a result the sand, dredged from the sea, had to be washed extensively.
- Cover to the rebar for the piles 70 mm, for the superstructure 50 mm.
- The piles have been epoxy coated from -2,0 CD to +4,0 CD (splash zone).

#### Design criteria

In accordance with AASHTO, with some exceptions regarding the loading:

- lane loads : 10 kN/m' lane.
- trucks : 2 trucks, one of 600 kN and one of 300 kN.
- future pipeline : 10 kN/m', situated 4,5 m outside centre line of bridge
- earthquake : static load consisting of 6% of the permanent vertical load.
- ship collision : -56000 kN on each of the two mainspan piers.  
-28000 kN on each of the side piers of the mainspan.  
-varying load of 300-1000 kN for the piers adjacent to navigation spans.







#### Materials

- Concrete quality :  $f_c = 40 \text{ N/mm}^2$  for prefabricated part of halving joint.  
 $f_c = 35 \text{ N/mm}^2$  for all structural elements.
- Reinforcement steel : Fe B 400 and Fe B 500 ( $f_y = 400 \text{ N/mm}^2$  and  $500 \text{ N/mm}^2$  respectively)
- Prestressing steel : Longitudinal prestressing, consisting of BBR CONA-MULTI 0,62" strands:  $f_{pu} = 1770 \text{ N/mm}^2$ .  
Transverse prestressing, consisting of BBRV 7 mm wires:  
 $f_{pu} = 1670 \text{ N/mm}^2$ .  
Inclined Dywidag bars in halving joints  $f_{pu} = 1035 \text{ N/mm}^2$

#### Soil conditions

- sea bottom 4.00 to 12.00 minus CD.
- top layer of caprock 0.00 - 3.00 m thick.
- soft soil (sand/clay) 2.00 - 8.00 m thick.
- soft rock of claystone/siltstone.

# SAUDI ARABIA-BAHRAIN CAUSEWAY





**300 metres bridge per week**



**8 piles drilled and placed every week**

# WIRKLICHKEITSNAHE ERFASSUNG DES BETONLANGZEITVERHALTENS


## EINFLUSS DER SCHLAFEN BEWEHRUNG ( $A_s$ ) AUF DIE SPANNUNGSUMLAGERUNGEN



## DRUCKZONENHÖHE $x_{\sigma t}$ , STAUCHUNGSZONENHÖHE $x_{\epsilon t}$ , SPANNSTAHLSPANNUNGEN $\sigma_{pt}$



## BERÜCKSICHTIGUNG DER ZEITABHÄNGIGKEIT DES $E_b$ -MODULS



# ANALYSIS OF CONCRETE PIER WITH ASEISMATIC WALL




Fig-1 General view of Bannosu Viaduct

1. Bannosu viaduct, the highway-railway combined bridge, has high-rise piers with piles of 3 m in diameter.

Elasto-plastic FEM analysis and loading experiment with a 1/10 model were carried out to evaluate and to estimate the ultimate bearing capacity of concrete pier with aseismatic wall as well as the horizontal displacement at the rail level.

The cases of analysis by FEM consist of four cases as shown in Table-1  
 The model for analysis is two dimensional and composed of concrete elements, reinforced ones, and bond ones to link both.




Fig-3 FEM Element




Fig-4 Concrete stress vs strain




Fig-5 Reinforcements stress vs strain




Fig-6 Bond stress vs displacement





Fig-2 Pier (No.5)

## 2. Consideration

As shown in Fig-8, the pier does not show sudden deformation and can keep its shape at the time of cracks generation or reinforcements yielding.

This is also confirmed by the experiment with a 1/10 model.

The ultimate bearing capacity of the lower column is judged to be more than 3.5 times the design load.



| Case No. | Tensile strength of concrete                 | Rate of reinforcements (%) | Purpose of analysis   |
|----------|--|----------------------------|---|
| Case-1   | Considered as 100% for both columns and wall | 0.5                        | Basic case  |
| Case-2   | Considered as 100% for columns only          | 0.5                        | Influence of initial deterioration of wall due to shrinkage, etc.         |
| Case-3   | Ignored for both                             | 0.5                        | Influence of initial deterioration of pier due to earthquake along bridge |
| Case-4   | Ignored for both                             | 0.3                        | Influence of ratio of reinforcements as well as case-3                    |




Fig-8 Ground acceleration vs displacement (at 1262nd nodal point)




Fig-9 Close-look-up ground acceleration vs displacement (at 1262nd nodal point)

Followings show progress of concrete cracking (Case-1)





Fig-7 Distribution of load





Fig-10 Progress of destruction (Case-1)



M. MARCHETTI

Dragages et Travaux Publics, Puteaux, France

# PONTS DU ROI TAKSIN-BANGKOK, THAILAND



### CARACTERISTIQUES DES OUVRAGES

#### OUVRAGE EN RIVIERE


Deux tabliers parallèles = longueur 224.00 m  
 = largeur 13.25 m  
 Portées 66.00 m - 92.00 m - 66.00 m

#### VIADUCS D'ACCES

4 ouvrages = longueur 305.00 m  
 = largeur 11.51 m  
 Portées courantes = 45.00 m

### VIADUCS D'ACCES

#### PHASES DE POUSAGE



### OUVRAGE EN RIVIERE

