Zeitschrift: IABSE congress report = Rapport du congrès AIPC = IVBH

Kongressbericht

Band: 13 (1988)

Artikel: On the load capacity of stiffened plate girders

Autor: Scheer, Joachim / Pasternak, Hartmut

DOI: https://doi.org/10.5169/seals-13061

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Mehr erfahren

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. En savoir plus

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. Find out more

Download PDF: 20.10.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch



On the Load Capacity of Stiffened Plate Girders

Sur la capacité portante des poutres à âme pleine raidie

Zur Regelung der Tragfähigkeit versteifter Blechträger

Joachim SCHEER
Civil Engineer
TU Carolo-Wilhelmina
Braunschweig, FRG



Joachim Scheer, born 1927, obtained his Ph.D. in 1958. As a Consulting Engineer he was involved in the design of bridges, masts and scaffolding. Since 1971 he has been a professor for Steel Structures, first in Hannover. and from 1976 in Braunschweig, working mainly on plate stability, masts and code development.

Hartmut PASTERNAK
Civil Engineer
TU Carolo-Wilhelmina
Braunschweig, FRG



Hartmut Pasternak, born 1954, obtained his Ph.D. in 1981. As a research engineer he was involved in the design of industrial steel buildings, silos and cranes. Since 1986 he has been a research worker at the Institute of Steel Structures in Braunschweig, working on load capacity and load modelling problems.

SUMMARY

Since 1935 over 200 experiments on stiffened plate girders, subjected to shear and bending loads, have been carried out worldwide. It is now to be determined, using a probabilistic approach whether, by means of the above mentioned experiments, the tension field model of the Eurocode 3 is verified for transversely stiffened girders and whether it may be extended to longitudinally stiffened ones.

RÉSUMÉ

Depuis 1935, plus de 200 expériences ont été effectuées sur la capacité portante des poutres à âme pleine raidie, soumises à des efforts tranchants et fléchissants. L'objet de cette publication est de déterminer, de façon probabilistique, si le modèle de champ de traction de l'Eurocode 3 est vérifiable pour les poutres à âme pleine raidie transversalement et s'il peut être étendu aux poutres à âme pleine raidie longitudinalement, en tenant compte des expériences mentionnées auparavant.

ZUSAMMENFASSUNG

Weltweit wurden seit 1935 über 200 Versuche zur Tragfähigkeit ausgesteifter Vollwandträger unter Schubund Biegebeanspruchung durchgeführt. Jetzt wird auf probabilistischer Grundlage untersucht, ob damit das Zugfeldmodell des Eurocode 3 für querversteifte Träger verifiziert und auf längsversteifte Träger ausgedehnt werden kann.



1. INTRODUCTION

In the past three decades, various tension field models were developed in order to predict the ultimate load capacity of stiffened plate girders subjected to shear and bending loads [1].

From time to time this development has been the target of fundamental questioning. Recently, a design model, based on the fully plastic shear load of the unstiffened web, has been presented [2].

Parallel to this, the number of experiments on stiffened plate girders has continually increased; in 1968, approximately 50 experiments were carried out, ten years later about 140 and nowadays there are more than 200.

However, experiment and theory only have their meaningfulness if full attention is paid to the stochastic character of the load capacity, and its influence quantities, in the experimental evaluation as well as in the calculations.

Since 1986, the Institute for Steel Structures in Braunschweig is working on the documentation, evaluation and recalculation of all available experiments. The work is performed — in an unprecedented extensive manner — using the programmable database system dbaseIII+. Moreover, it was attempted to estimate the uncertainty in the experiment execution and in the load capacity prediction.

In the context of the revision of the EC3, a few new questions arise, that may now be answered:

- is it allowable, in the Eurocode safety concept to apply the tension field models to transversely stiffened plate girders?
- could the application of these models, within the same safety concept, be extended to longitudinally stiffened girders? Which of the established models is optimal, taking into account the results of the experiments that were analysed in this study?

2. EVALUATION PROCEDURE

After compiling all experimental data into databases for transversely and longitudinally stiffened girders, the experiments containing parameters outside of the EC3 definition domain were rejected. The most frequent reason therefore were end post failures.

The test analysis described below (Fig. 1) was derived from the outline of the Eurocode paper "Procedure for the determination of the design resistance from tests" published in September 1987.

For the remaining i tests, the measured values of load capacities $V_{ue,i}$ (for the moment considered as exact), are compared with the calculated values $V_{ut,i}$ using model factors M_i , whose mean value \overline{M} as well as the error terms δ_i are calculated. The scattering of the measured values with respect to the theoretical ones can be estimated by means of v_{δ} .



The variation coefficient v_{Vut} of the calculated load capacity is to be estimated from the randomization of the design models according to sections 3 and 4, in which the input values (basic variables) are to be formulated with variation coefficients normally used for steel structures:

yield stress
$$-v_{fy} = 0.06...0.08$$

modulus of elasticity $-v_{E} = 0.04$
plate thickness $-v_{t} = 0.02$

The authors have no data concerning the scattering of the buck-

- 1. Measure V_{ue.i}
- 2. Calculate V_{ut,i} (from EC3 or [1])

3.
$$M_i = \frac{V_{ue,i}}{V_{ut,i}}$$

4. $\overline{M} = 1/n \Sigma M_i$

5.
$$\delta_i = \frac{M_i}{\overline{M}}$$

6.
$$v_{\delta} = \sqrt{\frac{1}{n-1} (\sum_{i=1}^{n} \delta_{i}^{2} - n \cdot 1)}$$

- 7. Estimate v_{Vut}
- 8. Estimate ν_{δexp}

9.
$$v_{Vu} = \sqrt{v_{Vut}^2 + v_{\delta}^2 - v_{\delta exp}^2}$$

10. $V_{u,k} = \overline{M} V_{ut} \exp(-1.645 v_{Vu} - 0.5 v_{Vu}^2)$ for LN-distributed load capacity

11.
$$\gamma_m = \exp((0.8 \,\beta - 1.645) \,v_{Vu}), \beta = 3.8$$

ling coefficient k_s (mainly because of the scattering of the boundary conditions). It is assumed that $v_{ks} = 0.03$. The scattering of the other input values is negligible. From the computational model, the variation coefficient of the load capacity is then calculated to be $v_{yut} = 0.08$.

Until now it has not been taken into account, that vaguely defined experimental data must also have been introduced into the data base: e.g. the yield stress was often not measured or measured inaccurately, the modulus of elasticity was often not measured at all, and in some cases, only nominal plate the thicknesses were given. The scattering for the whole set of experiments may estimated with $v_{\delta exp}$ = = 0.10.

Fig.1 Algorithm

The variation coefficient ν_{Vu} , characteristic value $V_{u,k}$ as well as the partial safety factor γ_m of the ultimate load capacity may then be calculated.

3. TRANSVERSELY STIFFENED GIRDERS

The EC3 contains simplifying assumptions for the load capacity calculations of transversely stiffened girders: bending moment and longitudinal force are taken up by the flange, transverse






Fig.2 Correlation between calculation and experiment

forces are transferred to the web through the tension field and the shear field mechanism.

Fig.2 shows the satisfactory agreement between calculated and experimental results.

Fig.3 gives the frequency distribution of the model factor.

Characteristic value and partial safety factor of the load capacity may be read off Fig.4.

4. LONGITUDINALLY STIFFENED GIRDERS




Fig.3 Frequency distribution of the model factor

The limit load capacity of longitudinally stiffened girders could be determined within EC3, in same way as for transversely stiffened gir-The assumption ders. of the tension field mechanism, however, still has to be determined. During the comparison of competing models, it was possible to substantially increase the number of evaluated experiments, relative to earlier investigations described in [1]. Fig.4 githe results for ves various models.

		Longitudinally stiffened girders (n = 59)			
		1	2	3	4
	Trans- versely stiffened girders (n = 98)	> -	V _u	V _u	V _J
		Separate tension field bands	Single tension field band	Separate tension field bands	Separate tension field bands
		Each a function of subpanel τ_i and aspect ratio α_i	A function of full panel aspect ratio α	Each a function of subpanel T; and common aspect ratio α_{min}	Each a function of subpanel τ; and common panel aspect ratio α
M	1,10	1, 15	1, 17	1,12	0,99
ν _δ	0,16	0,13	0,10	0,12	0,08
$V_{u,k}$	0,85 V _{ut}	0,95 Vut	0,94 V _{ut}	0,94 V _{ut}	0,91 V _{ut}
Υm	1,23	1,17	1,12	1,16	1,08

Fig.4 Characteristics of various computational models

5. CONCLUSIONS

The first two questions of section 1 can in priciple be answered positively. However, the characteristic values of the load capacities are a few percent lower than the theoretical values; the partial safety factors are mostly greater than the code value of $\gamma_m = 1.1$.

Moreover, it is noticeable that even the models having an average model factor above 1, with consideration of all the scattering originating from experiment and calculation, do not lie on the safe side any more. Considering this result, one might be tempted to jump to conclusions, but should rather be prompted to further investigate the experimental assessment of computational models.

Model 2 seems to be optimal for describing the behaviour of longitudinally stiffened girders; the model is simpler and does not yield worse characteristics than the other models.

The method in [2] is characterized by scattering in the model factors, that is larger than that of the models discussed in section 3 and 4. From our experience, this yields a lower bound

1

of the load capacity.

All of the experimental data and detailed results of the evaluation are available from the authors.

6. ACKNOWLEDGEMENT

The Authors wish to thank the Federal Ministry of Civil Engineering for financial support, all scientists who have sent their research papers, as well as Mr. O. Kroth for his support in setting up the data base.

REFERENCES

- 1.Dubas P., Gehri E.: Behaviour and Design of Steel Plated Structures, ECCS publication n.44. Zurich 1986
- 2.Herzog M.: Tragfähigkeit und Bemessung unversteifter und versteifter Blechträger auf Schub in einfachster Näherung, Bauingenieur 63 (1988)