Zeitschrift:	IABSE congress report = Rapport du congrès AIPC = IVBH Kongressbericht				
Band:	9 (1972)				
Artikel:	Ductility and limit states				
Autor:	Marinek, M.				
DOI:	https://doi.org/10.5169/seals-9538				

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. <u>Mehr erfahren</u>

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. <u>En savoir plus</u>

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. <u>Find out more</u>

Download PDF: 10.07.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch

Ductility and Limit States

Ductilité et états limites

Duktilität und Grenzzustände

M. MARINČEK Professor at the University of Ljubljana Jougoslavia

<u>INTRODUCTION</u> The limit states of the load carrying members and structures clearly can be treated with the help of the typical load-displacement diagram, obtained experimentally, or with the elasto-plastic theory, which enables the prediction of the real deformational behaviour. With this theory any shape of the stress-strain diagram of the material and the influence of the residual stresses can be taken into account. So the instability loads and/or the suitable defined inelastic deflection limit load can be established. Various secondary and local effects like lateral instability, local instability, ductile, brittle, and fatigue fracture have to be refered to the primary global elasto-plastic behaviour. The reliability of different approximate design methods may be estimated by correlating them to the elasto-plastic behaviour. The dimensionless treatement (which represents also the model law for experimental work) and the appropriate classification make possible the wider use of the results of the elasto-plastic theory.

In this article the inplanar treatement for the single loading of simple linear structures with time independent inelastic material behaviour is presented.

<u>DUCTILITY FUNCTIONS OF THE CROSS-SECTION</u> The nonlinear relationship between the internal force and corresponding specific deformation of the axe of the bar can be expressed in the general case by

$$\varphi_{x} = \frac{M_{x}}{EI_{x}} K_{\varphi x} \qquad \varphi_{y} = \frac{M_{y}}{EI_{y}} K_{\varphi y} \qquad \varepsilon = \frac{N}{EA} K_{\varepsilon}$$

$$\chi_{x} = \frac{\Im e_{x} Q_{x}}{EA} K_{yx} \qquad \chi_{y} = \frac{\Im e_{y} Q_{x}}{EA} K_{yy} \qquad \theta = \frac{T}{EJ} K_{\theta}$$
(1)

where the ductility function of the cross-section K can depend on all internal forces, K = f (M_x, M_y, Q_z, Q_y, N, T). Dimensionless, for the case of uniaxial bending with the normal force, there is

$$K_{\varphi} = f(\bar{M}, \bar{N})$$
⁽²⁾

with $\overline{M} = M : M^{O}$ and $\overline{N} = N : N^{O}$, where M^{O} and N^{O} are typical internal forces (refered to the proportional limit, yield strength limit, or compression strength of material). Using the Bernoulli hypothesis for the chosen strains over the cross-section, M and N are obtained with the corresponding integration for a given stress-strain diagram of material.

For the stress-strain diagram after Ramberg-Osgood $\tilde{\epsilon} = \bar{\sigma}(1+\bar{\sigma}^n)$, with $\bar{\epsilon} = \epsilon : \epsilon^{\circ}$, $\bar{\sigma} = \sigma : \sigma^{\circ}$, where $\epsilon^{\circ} = \sigma^{\circ} : \epsilon$ and the yield strength σ° , defined in Fig.1, the curves in Fig.2 with different parameters n represent four typical dimensionless stress-strain behaviour. For n = 10 and the rectangular

cross-section the ductility functions K_{ψ} are given in Fig.3, full lines for strain reversal with constant \overline{N} , and the dashed ones for nonlinear elastic material.

There is a simple relationship between the ductility functions of the individual parts of the cross-section and those of the whole composite one.

$$K_{\varphi} = \frac{\sum_{n} EI}{\sum_{n} \frac{EI}{K_{\varphi}}}$$
(3)

In this way calculated ductility functions for bending and compression of a concrete filled tube are presented in Fig.4, for an ideal elastic-ideal plastic stress-strain diagram of steel and according to CEB for concrete. The typical internal forces are here

$$M^{\circ} = \frac{\widehat{\pi}}{32} \left[\sigma_{s}^{\circ} (D^{3} - d^{3}) + \sigma_{c}^{\circ} d^{3} \right] \qquad \qquad N^{\circ} = \frac{\widehat{\pi}}{4} \left[\sigma_{s}^{\circ} (D^{2} - d^{2}) + \sigma_{c}^{\circ} d^{2} \right]$$

<u>DUCTILITY FUNCTIONS OF THE LOAD CARRYING MEMBERS</u> The typical elasto plastic load-displacement diagram can be performed for example with

$$\delta = \int_{0}^{s} \frac{MM_{\nu}}{EI} K_{\varphi} ds \qquad (4)$$

One can replace the influence of K_{ϕ} with

$$\frac{EI}{K_{\varphi}} = EI_{eff} = E_{eff}I = (EI)_{eff},$$

but the ductility factor K_{ϕ} has a clearer meaning, especially for composite cross-section.

Similar to the definition of $K_{\pmb{\varphi}}$, the ductility of the load carrying member, or structure $K_{\pmb{\xi}}$, is the ratio between the elasto-plastic displacement and the corresponding elastic one,

$$K_{S} = \delta : \delta^{e} . \tag{5}$$

Consequently, the relationship between the dimensionless load $\overline{P} = P : P^{\circ}$ and dimensionless displacement $\overline{\delta} = \delta : \delta^{\circ}$, where P° represents for example the limit state according to the theory of elasticity, and δ° the corresponding elastic displacement, is

$$\overline{\delta} = \overline{P}. K_{\delta}. \tag{6}$$

SOME EXAMPLES For the simple beam with constant properties along the axe there is the deflection under concentrated load, acting in any point,

$$K_{\delta} = \frac{3}{\overline{P}^{3}} \int_{0}^{\overline{P}} \overline{M}^{2} K_{\psi} d\overline{M} , \qquad (7)$$

for the uniformly distributed load on a beam

$$K_{\delta} = \frac{6}{5P^2} \int_{0}^{P} \left(\frac{1}{\sqrt{1-\frac{M}{B}}} - 1\right) \widetilde{M} K_{\varphi} d\widetilde{M}, \qquad (8)$$

and on a cantilever

$$K_{\delta} = \frac{2}{\bar{P}^2} \int_{0}^{P} \bar{M} K_{\varphi} d\bar{M} , \qquad (9)$$

with $\bar{P} = \bar{M}$. Fig.5 shows the results for the rectangular cross-section and three different stress-strain diagrams with strain hardening.

For the examples in Fig.6 the dimensionless deflection limit load P_{AA} , defined with 10% irreversible deflection and the plastic hinge load, both related to the elastic limit loads, are presented in the table I. Thus there is the possibility for higher allowable stresses in elastic design, dependent on the cross-section and loading (in this case for the material with $n = \infty$, without residual stresses).

Table I								i i
			D/t=20	$D/t=\infty$	$IPB_v 100$	IPB _v 340	198 ₁ 300	
A THINKING	1,43	1,31	1,23	1,17	1,21	1,14	1,08	P _{1,1}
	1,54	1,39	1,29	1,22	1,23	1,16	1,10	P _{1,1}
	1,70	1,50	1,34	1,27	1,24	1,16	1,10	₽•

The symmetric continuous beam, loaded as in Fig.7, has the ductility function

$$K_{\delta} = \frac{6(3+2\lambda)}{(3+10\lambda)(\overline{M}_{1}+M_{2})} \left(\int_{\overline{M}_{2}}^{\overline{M}_{4}} \overline{M}_{q} d\overline{M} + 4\lambda \frac{\overline{M}_{4}+\overline{M}_{2}}{\overline{M}_{1}^{2}} \int_{0}^{\overline{M}_{4}} \overline{M}_{q}^{2} K_{q} d\overline{M} \right), \quad (10)$$

$$\int_{0}^{\overline{M}_{2}} \frac{\overline{M}_{kq} d\overline{M}}{\sqrt{1-\frac{\overline{M}}{\overline{M}_{2}}}} = \int_{0}^{\overline{M}_{4}} \frac{\overline{M}_{kq} d\overline{M}}{\sqrt{1+\frac{\overline{M}}{\overline{M}_{2}}}} + \frac{4\lambda}{\overline{M}_{1}^{2}} \sqrt{(\overline{M}_{4}+\overline{M}_{2})\overline{M}_{2}} \int_{0}^{\overline{M}_{4}} \overline{M}_{q}^{2} K_{q} d\overline{M}$$

with

.

as the deformational condition. There is strong dependence on λ , the ratio of spans.

Fig.8 shows for $\lambda = 1$ the influence of different stress-strain parameters n, compared with the plastic hinge theory, and Fig.9 the influence of the cross-section properties for $\lambda = 0$.

In Fig.10 the load carrying capacities are given for a beam-column, made of the material with n = 10, as the function of the slenderness λ . The dashed lines represent the influence of strain reversal at \bar{N} = const and growing \bar{Q} .

In Fig.11 the elasto-plastic load deflection diagram $\bar{Q} - \bar{\delta}$ for $\bar{N} = Q_1$ for different parameter n of material can be compared with those of the second order elastic theory and the second order plastic hinge theory. Similarly in Fig.13 for $\bar{N} = 0,25$ and in Fig.14 for $\bar{N} = 0,525$ are $\bar{Q} - \bar{\delta}$ curves for weak axial bending of DIE20, material with $n = \infty$, dashed curves for the presence of residual stresses and nonhomogeneity, dimensionless given in Fig.12. For higher $\bar{\lambda}$ and higher \bar{N} the difference between elastic limit load, plastic hinge limit load, and elasto-plastic instability limit load, with and without residual stresses, are substantional.

For the case when Q = const, in Fig.15 and 16, the relationship $\overline{N} - \delta$ is presented for the material with n = ∞ and the rectangular cross-section.

In Fig.15 for $\overline{Q} = 0.5$ there exists the elastic limit curve and the plastic hinge curve, whereas in Fig.16 the value $\overline{Q} = 1$ alone represents already the elastic limit state, but for all that there is a large additional normal force carrying capacity, particularly for lower slendernesses.

The dimensionless buckling curves for column with the composite crosssection can be represented in the same diagram as for columns with the single material. So in Fig.17 the lower curve is the tangent modulus curve for the plain concrete, CEB stress-strain diagram, and the upper curve is the Euler curve for the ideal elastic - ideal plastic diagram of steel. Three curves in between belong to columns with concrete filled tubes and encased I-profile (numbers describe the steel cross-section, steel yield strength, and concrete compression strength). The slenderness of concrete filled steel tube is

$$\bar{\lambda} = \frac{4L}{\Pi D} \sqrt{\frac{1+c\frac{\delta \bar{c}}{GP}}{1+c\frac{E_c}{E_s}}} \quad \text{with} \quad C = \frac{1}{\frac{D^4}{d^4} - 1}$$
(11)

Of course, the real columns have geometrical and structural imperfections. Therefore, the corresponding instability limit loads with the help of the beam-column elasto-plastic theory have to be determined. Fig.18 gives the $\bar{Q} - \bar{\delta}$ curves with the instability limit states for different slender beam-columns with concrete filled tube cross-section, having ductility functions in Fig.4.

FINAL REMARKS The consequent dimensionless treatement would have larger effects in using the results of the elasto-plastic theory for better understanding of the ductile behaviour of structures and with this more rational use of material.

The deterministic treatement of structures with the elasto-plastic theory supports and supplies the probabilistic treatement because a significant variation is possible only with representative parameters for separated influences. On the contrary, the pure empirical statistical analysis of the complex phenomena appearing in the ductile bahaviour of structures is rather questionable, if not impossible.

The extension of the elasto-plastic theory on the problems, taking into account more complicated loading and structural geometry, the Bauschinger effect, the influence of the temperature (also fire), and strain velocity, calls even more attention to the international collaboration in finding the appropriate classification of the shapes for stress-strain diagrams of the material, cross-sections, structural and geometrical imperfections.

<u>AKNOWLEDGEMENT</u> Some results are presented here from larger research project, carried aut with the financial support by "Boris Kidrič" Foundation of Ljubljana. The collaboration with my past and present assistent P.Fajfar, V.Marolt, J.Reflak and M.Vitek, and also numerous students, is very much appreciated.

<u>SUMMARY</u> Presented results of the elasto-plastic theory, compared with the corresponding elastic theory and plastic hinge theory, show on the one side, that the possibility exists for better exploatation of material also for statical determined structures when inelastic deflection limit state has to be decisive, and on the other side, that one should be carefull with the unlimited use of the plastic hinge theory for stability limit states.



