Zeitschrift:	IABSE congress report = Rapport du congrès AIPC = IVBH Kongressbericht
Band:	14 (1992)
Artikel:	New opportunities with Arapree presetressed concrete
Autor:	Gerritse, Arie / Hyna, Lou / Böttcher, Rolf-Dieter
DOI:	https://doi.org/10.5169/seals-13839

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. <u>Mehr erfahren</u>

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. <u>En savoir plus</u>

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. <u>Find out more</u>

Download PDF: 11.08.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch



New Opportunities with Arapree Prestressed Concrete

Béton d'arapree précontraint

Arapree-Spannbeton

Arle GERRITSE Civil Eng. Hollandsche Beton Groep Rijswijk, The Netherlands

Lou HYNA Civil Eng. Hollandsche Beton Groep Rijswijk, The Netherlands Rolf-Dieter Böttcher Civil Eng. AKZO Wuppertal, Germany

1 <u>Introduction</u>

In recent years extensive research has been carried out into the behaviour of man-made high strength fibres, aiming for structural application in concrete. This paper describes some recent designs and applications of Arapree (ARAmid PREstressing Element) in concrete.

ARAPREE prestressing elements are composed of aramid fibres, embedded in a polymeric matrix, with the following main characteristics: high strength (3000 N/mm^2), non-corrosive, resistant to aggressive environments, excellent fatigue behaviour and insensitive to electro-magnetic currents. The durability of Arapree is even guaranteed in cracked cross-section. For more detailed information, see [1].

2 Applications

2.1 Fish ladder

In The Netherlands a hydro-electro power station has recently been built in the river Meuse. To enable fish to pass the 4,5 m head (difference in water level) a fish ladder was constructed consisting of 24 small weirs. Each weir is composed of vertical driven piles with shutters in between. To allow for optimalisation of the water stream over the weirs, the shutters have to be adjustable by hand. They are 35 mm thick and weigh 19 kg. In addition to these elements, the slide near the entrance and the walkway to the control winch are also made of concrete prestressed with Arapree.



Typical cross-section fish ladder

Details



A construction comparable to the weirs is the bank protection. A feasibility study showed that the use of Arapree prestressed concrete elements can be economically more attractive than traditional concepts in steel or wood for a retaining height of 3 m.

2.2 Sun screen

The possibilities of Arapree prestressed concrete require a new way of thinking to utilize the material at its best. A typical example of this is the design of a sun screen for tunnel entrances. Traditionally, these screens are made of aluminum lamellae which are supported by a steel structure. An alternative construction in concrete is not possible due to the large concrete cover. The slightly curved Arapree elements with a rise of 1 m span 12,8 m have a crosssection of 250 mm wide and 90 mm high.



Tunnel entrance

Wall elements

2.3 Wall elements

The eastern entrance of the new tunnel under the river de Noord in the Netherlands is a trough-like structure, founded on concrete foundation piles up to 6.5 m above ground level. To hide these piles from view, a wall of concrete elements along both sides of the entrance is currently under construction. The noncorrosive Arapree made it possible to construct attractive prestressed, light weight elements, in an aggressive environment. The wall elements have a T-shaped cross-section with a width of 500 mm, a flange thickness of 45 mm and a total thickness varying from 125 mm to 65 mm.

2.4 Structural building elements

The demand for handy, slender and durable structural elements is in contradiction with the increasing concrete cover necessary to protect normal reinforcing and prestressing steel in aggressive environments. In this field Arapree solves the problem. For instance prestressed concrete lintels and floor elements with minimal dimensions are architecturally attractive and easy to handle.

3 Conclusion

New prestressing materials like Arapree make it possible to widen the horizon of prestressed concrete. The examples discussed make it clear that by using Arapree, concrete can now economically replace traditional materials such as steel, aluminum and wood. Structures that were not possible before in concrete, now are!

4 <u>References</u>

[1] Gerritse, A et.al.: New horizons with Arapree prestressed concrete. Conference papers: IABSE Congress, New Delhi, March 1-6 1992