

Zeitschrift: IABSE structures = Constructions AIPC = IVBH Bauwerke
Band: 2 (1978)
Heft: C-4: Structures in the USSR

Artikel: Steel railway bridge on the Baikal-Amour Railway Line
Autor: Potapkin, A.
DOI: <https://doi.org/10.5169/seals-15102>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 06.08.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>

9. Steel Railway Bridge on the Baikal-Amour Railway Line

Contractor: Ministry for Transport Construction

Dimensions: spans 110 x 132 x 110, space between trusses

5,8 m in width and 15 m in height

Materials: steel grade 10 XCHD, minimum yield limit
40 kg/mm²

Designed operating T°: – 55 °C

Metal consumption: 5,1 t per 1 m/span

Terms of construction: 2 years in operation since 1975

The bridge is built up on the Baikal-Amour railway line now under construction in the Siberia. Cast in place massive pier foundations rest on natural grounds. They were cast in open pits protected with a sheet piling wall. Foundations were embedded for 13 m.

A steel continuous bridge superstructure 110 x 132 x 110 m with the bottom floor crossed the river bed. All the truss elements are of welded type, bolt joints fitted with high-strength bolts. Panels are 11 m long. Booms and braces in main trusses are box-shaped, struts and counter struts are

H-shaped. Transverse and longitudinal welded girders under the deck are of I-form.

The main feature of this type of bridge superstructure is that its deck gets in operation together with the main trusses. Their mutual operation is secured with the help of special ties which tighten the continuous longitudinal girders to the bottom booms.

The bridge superstructure is calculated through computer as a three dimensional design.

Application of a continuous design compared with a non-continuous one reduces metal consumption for 7 o/o.

The bridge superstructure is assembled by cantilevering procedure.

The bridge superstructure being tested, designed predictions including the mutual operation of the carriageway with the main trusses proved to be correct.

(A. Potapkin)



Steel Railway Bridge on the Baikal-Amour Railway Line