Zeitschrift: IABSE structures = Constructions AIPC = IVBH Bauwerke

Band: 7 (1983)

Heft: C-24: Structures in Italy

Werbung

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Mehr erfahren

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. En savoir plus

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. Find out more

Download PDF: 11.12.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch

Mageba production programme



Expansion

Watertight transition structures for modular joints in transport routes of all kinds.

Lamella joints Robek System Transition structures for heavy traffic bridges and for expansion paths of all magnitudes. Load compensating segments with folding expanding sections divide the

total expansion path into traversable grooves. The modular joint remains watertight and level with the carriageway in all conditions of movement. It is specially designed and manufactured to suit the conditions of each structure.

Unitary joints Robek System Modular joints for the expansion of a groove. Steel edge sections with integral anchorings are incorporated in elements in an elastic and compact special concrete. An elastomeric expanding section provides a waterlight seal of the groove.

Unitary joints are made for light and heavy traffic. They are particularly suitable for later installation. Matt joints Robek System

Modular joints for medium-sized expansion paths. A reinforced, elastomeric deformable matting is fitted in a cavity of the structure. It can expand while simultaneously load compensating and provides a level closure of the movement joint. Matt joints are made for light and heavy traffic. They are particularly suitable for later installation



magaba Bearings

Elastomeric, torsionable bearing structures for loadbearing and movement equalization in structures of all kinds.

Pot-type bearing Robek System Bearing structures for applied loads and displacements of any magnitude, particularly for bridge construction. These pot-type bearings rotate in all directions on an enclosed pressure pad with integral sealing chain of tough plastic, sliding without wear on the pot wall. The pot bearing is made into a sliding pot bearing if movements have to be equalized. It can be provided with sliding chains permitting external re-lubrication.

Reinforced elastomeric bearings

Bearing structures for applied loads and displacements of medium magnitudes in bridge construction and structural engineering. Elastomeric bearings are reinforced with sheet steel and accommodate movements by shear deformation. For larger movements they can be combined with a sliding bearing.

Structural bearings Delta System Bearing structures for applied loads and displacements of small magnitudes in structural engineer-

The structural bearings are rigid without reinforcement and accommodate movements by shear deformation and/or by sliding.

In addition to elastomeric torsionable bearing structures, conventional designs are also produced. They can be combined with sliding bearings.

Point tilting bearings

These rotate in all directions by rolling on a spherical dome.

Spherical bearings

These rotate in all directions by the sliding of a spherical dome.

Linear rocker bearings


These rotate in one direction by rolling on a curved section.

Roller bearings

These extend the curved section to . a single-sided moving roller.

Pilot bearings

Provide fixed point or movement directions without accepting applied vertical loads.



Hydraulically stacked parking places for private cars in multicarparks and parking areas.

Double parker (Pit Machine)

Mageba System

Car parking system requiring little space for two parking places one above the other and swivelled for entering and leaving the driving level. Both parking places can be used independently.


Hoist parker (Surface Machine) Mageba System


Car parking system with two horizontal parking places one above the other and raised or lowered for entering and leaving the driving le-


Hoist parkers are particularly economical with only one movable parking place. Two vehicles can then be parked dependent on one another


14 km away with millimetre accuracy within seconds


























RESTON Pot Sliding Bearings are highly suitable for installation in bridge structures. They feature a low-profile design, low weight and high loading capacity.

RESTON Linear Tilting and Sliding Bearings

are a combination of normal linear tilting bearings and PTFE sliding bearings and are suitable for installation in bridge structures.

PROCEQ SA Riesbachstrasse 57 CH-8034 Zurich LASTO-BLOCK Bearings are suitable for building, civil engineering and bridge con-

engineering and bridge construction applications. Their simple form allows easy installation.

LASTO-STRIP Bearings for Buildings

were especially developed for building constructions. They are particularly suitable for movement compensation between concrete slabs and load-supporting walls and prevent structural cracking.

proceq

TENSA-ACME Roadway
Construction Joints
are highly suitable for instal-

lation in traffic levels (parking lots, bridges, airport areas etc.). Dilatation up to 60 mm.

TENSA-LASTIC Roadway
Construction Joints

meet all the requirements that can be made in bridge engineering of a modern joint design. They are rugged and watertight. Dilatation range 60 mm and bigger.

Phone: 01/477800 Telex 53357 proce ch