

**Zeitschrift:** IABSE structures = Constructions AIPC = IVBH Bauwerke  
**Band:** 7 (1983)  
**Heft:** C-27: Recent structures: Part I  
  
**Artikel:** Bottling plant at the Carlsberg Breweries, Copenhagen (Denmark)  
**Autor:** Frandsen, A.G.  
**DOI:** <https://doi.org/10.5169/seals-18281>

### **Nutzungsbedingungen**

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

### **Conditions d'utilisation**

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

### **Terms of use**

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

**Download PDF:** 10.12.2025

**ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>**



### Steel Structure

The roof of the bottling hall forms a shed roof with four steel trusses comprising the main structure, each of which are supported by four reinforced concrete columns.

The trusses have a trapezoidal cross section with a maximum width at the bottom of 8.6 m and a height of 3.5 m. Bracing members are arranged only in the top level and the sloping sides of the trusses. As there is no bracing in the bottom level of the trusses, unsymmetrical loads are catered for by providing bracings between neighbouring trusses which restrains the bottom chords.

All members in the trusses are circular hollow sections of steel grade St. 52.3. The joints are designed with gusset plates that form a saddle over the top and bottom chords. This design has been chosen primarily for esthetical reasons but the contractor has found the solution to be also economically favourable.

The secondary roof structures consist of standard sections that allow for arbitrary suspension of services etc. These structures are supported by the trusses at the bottom joints only and are arranged in such a way that only the main trusses are visible from below the suspended ceiling.

### Erection of the Roof Structures

In order to achieve the specified quality a careful quality control system has been carried out by the consultants' supervision. Due to transportation the



*Bottom joint*

main trusses were manufactured in sections at the workshops and assembled on the site under the cover of two large tents. Only shop priming was applied before arrival at the site. The trusses were completed inclusive of the final paint at ground level i.e. before erection.

*(A. G. Frandsen)*



*Building under construction*