

Zeitschrift: IABSE structures = Constructions AIPC = IVBH Bauwerke
Band: 7 (1983)
Heft: C-27: Recent structures: Part I

Artikel: Sport stadium at Karlsruhe (Fed. Rep. of Germany)
Autor: Schlaich, J. / Horstkötter, K. / Ludescher, G.
DOI: <https://doi.org/10.5169/seals-18282>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 26.07.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



8. Sport Stadium at Karlsruhe (Fed. Rep. of Germany)

| | |
|---------------------------|--|
| Owner: | City of Karlsruhe |
| Architects: | Schmitt, Kasimir und Partner, Karlsruhe |
| Engineers: | Schlaich + Partner, Stuttgart Prof. Dr. Ing. J. Schlaich, Dipl. Ing. R. Bergemann |
| Contractors: | Steel and cable work : Lavis, Offenbach Pfeifer, Memmingen |
| Duration of work : | 18 months |
| Service date : | October 1984 |

The 69 m span of the main stadium could have easily been covered by simple steel girders requiring a depth of about 2.5 m. However by suspending this roof by means of a cable structure and hence creating in addition to the end supports two inner supports for these girders, their depth could be reduced to half of that, i.e. 1.25 m. Thus the whole structure becomes much less heavy with favourable architectural consequences as well for the interior impression as for the outer view of the hall. Detailed comparison revealed that this improvement of the design could be achieved without additional costs.

The cable structure is of the same type as a self-anchored suspension bridge. Its two masts are oc-

tagonal and tapering steel tubes carrying 15,000 kN each. The two main cables and the two guy cables of each mast, which are anchored by soil anchors, consists of two locked coil ropes of 82 mm diameter each. The suspender cables' diameters are 33 mm. All saddles, joints and anchorages are made from cast steel.

The steel grid consists of girders with 1/2 IPB chords and tubular diagonals with diameters between 42 and 70 mm. They are fully welded without any gusset plates. Horizontal stiffening of the grid is provided at its periphery by four vertical trusses having prestressed diagonals made from thin rods. The outer columns following the facade are hinge supported at their base and their top. The grid is covered with corrugated sheets.

The grid was conventionally erected on temporary trestles and loosely connected with the cable structure. The whole roof was simultaneously lifted from its temporary supports and prestressed by hydraulically jacking up the two masts.

The total structural steel quantity for the main hall, including the cables and masts, is only 65 kg/m². For the appendix with its extremely light suspended girders of 18 m span, even 28 kg/m² are needed only.

(J. Schlaich, K. Horstkötter, G. Ludescher)



