Zeitschrift: IABSE structures = Constructions AIPC = IVBH Bauwerke

Band: 7 (1983)

Heft: C-28: Recent structures: Part II

Artikel: East Coast Parkway (Singapore)

Autor: Maunsell

DOI: https://doi.org/10.5169/seals-18285

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Mehr erfahren

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. En savoir plus

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. Find out more

Download PDF: 10.12.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch



11. East Coast Parkway (Singapore)

Authority: Public Works Department,

Republic of Singapore

Client and Contractor: Sato Kogyo Co Ltd, Tokyo Consulting Engineers: Maunsell Consultants Ltd

Value: \$US 70.5 million

Design period: 1976-1978 Construction period: 1977-1981

Maunsell was responsible for the design of major elements of Phase IV of the Parkway which serves the new Changi airport. Phase IV includes a 5.6 km length of eight-lane expressway which skirts the central business area of Singapore and provides connecting links with it.

The Public Works Department invited international tenders for a design and construct contract which was awarded to Sato Kogyo Co Ltd of Tokyo, Japan. Maunsell acted as consulting engineers to the contractor for design of the project including highway alignments, interchanges and viaduct structures. The high-level viaduct spanning the Singapore River and Kallang Channel is 1,800 m long and four slip-road elevated ramps are each 350 m long. There is also a 400 m-long low-level viaduct.

The high-level viaduct consists of a series of 84.5 m spans comprising 38.4 m-long trestle decks supporting suspended spans of 46.1 m. Trestle decks are formed of precast prestressed concrete segmental box girders supported by H frames with inclined upper and lower legs. Suspended spans consist of wide flange precast prestressed concrete girders. In situ slabs and diaphragms transversely join trestle deck box girders and suspended span girders. Sliproad elevated ramps are continuous prestressed

concrete spine beam box girders with span lengths varying from 29 m to 40 m. The low-level viaduct is a continuous reinforced concrete voided slab structure supported on rows of circular columns generally at 24 m centres. Structures are geometrically complex as they accommodate high curvatures and superelevation, varying width at sliproad connections and skew crossings of ground-level roads.

The Parkway traverses recently reclaimed land, so all structures are supported on piles of steel H section or driven steel casings filled with concrete.

The consulting engineers played an important role in the development of erection methods and design of temporary works. Responsibilities included detailed design of structural steelwork centring and handling equipment for construction of trestle decks, and attendance during initial erection and commissioning. Provision was made in the design of permanent works for support of centring and manœuvring of precast units.

Close liaison was maintained with the specialist subcontractor for beam lifting. Beams weighing up to 170 tons were transported from casting yards at ground level and lifted by jacks positioned on an erection girder. Permanent works were designed for loadings imposed by this erection method and incorporated many special details to meet complexities of alignment at the main interchange. The advantages of a package deal contract are well illustrated by the integration of permanent and temporary works design in many areas of the Works.

The main viaduct received the Tanaka award in 1981. This award is made annually by the Japan Society of Civil Engineers for outstanding achievement in structural engineering.

(Maunsell)





