

Zeitschrift: IABSE structures = Constructions AIPC = IVBH Bauwerke
Band: 8 (1984)
Heft: C-30: Industrial cranes

Artikel: Travelling crane at work on the Onaruto Bridge (Japan)
Autor: Enjoji, T.
DOI: <https://doi.org/10.5169/seals-18830>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 20.08.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



5. Travelling Crane at Work on the Onaruto Bridge (Japan)

The 2400-P Travelling Crane is playing a central role in the construction of the Onaruto Bridge, scheduled to open in the spring of 1985. This suspension bridge is one in a series of bridges which will eventually link Honshu and Shikoku, two of Japan's four major islands. The 2400-P has a maximum boom length of 39.62 m, with a lifting capacity of 85 tons at 28 m (15.5 tons at 35 m with the auxiliary jib) and an operational weight of approximately 348 tons. It is used to set reinforcing girders in place, which evenly distribute the load on the bridge cables (preventing the cables from bending) and provide the overall bridge structure with the proper amount of rigidity. The crane lifts prefabricated blocks weighing 85 tons, which have been transported to the construction site by ship.

Operations of this kind require precise control coupled with perfect safety. In order to satisfy these requirements, the 2400-P is equipped with computerized digital controls which utilize information stored in cartridges. Boom load limit and angle are displayed digitally, while boom moment is shown as a percentage. The design of the display panel makes it possible to determine the machine's operating condition at a glance. Standard features include overload and scamper prevention devices, as well as an automatic levelling mechanism that regulates the angle of the swing axis. Safe operation is further assured by a long list of safety devices, including mechanisms to prevent boom reversal and oil depletion, a swing parking brake and

swing warning device. The swing clutch incorporates the highly reliable «magnetorque» system, providing smooth swing with precise control.

The 2400-P can be fitted to a barge to form a floating crane, or to a crawler undercarriage to become a crawler crane. This interchangeability makes the 2400-P a versatile crane for a wide variety of construction jobs.

(T. Enjoji)

