

Zeitschrift: IABSE structures = Constructions AIPC = IVBH Bauwerke
Band: 10 (1986)
Heft: C-36: Structures in Japan

Artikel: ARK buildings, Tokyo
Autor: Tsuchiya, Y.
DOI: <https://doi.org/10.5169/seals-19850>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 21.08.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



3. ARK Buildings, Tokyo

<i>Client:</i>	<i>Association for redevelopment of Akasaka-Roppongi blocks.</i>
<i>Consultant:</i>	<i>Mori Buildings Co., Ltd.</i>
<i>Architect:</i>	<i>Irie Miyake Architects & Engineers</i>
<i>Engineer:</i>	<i>Irie Miyake Architects & Engineers</i>
<i>Contractors:</i>	<i>Kajima Corporation, Toda Construction Co., Ltd. and Fujita Corporation</i>
<i>Dimensions:</i>	
<i>Number of storeys:</i>	<i>37</i>
<i>Total floor area:</i>	<i>181,924 m</i>
<i>Maximum height:</i>	<i>153,55 m</i>
<i>Materials:</i>	<i>Steel, Reinforced concrete</i>
<i>Construction Period:</i>	<i>28 months</i>
<i>Service date:</i>	<i>March 1986</i>

Introduction

The office building described is one of the buildings being constructed for the redevelopment project of the Akasaka-Roppongi blocks. A hotel, a concert hall, a TV studio and two high rise residences are under construction. The structural system of the building is a steel framework with the reinforced concrete floors and the concrete shear walls which have some slits to provide ductile deformation in severe vibrations caused by earthquakes. The precast concrete sheets are installed as the exterior walls. The exterior walls were so designed as to make a unique facade and to interrupt the direct ray of the sunshine. With these walls less energy consumption is expected. The precast concrete is reinforced by carbon fibers.


Design

In plan the building consists of two rectangular parts of 45×42 m, each of which comprises the beam spans of 15 m, 6 m, 9 m and 15 m in the east-west direction and the 6 m spans of beams in the south-north direction. At the centre of each plan the core of 84×15 m surrounded by the shear walls is placed as shown in Fig. 1. The thickness of the shear walls varies from 15 cm to 20 cm. The shear walls can transmit the storey shear due to the earthquake motions from the upper floor girder to the lower floor girder through steel bars in the wall. The 1 cm wide vertical slits are cut every 50 cm distance. These slits can change the brittle shear failure of the shear wall into the flexural failure. The flexural failure can provide the large energy absorption against earthquake excitations. Large viscous damping is also expected during vibration. The floor slabs in the basements were designed as a flat slab structure without beams, in order to save as much storey height as possible.


(Y. Tsuchiya)



ARK Building



Shear wall



Shear wall




Fig. 1