

Zeitschrift: IABSE structures = Constructions AIPC = IVBH Bauwerke
Band: 11 (1987)
Heft: C-43: Excavations

Artikel: Deep excavation for gravity separator at steel mill (Sweden)
Autor: Lindh, B. Göran
DOI: <https://doi.org/10.5169/seals-20387>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 21.08.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



1. Deep Excavation for Gravity Separator at Steel Mill (Sweden)

Client: Swedish Steel Corporation, SSAB
Consultants: Viak AB, Stockholm
Contractors: Siab
Grout contractors: Sweba, Gothenburg

The new rolling mill demanded a separator system for the cooling water which contains a lot of ironoxid. A circular sedimentation basin was founded 18 m below the factory area level, just beside a factory hall in operation and under a crane runaway.


A pumping station was founded at 11 meters depth.

Soil strata


Elevation	Depth	Soil
+12 to +6	0–6 m	Filling of slag, sand and gravel
+6 to app. -2	6–14 m	Silt
-2 to -5	14–17 m	Till with boulders
-5	17 m	Rock, mainly granite

Planned construction method


- Open cut down to +7 = 5 meters below the mill yard. At +7 the adjacent factory hall and the crane runaway are founded. The groundwater level was also found at this level.
- Driving of a sheet pile wall to refusal on rock. If the sheet pile did stop earlier on boulders the vertical stability should be guaranteed by driving steelpiles in pipes welded to every third sheet pile.
- Anchoring the sheet pile wall by oblique wirecables grouted at least 3 meter in the rock.
- Sinking of a prefabricated circular concrete basin, 6 m in height, from elevation + i.e. 11 meters below the ground.
- Lowering of the groundwater tabel to the rock by means of sinkwells outside the sheet pile wall.
- Excavation of the rock in the deepest part of the basin by blasing.



SSAB Domnarvet Borlänge Steel Plant



Cut Through Sheet-Pile Wall




Drilling and grouting the anchors

Changing assumptions

The sheet pile wall consisted of Larssen IV profiles and every second pile a Larssen II profile. The Larssen II piles was driven to refusal 3–4 meters earlier than expected. Groundwater lowering gave a large influence area because of heavy leakage in open fissures and cracks in the rock.

The influence area gave risk for subsidences on sensible factory buildings and groundwater sinking was therefore abandoned.



Excavation during sinking of the concrete basin, Ø 17 m; 16 m below the ground surface

Final performance

The leaking rock under the basin bottom was grouted with cement and silicate.

The soil under the sheet pile wall was grouted with polyaratan gel, silicate and cement depending on the permeability of the soil indicated by the loss of the drilling water measured level by level.

The grouted soil had to withstand the vertical force from the sheet pile wall = 500 kN/m, and the horizontal earth and water pressure almost 600 kN/m.

As anchors, taking the horizontal force 500 kN/m, was used boring pipes fitted with temporary boring crowns. The pipes was drilled in place an grouted through the boring pipe.

The circular basin was fitted with pipes which made it possible to smear the outside with bentonite during sinking.

As a precaution the basin was possible to complete with vertical anchors for jacking the ring downwards.

(B. Göran Lindh)