

Zeitschrift: IABSE structures = Constructions AIPC = IVBH Bauwerke
Band: 12 (1988)
Heft: C-47: Repair and rehabilitation of bridges: case studies II

Artikel: Repair and rehabilitation of Roma-Viterbo railway bridges (Italy)
Autor: Croci, G.
DOI: <https://doi.org/10.5169/seals-20940>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 21.02.2026

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



10. Repair and Rehabilitation of Roma-Viterbo Railway Bridges (Italy)

Owner: A.C.O. TRA.L. – Azienda Consortile Trasporti Laziali
Design: Prof. Ing. Giorgio Croci
Contractor: NICIS S.P.A. – Roma

The railway line Roma – Viterbo (Italy) has been realized between 1906 and 1913.

The original execution had a narrow gauge of 1.00 meter.

Later works for a complete structural remaking were executed; they involved modifications of lay out, the adoption of the normal gauge and the suppression of those parts in curve with a radius of curvature lower than 120 meters. These variations have modified the loads and their manners of application, provoking several damages in the structures, pointed out during the ordinary maintenance; the cracking observed on both, on the hanging and on the arcades, suggested, in the sixties, the insertion of cross chains with still visible relative anchor shapes.

Phenomena of ruins and decay of materials have necessitated the consolidation of the viaducts.

The main cracking manifestations are located in correspondence of the connection zone between the external hanging and the arcades involving the almost longitudinal development of viaducts.

These crackings are located almost exclusively on the external side of the curves because of centrifugal actions (see fig. 1).

The decay of masonry structures shows an erosion of tuff ashlar and a deterioration of mechanical characteristics of the mortar that near external surfaces is completely lacking.

The above-mentioned decay conditions are due to effects of atmospheric agents and, in some cases, to the defective drainage system.

Measures for improvement of the static behaviour and of the contrast decay phenomena have been adopted for the restore of safety conditions and for the complete functional recovery of the viaducts.

The structural consolidation interventions consist in the realization of a reinforced concrete structure adherent on the existing masonry, after removing the internal filling (see fig. 2).

The slab on the extrados of the arcades has a thickness variable between 15 and 25 cm; the internal walls are 15 cm thick and follow the internal configuration of existing structures.

In correspondence with the bridge, piers have been realized with 2 transversal stiffening walls to resist to centrifugal actions.

The above-mentioned structures have been jointed with the existing masonry by means of injections of reinforced concrete both on the walls and on the vaults.

Relating with the requirement of non-interruptions of railway traffic, a different intervention of consolidation, which foresees the insertion of a prestress cables system, arranged according with the schemes in fig. 4, 5, has been studied.

The cables included in the vertical walls with an appropriate inclination supply a bending moment which compensates the moment due to centrifugal actions.

The horizontal cables arranged along the arcades tend to equilibrate the radial translation.

The anchor zones, realized with reinforced concrete curbs supply moreover an effective longitudinal connection.

Relating to the phenomena of decay for improvement of the physical-mechanical characteristics of masonry it is forecast to inject cement mixture along the cracking development and in correspondence of visible lacking between stones after a complete removal of mortar.

(G. Croci)




Fig. 1 Global view of the viaduct



Fig. 2 A view of the inside of viaduct after removing of filling



Fig. 3 Arrangement of steel-bars




Fig. 4 Arrangement of prestressing cables




Fig. 5 Cross section on bridge-pier