Zeitschrift: IABSE reports of the working commissions = Rapports des

commissions de travail AIPC = IVBH Berichte der Arbeitskommissionen

Band: 10 (1971)

Artikel: Design according to reliability theory

Autor: Murzewski, Janusz

DOI: https://doi.org/10.5169/seals-11170

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Siehe Rechtliche Hinweise.

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. <u>Voir Informations légales.</u>

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. See Legal notice.

Download PDF: 21.05.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch

Design according to Reliability Theory

Projet selon la théorie de fiabilité

Entwurf nach der Zuverlässigkeitstheorie

JANUSZ MURZEWSKI

Professor of Civil Engineering Politechnika Krakowska Kraków, Poland

New solutions of structural analysis are not so important as the technological concepts for the development of the mass-produced steel structures design, as Prof. Jungbluth pointed out in his Introductory Report. It does not mean that there is no need for new theoretical considerations. It seems that the reliability analysis will take place of the structural analysis in the design. Two questions are basic for the reliability analysis. One of them is the anticipated sevice time of the structure. It happens more and more often now that the requirements and opinions about usefullness of some kinds of structures change sooner than their real durability expires. This problem must be taken under consideration in conditions of the mass-production of steel building. and it can be done in terms of probability theory. The structure shall be designed for a given risk of failure r. structure is protected against the corrosion and it does not suffer the fatigue, we have

$$r = \frac{1}{T} \ln \frac{1}{1 - \omega} \approx \frac{\omega}{T} , \qquad (1)$$

where T - service life .

 probability of excessive overloading, which depends on the safety class.

The second basic question is the efficiency of the quality control. We expect that no defective building structure will be given to users, although some defectiveness is allowable in the case of other industrial products. A period of initial aging, when the risk of failure decreases thanks to eliminations of defective objects, must not take place for buildings, because a spontaneous elimination would mean the structural collapse and it is too dangerous for the personal life. So the risk of

failure r concerns only the failures due to exceptional overloadings and it is constant in such circumstances. Each system of mass-produced structures shall be designed simultaneously with a system of quality control. The solutions of statistical quality control shall be elaborated for this purpose.

Applications of optimization in the design of mass-produced steel structures have found a special interest on this Symposium. Prof. Goble presented effective techniques of optimal design, where the objective or cost function is minimized. Other contributors have extended the cost critrion for the whole design, fabrication and erection process. The most general point of view adopted in reliability theory defines the total costs as follows

$$C = C_r + C_a + C_e + C_1,$$
where
$$C_r - \text{cost of realisation,}$$

$$C_a - \text{cost of insurance,}$$

$$C_e - \text{cost of maintenance,}$$

$$C_1 - \text{cost of demolition.}$$
(2)

The cost of insurance for many buildings shall defray the costs of failures $C_{\rm f}$ with a probability ω

$$C_a = \omega C_f$$
 , (3)

and all kinds of costs shall be discounted for a definite moment of time.