Zeitschrift:	IABSE reports = Rapports AIPC = IVBH Berichte		
Band:	42 (1983)		
Artikel:	Ultimate strength of bow construction		
Autor:	Ohnishi, Tokio / Kawakami, Hajime / Yasukawa, Wataru		
DOI:	https://doi.org/10.5169/seals-32422		

# Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. <u>Mehr erfahren</u>

# **Conditions d'utilisation**

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. <u>En savoir plus</u>

# Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. <u>Find out more</u>

# **Download PDF:** 27.07.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch

# Ultimate Strength of Bow Construction Résistance structurale limite de la proue d'un navire Bruchfestigkeit des Buges

Tokio OHNISHI Naval Architect Kawasaki Heavy Industries Ltd. Akashi, Japan

Hajime KAWAKAMI Naval Architect Kawasaki Heavy Industries Ltd. Akashi, Japan Wataru YASUKAWA Naval Architect Kawasaki Heavy Industries Ltd. Akashi, Japan Hitoshi NAGASAWA Naval Architect Ministry of Transport Tokyo, Japan



Tokio Ohnishi, born 1948, received his Masters Degree in engineering from Osaka University, Osaka, Japan. For ten years, he was involved in dynamic problem and nonlinear problem in structural analysis region, and he is now a research engineer at the Structure Analysis Section of Strength Laboratory in the Technical Institute.

Hajime Kawakami, born 1940, obtained a degree in Naval Architecture from Osaka University, Osaka, Japan. He is a specialist in ship hull vibration and now manager at the Structure Analysis Section of Strength Laboratory in the Technical Institute.



Wataru Yasukawa, born 1933, received his doctor of engineering degree from Osaka University, Osaka, Japan. His major fields of research activities include strength of ship structures, plastic analysis buckling and ultimatestrength of structures, and he is now a senior manager of Strength Laboratory in the Technical Institute.



Hitoshi Nagasawa, born 1925, got his doctor of engineering degree at the University of Tokyo, Tokyo, Japan. For about 30 years he studied the strength of ship structure in the Ship Research Institute, Ministry of Transport, and now he is the director general of the Institute.

# SUMMARY

A study of the ultimate strength of the bow construction of two ships which have suffered a collision, has been made by means of a theoretical calculation by the FEM and experiments on static collapse by using 1/10 scale bow models have been conducted. It has been possible to estimate the load acting on the side structure of the struck ship and the bow deformation of the striking ship.

# RÉSUMÉ

La résistance structurale limite de la proue de deux navires qui sont entrés en collision, a été déterminée par un calcul théorique au moyen la méthode des éléments finis et aussi par des expériences sur leur rupture statique au moyen des modèles réduits au 1/10<sup>e</sup> des proues précitées. Il a été possible d'évaluer la charge exercée sur la structure latérale du navire endommagé et la déformation de la proue du navire opposé.

# ZUSAMMENFASSUNG

Die Bruchfestigkeit des Buges zwei zusammenstossenden Schiffen – wurde anhand einer Berechnung mit finiten Elementen sowie einem Modell untersucht. Die Last auf der seitlichen Struktur des beschädigten Schiffes und die Umformung des Buges des gegnerischen Schiffes konnten geschätzt werden.

#### 1. INTRODUCTION

So far the capacity of the collision-resisting structure of a nuclear-powered ship designed to protect its reactor from a collision has been evaluated in that it absorbs the kinetic energy of the striking ship through its own structural destruction. But it is reported that recent researches have developed collision -resisting structure of a resisting type intended to minimize the demage of one's own ship and mainly to destroy the bow of the striking ship in collision [3][2][3].

In order to design such a barrier of a resisting type it is necessary to precisely estimate the load acting on the side structure of the nuclear-powered ship. In the case of the side structure of a resisting type this load is found by the following procedure.

- (1) To find the relation between the load and the deformation at the moment of collapse of the bows of the ships in collision.
- (2) To find the bow deformation by carrying out a collision simulation analysis by means of the above-mentioned relation.
- (3) To estimate the load corresponding to the bow deformation by using the load -deformation curve.

In order to find the collapse load it is necessary to analyze the ultimate strength of the bow construction but so far this analysis has scarcely been carried out [4] - [7], nor does any established method of its calculation seem to exist.

In this study, for the purpose of establishing the method of analyzing the ultimate strength of the bow construction and finding the load acting on the side structure, first, we have made a theoretical calculation by the FEM by means of an ideal mathematical model of the frame of bow construction. Next, in order to clarify the behavior of the bow collapse and verify the method of calculation, we have carried out static collapse experiments by using 1/10 scale models of the bows of a tanker and a container carrier and compared the results of the experiments with those of the theoretical calculation, thereby a reasonable agreement between the two has been confirmed. And further, we have estimated the collapse loads of bow construction of actual ships (tanker, container carrier and ice-strengthened ship) and obtained the load-deformation curves.

By using these load-deformation curves of bow construction we can estimate the load acting on other types of structure such as bridges, offshore structures when ships strike against them.

# 2. THEORETICAL ANALYSIS

When calculating the ultimate strength of bow construction, it is considered necessary, strictly speaking, to deal with bow con-

struction as a plate structure. But then it will entail a complicated process and will take a much time for computation. Therefore, in order to obtain the load-deformation curves, we regard the bow construction as an ideal frame structure with effective plate width and analyze the ultimate strength by FEM, which utilizes the plastic hinge method.

We regard the side structure of a nuclear-powered ship as rigid and we consider such a case as the bow collapsing one-sidedly in collision. According to the results of the experiment, the sub-structure between the transverse frames collapses as a unit





structure, and the weaker sub-structure collapses first. In calculation, we assume that the sub-structure collapses first at stem and down to stern. The load is applied to the frame section by forced displacement, and the loading point is shifted to the next frame after each sub-structure has collapsed.

As the side shell plate, the web plate of girders, etc. are considered to have already buckled under the maximum load, we have used the effective width of the buckled plate for an ideal mathematical model of the frame of the longitudinal member. The above-mentioned effective width is given in the following formula [8]

$$b_{e} = b \qquad \text{for} \quad \frac{b}{t} \le \sqrt{E/S_{y}}$$

$$b_{e} = t \sqrt{E/S_{y}} (2 - \frac{t}{b} \sqrt{E/S_{y}}) \qquad \text{for} \quad \frac{b}{t} \ge \sqrt{E/S_{y}}$$
(1)

where b is the plate width,  $b_e$  is the effective width of the plate, t is the plate thickness, E is the young's modulus and  $S_y$  is the material yield stress. The results of the box column experiment carried out by the authors [9] are in good agreement with the results of the calculation made with the above formula. According to the above mentioned experiment, the load decreases rapidly after it has reached the maximum. Therefore in this calculation, the load-deformation curve of longitudinal member is assumed as shown in Fig. 1.

#### 3. STATIC COLLAPSE EXPERIMENTS ON BOW CONSTRUCTION

Static collapse experiments have been carried out by using 1/10 scale bow models of a container carrier and a tanker (Fig.2, Fig.3). The test apparatus is shown in Fig. 4. The load acting on the bow model and the deformation and strain of the bow models were measured, and load-deformation curves and the mode of collapse were obtained.

Fig. 5 and Fig. 6 show the load-deformation curves of the models of a container carrier and a tanker. In these figures, peak load and the corresponding collapse mode are shown. The shaded portion collapsed under peak load and the blackened portion had collapsed before. The solid black circles in Fig. 5 and Fig. 6 show the results of the calculation by FEM, which are in good agreement with the results of the experiments.

The sub-structures between the frames are numbered (1), (2), ---- in order fore and aft, as shown in Fig. 5 and Fig. 6. Regarding the container carrier, we considered that theoretical collapse occurs in the order of (1), (3), (4), (5), (2),which, however, changed to (1), (5), (4), (3), (2) in experiment. This disagreement is considered to be due to the following reason. The difference in strength between (3) and (5) is so small that the strength of (5) decreased in experiment because of end effect. As for the tanker, the analytical and experimental orders of collapse agree with each other.

In the case of the model of the container carrier, the load decreases rapidly after peak load is reached, and the entire load-deformation curve is sawtoothed. In theoretical calculation, we can obtain only the peak load, and in order to obtain the entire load-deformation curve we must study further in the future. With the tanker model, the load does not decrease so rapidly after peak load is reached.

With the tanker model, a big discrepancy is noticed between calculation and experimentation when deformation exceeds 1200 mm. This is probably because experimentally the upper deck buckled totally at the moment of such deformation, and afterwards the loading capacity of the upper deck decreased remarkably. The total buckling of the upper deck is not treated in this calculation. For reference, we calculated the maximum load, supposing that the loading capacity of the upper deck is entirely lost after buckling. The results of calculation



33

tanker

375

FR No 119 124 129 134

375 320

139 144

Bow model of

Fig.4 Test of Bow model



077

Fig.3

270\_150

260

Bow model of con-

tainer carrier

325

260 27.

FR. No 309 313 317 321

Fig.2



230





# 4. ULTIMATE STRENGTH OF BOW OF ACTUAL SHIP

As typical ships, we chose a container carrier, a tanker and an ice-strengthened ship. Their principal dimensions are shown in Table 1. The ultimate strength of the bow structure of these ships is calculated, based on the method mentioned in Chapter 2. In consideration of symmetry, we have modeled a counterpart of the bow construction for calculation. The ideal mathematical model of the frame is shown in Fig. 7  $\degree$  9. The model is fixed at the collision bulkhead and the load is applied to the frame section by forced displacement. In the calculation, 242 MPa was used for yield stress. Fig. 10  $\degree$  12 show the results of calculation. "Full yield" mentioned therein means the load caused when the longitudinal member yielded entirely by axial load. The load resulting from "full yield" becomes larger than that obtained through FEM. Fig. 7  $\degree$  9 show with a mark () where the plastic hinge is produced when the maximum load is reached.

We compare the collapse loads of the bows of these three ships. As the collapse loads vary with sectional position we have taken up the collapse load arising midway between the forepeak and the collision bulkhead. These collapse loads are shown in Table 2. Generally the collapse load of the tanker is the largest, but when calculated per unit area, the load of the container carrier turns out largest. When we design the side structure of the struck ship, we must take into account not only the magnitude of the load but also the load per unit area.

#### 5. SOME CONSIDERATIONS ON COLLISION ANALYSIS

When the side structure of the struck ships is rigid, the deformation of the bow and the load acting on the side structure are calculated by collision analysis by means of the load-deformation curves of the bow as mentioned in Fig.  $10 \ 12$ . When the load-deformation curve is sawtoothed, the energy absorbing capacity of the bow is reduced, and the collapse deformation is intensified. Accordingly the load acting on the side structure becomes larger. But if the increase of load corresponding to the increase of deformation is not remarkable, the difference between the two is considered to be small.

Next, we consider the case where not only the bow construction but also the side structure of the struck ship collapses. Suppose the load-deformation curve of the side structure or other damaged structure is already obtained and is denoted by  $S_1$  in Fig. 13. The load-deformation curve of the bow construction is







Fig.8 Idealized model of tanker

# Table 1 Principal dimensions

Item		Container carrier	Tanker	Ice strengthend	
	L <sub>PP</sub> (m)	248.0	360.0	134.5	
	B (m)	32.2	69.0	32.2	
	D (m)	19.9	28.7	20.3	
	d (m)	12.0	22.75	7.8	
C	WT (ton)	35,000	409,000	11,200	

Table 2 Comparison of bow strength

	P (MN)	A(m <sup>2</sup> )	P/A(MN/m²)
Container carrier	88	74	1.19
Tanker	245	602	0.41
Ice strengthend ship	98	108	0.91



Fig.9 Idealized model of ice strengthend ship

denoted by  $S_2$  therein. The collapse deformations corresponding to the load  $P_A$  are  $d_1$  for the side structure and  $d_2$  for the bow construction. The total deformation is  $d_1 + d_2$ , and the load-deformation curve is denoted by  $S_3$ . Through the collision analysis using  $S_3$ , we can obtain the deformation of the side structure and bow construction. If the load-deformation curve of the bow construction is sawtoothed, the treatment becomes slightly complex, but it is made possible to analyze in the same way.

#### 6. CONCLUSION

In order to estimate the load acting on the side structure of the struck ship, we carried out experiments by using 1/10 scale bow models and studied the method of calculating the ultimate strength of the bow construction.

The theoretical calculation shows results in good agreement with those of the experiments and it is made possible to calculate the ultimate strength of the



Fig.10 Load-deformation curve of container carrier by FEM



Fig.ll Load-deformation curve of tanker by FEM



Fig.12 Load-deformation curve of ice strengthend ship

bow construction by FEM by using an ideal mathematical model of the frame.

Among the three ships treated in this paper, the collapse load of the bow of the tanker is the largest. But the load per unit area of the bow of the container carrier is also large. When we design the side structure of the struck ship, we must take into account not only the magnitude of the load but also the load per unit area.

Finally, the items to be pursued further are :

- (a) To develope the method of obtaining entire load-deformation curves, and
- (b) To establish the method of analyzing collision problems more precisely when not only the bow construction but also the side structure collapses.



Fig.13 Load-deformation curve of bow and side structure

REFERENCES

- 1. WOISIN, G., Bericht über Kollisionsshutzersuche, GKSS, 1976.
- 2. WOISIN, G., Conclusion from Collision Examinations for Nuclear Merchant Ships in the FRG, Proc. of Symp. on N.S. Humb., 1977.
- 3. RECKLING, K.A., On the Collision Protection of Ships, PRADS Sympo. Tokyo, 1977.
- 4. MINORSKY, V., Bow Loading Values (Bulbous bow) Task II, U.S. Maritime Adm., 1977.
- 5. MINORSKY, V., Development of Ship Loading Values (Bow in Collision) Task VIII, U.S. Maritime Adm., 1978.
- 6. RECKLING, K.A., Beitrag der Elasto und Plasto mechanik zur Untersuchung von Shiffscollision, Jahrbuch STG, 1976.
- 7. NAGASAWA, H., ARITA, K., TANI, M., OKA, S., A study on the Collapse of Ship Structure in Collision with Bridge Piers, Jr. Soc. of Nav. Arch. of Japan, Vol 142, December 1977.
- FAULKNER, D., A review of Effective Plating for Use in the Analysis of Stiffened Plating in Bending and Compression, Jr. of Ship Research, Vol 19 No.1, 1975.
- 9. OHNISHI, T., KAWAKAMI, H., YASUKAWA, W., and NAGASAWA, H., On the Ultimate Strength of Bow Construction, Jr. Soc. of Nav. Arch. of Japan, Vol 151, June 1982.