

**Zeitschrift:** IABSE reports = Rapports AIPC = IVBH Berichte

**Band:** 46 (1983)

**Artikel:** A method to assess the reliability of actual buildings

**Autor:** Zaupa, Francesco / Modena, Claudio / Odorizzi, Stefano

**DOI:** <https://doi.org/10.5169/seals-35858>

#### **Nutzungsbedingungen**

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

#### **Conditions d'utilisation**

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

#### **Terms of use**

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

**Download PDF:** 04.02.2026

**ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>**

## A Method to Assess the Reliability of Actual Buildings

Méthode d'évaluation de la sécurité des bâtiments

Methode zur Abschätzung der Gebäudesicherheit

### Francesco ZAUPA


Civil Engineer  
Università di Padova  
Padova, Italy



Born 1944, received his civil engineering degree at the University of Padova where he has been assistant professor at the department of civil engineering since 1970.

### Claudio MODENA

Civil Engineer  
Università di Padova  
Padova, Italy



Born 1946, received his civil engineering degree at the University of Padova, where he has been assistant professor at the department of civil engineering since 1972.

### Stefano ODORIZZI

Civil Engineer  
Università di Padova  
Padova, Italy



Born 1949, received his civil engineering degree at the University of Padova, where he has been research worker at the department of civil engineering since 1980.

## SUMMARY

A reliable and easy to use procedure is proposed, for the quantitative evaluation of the safety level of a building. The information coming from large scale and primary exterior inspections on a suitable sample of buildings is described in terms of symbolic entities, which are automatically processed. On this basis, once an appropriate safety criterion is fixed, a numerical determination of a statistically significant safety level can be obtained for a large urban settlement.

## RESUME

Une procédure sûre et d'application aisée est proposée pour évaluer quantitativement le niveau de sûreté d'un bâtiment. Les informations provenant de travaux d'inspection extérieure effectués à grande échelle sur un échantillon représentatif de bâtiments, sont traduites en termes symboliques, traités automatiquement par l'ordinateur. Sur cette base, et après avoir fixé un critère de sûreté approprié, on peut obtenir une détermination numérique d'un niveau de sûreté statistiquement représentatif pour un grand ensemble urbain.

## ZUSAMMENFASSUNG

Es wird ein zuverlässiges und leicht anwendbares Verfahren vorgeschlagen um den Sicherheitsgrad des Gebäudebestandes einer Region quantitativ zu erfassen. Die Informationen, die von einer Bestandesaufnahme einer grossen Anzahl bestehender Gebäude stammen, werden auf symbolische Zeichen übertragen, die dann automatisch verarbeitet werden. Mit diesem Mittel kann ein statistisch signifikativer Sicherheitsgrad von grossen Siedlungen bestimmt werden, sobald ein geeignetes Sicherheitskriterium angenommen worden ist.



## 1. INTRODUCTION

A general approach to the problem of giving practically a quantitative evaluation, in the statistical sense, to the safety level of a regional building consistence was presented in a previous paper [1], where reference was made to the old, most frequent, masonry works and to their vulnerability to the seismic actions.

The matter of discussion was concerned with the establishment of those criteria which could lead to the formulation on a function of safety of a building, on the base of relevant parameters giving a measure of resistance and stability.

A procedure was also described in some details to process the informations which could be obtained only from exterior, widespread and quick inspections, to develop automatically the structural parameters.

Here some new parameters are introduced, and a multiple regression analysis is carried out within the whole series to find out the most representative ones.

A quite homogeneous sample of 41 buildings of the provincia of Trento is employed as a test case. The sample shows multiple correlation coefficients which are approximately 0.8 in the case of the structural indexes of geometric kind, when related to the VK ratios of the well-known POR and VET methods.

This application has been worked out also to control the reliability of the procedure and the arrangement of function of the global safety level.

## 2. RELIABILITY OF A SAFETY CRITERION WITH REFERENCE TO A SAMPLE OF MASONRY BUILDINGS.

The structural consistence of a building was drawn in [1] from the values of some dimensionless parameters, which were called structural status indexes.

In another paper [2] a method of survey was described which could produce the quantities to form such status indexes. For the sake of completeness a standard survey schedule is shown in figure 1 and the status indexes employed are listed in the table presented in the following, together with their classification. The geometrical ones are explicated in figure 2.

In this study all the mentioned indexes are preliminarily taken into account. Restricting practically the sample to a set of buildings which could be sufficiently homogeneous as age, architecture, technology and utilization, the number of indexes seems but to be reducible to few significant ones, whose choice can be pointed out through statistical dependencies like linear correlations.

As to the evaluation of the global safety level, the authors proposed in [1,2] to use a convenient combination of the status indexes. In fact a linear combination was employed, whose weighting coefficient were said to be significant of the risk of being the corresponding parameters close to certain limit values, and, by comparison, a linear multiplication of some normalized parameters was worked out. Introducing the problem of the definition of the weighting coefficients, and hence of the reliability of the safety function, a useful starting information seems to be the degree of correlation of the structural parameters with those coming from the methods which are most commonly adopted while drawing or verifying a structure. In the present work reference was made to the italian code for the restoration of masonry buildings damaged dur-

## STRUCTURAL STATUS INDEXES

SOIL AND FOUNDATION PARAMETERS	SUPERSTRUCTURES PARAMETERS
a) Foundation soil.	a) Global indexes.
Identifier Attribution	aa) Ground floor.
1 Lack of information.	I 1 : Geometrical regularity index.
2 Loose soil with sloping surface.	I 2 : Compactness index.
3 Clayey soil with sloping surface.	I 3 : Concentration index.
4 Loose soil with horizontal surface.	ab) Vertical section.
5 Clayey soil with horizontal surface.	I 4 : Index of outer walls slenderness.
6 Sloping hard rock.	I 5 : Index of main walls slenderness.
7 Horizontal hard rock.	I 6 : Index of standard story height.
b) Groundwater level.	b) Local indexes.
Identifier Attribution	ba) Plant characteristics.
1 Lack of information.	I 7 : Index of eccentricity of the center of twist (in two orthogonal directions x, y;).
2 Water table at ground level.	I 8 : Index of masonry percentage on the gross total area of walls.
3 Medium deep level ( $1 < d < 3m$ ).	I 9 : Index of masonry percentage on the covered area.
4 Deeper level ( $d > 3m$ ).	I 10 : Ratio between external pier and adjacent opening widths.
c) Structural typology.	I 11 : Ratio between internal pier and adjacent opening widths.
Identifier Attribution	I 12 : Index of linear density of stiffening walls.
1 Lack of information.	I 13 : Index of normalized free length of a wall.
2 Non-existent foundation. Ground floor walls unbound and built directly on the ground.	I 14 : Index of openings percentage of a wall.
3 Non-existent foundation. Well connected ground floor walls.	I 15 : Ratio between external pier length and adjacent opening height.
4 Individual footings.	I 16 : Index of slenderness of a wall between two rigid floors.
5 Unbound continuous beams and individual footings.	I 17 : Index of normalized height of a story.
6 Countinuous beams or combined foundations with regular connections.	bb) Vertical section characteristics.
7 Mat foundations.	I 18 : Index of normalized height of a story.
d) Constitutive material of the foundations.	I 19 : Index of normalized height of a story.
Identifier Attribution	
1 Lack of information.	
2 Natural stone walls.	
3 Chain bond or brickwork.	
4 Reinforced or unreinforced masonry.	

Table 1 Structural status indexes.



ing the last Irpinia earthquake [ 3 ].

The sample to which the analysis is applied is an extension of the one illustrated in [ 1 ], excluding the coded buildings whose data were not complete.

As an example the statistical distribution of indexes I 3 and I 4 are shown in figure 3.

The high degree of correlation exhibited by some couples of structural indexes, e.g. I 4 and I 6, I 13 and I 14, whose linear correlation coefficients are about 0.8, clearly indicates the possibility to reduce their number.

On the same sample the VK values (i.e. the ratio  $V$  between the ultimate shear force at a floor level to the total weight, multiplied by a safety coefficient  $K$ ) have been computed, according to the POR and VET methods, taking in case as reference values those given by the italian standards [ 3 ].

The statistical distributions of VK are shown in figure 5a(POR method) and 5b(VET method), for seismic forces acting in one of the principal directions of the buildings.

The reliability of the obtained results can be firstly judged by comparison of figures 5a,b, and figures 4a,b, where the statistical distribution of the global safety indexes obtained from the two formulations of the safety function proposed in [ 1 ] are plotted, for a slightly reduced sample.

Obviously the VK values define only the safety against horizontal actions.

Hence a total safety function should be more reliable if expressed by means of more comprehensive parameters, like those proposed above.

### 3. CONCLUSIONS

The aim of this study has been to assess the reliability of a general procedure which should lead to evaluate the structural state of existing buildings.

The procedure was proposed by the authors in [ 1 ] and [ 2 ]. Quite a significant agreement has been found with the outcome of some standard methods to calculate the horizontal resistance of a building.

To the authors opinion the procedure is still to be improved as regards the choice of the representative parameters and their relative calibration, even with respect to the different characteristics of the sample examined and to the different limit states which can be considered. In this light a sample of buildings of Castelgrande (Potenza), which suffered various damages during the last Irpinia earthquake (table 2), is actually under investigation.

### REFERENCES


1. ZAUPA F., MODENA C., ODORIZZI S., Evaluation of the safety level of existing buildings with particular reference to seismic actions. 7th ECEE, September 1982, Athens.
2. ZAUPA F., MODENA C., ODORIZZI S., Sul problema della valutazione del livello di sicurezza degli edifici esistenti con particolare riferimento alle azioni sismiche. L'Industria delle Costruzioni, Gennaio 1982.
3. Circolare LL.PP. 30 Luglio 1982, n. 21745. Istruzioni relative alla normativa tecnica per le riparazioni ed il rafforzamento degli edifici in muratura danneggiati dal sisma.

BUILDINGS PROPERTIES						DAMAGES DISTRIBUTION									
Building Identifier	Number of stories	Vertical structures	Horizontal structures	Roof structure	Roof covering	Damage investigation made at story	Splitting of orthogonal not connected walls	Slipping of floor joists/roof struc. from bearing walls	Cracks at the headers over opening	Vertical/horizontal cracks in the walls	Diagonal cracks in the walls	Cracks nearby flues or niches	Distributed cracks on the walls	Damages at the roof covering	Other failures
1	(*) U.G.+2	Stonework	Timber	Timber	Brick	R.S.	*						****	*	
4	U.G.+2	Mixed stonework	Steel joists and brick	Timber		U.G.	*								
			Timber			1°	*					**	*	**	
			Timber			2°	****			**				**	
5	3+R.S.					R.S.	*	*						*	
6	2	Mixed stonework	Steel joists and brick	Timber		1				**				****	
						2			*			**			
7	2+R.S.	Stonework	Steel joists and brick	Timber	Brick	2°					*			***	*
10	U.G.+1 +R.S.	Mixed stonework	Steel/timber joists and brick	Timber		1°	****		*	*****				**	
12	U.G.+2	Mixed stonework	Timber	Timber		1°	**	**	***	*			****	*	
						2°	*	*	***	*				**	
13	1+R.S.	Stonework	Steel joists and brick			1				*					*
15	U.G.+3	Mixed stonework	Steel joists and brick	Timber		2°			****	**	***	*			*
			Timber joists			3°	*	*		*				**	
16	2	Steel		Timber	Brick	G.	**			**					
						1°	***							*	
17	1+R.S.	Stonework	Timber	Timber	Brick	R.S.	*			*					*


Table 2 Damages distribution on a building sample after Campania-Lucania earthquake of 23-11-1980.

(\*) Note: U.G.:underground story; G.: ground story; R.S.: roof story.






$$I_1 = a/b$$




$$\frac{A}{ds} = S^I$$




$$p = l_1 + l_2 + l_3 + \dots + l_n$$

$$I_3 = \frac{A}{p} / \frac{A}{4\sqrt{A}} = \frac{4\sqrt{A}}{p}$$




$$I_7 = \frac{x_{CT} - x_G}{x_{max} - x_{min}}$$


$$I_8 = \frac{y_{CT} - y_G}{y_{max} - y_{min}}$$




$$I_9 = \frac{A_n}{A_c}$$




$$I_{10} = \frac{A_n}{A_l}$$



$$I_{11} = \left( \frac{s_e}{l_e} \right) ; [e = 1, r]$$




$$I_{12} = \left( \frac{s_i}{l_i + l_{i+1}} \right) \min \frac{2}{2}$$




$$I_{13} = \frac{s_1 + s_2 + \dots + s_n}{L}$$



$$I_{14} = \frac{s_1 + s_2 + \dots + s_n}{n \cdot L}$$




$$I_{15} = \frac{l_0}{l_{rif}} ; [l_{rif} = 7.00 \text{ m}]$$



$$I_{16} = \frac{l_1 + l_2 + \dots + l_n}{L}$$




$$I_{17} = \left( \frac{s_i}{h_{i(i-1)}} \right) \min$$




$$I_4 = \left( \frac{h_e}{s_e} \right) \max ; [e = 1, r]$$


$$I_5 = \left( \frac{h_s}{s_s} \right) \max$$



$$I_6 = \frac{1}{n} \frac{\sum h_i}{h_{rif}} ; [h_{rif} = 3.00 \text{ m}]$$



$$I_{18} = \frac{h_e}{s}$$



$$I_{19} = \frac{h_i}{h_{rif}} ; [h_{rif} = 3.00 \text{ m}]$$

