

Zeitschrift: IABSE reports = Rapports AIPC = IVBH Berichte
Band: 54 (1987)

Artikel: Redistribution of inner forces in hyperstatic reinforced concrete structures
Autor: Mehl, M. / Haugeneder, E.
DOI: <https://doi.org/10.5169/seals-41948>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 01.04.2026


ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>

Redistribution of Inner Forces in Hyperstatic Reinforced Concrete Structures


Redistribution des forces internes dans des structures hyperstatiques en béton armé
Umlagerungen von inneren Kräften in statisch unbestimmten Stahlbetontragwerken

M. MEHL

Dr.Ing.
Consulting Engineer
Vienna, Austria



Manfred Mehl, born 1943, research assistant at TU-Vienna from 1971 to 1981 at the Institute of 'Stahlbeton und Massivbau', has specialized in reinforced concrete research. Since then he works in the field of design and construction of underground railways, partly doing some research in the FE-analysis of RC-structures.



E. HAUGENEDER

Dr.Ing.
Technodat
Vienna, Austria

Ernst Haugeneder is working for TECHNODAT, Technische Datenverarbeitung G.m.b.H. in the field of Finite Element Application and Development. He is also responsible for the Viennese office of the company. Ernst Haugeneder is 41 years old, married and father of two nice boys.

SUMMARY

The redistribution behaviour of an inner tunnel wall subjected to injection pressure is studied. From the calculation using the FEM several conclusions concerning the carrying behaviour and redistribution can be drawn. The FEM provides a model which explains the arising damage very well. Furthermore, the results agree with those of comparable experiments. As a comparison an estimate is carried out on the basis of beam theory supposing plastic hinges.

RÉSUMÉ

L'étude traite du comportement et de la redistribution des efforts sur la surface intérieure d'un tunnel par suite de pressions d'injection. Sur la base de calculs à l'aide de la méthode des éléments finis, plusieurs conclusions sont tirées sur la résistance et la redistribution des efforts. La méthode des éléments finis fournit un modèle qui permet également d'expliquer les dommages naissants. Les résultats concordent avec ceux d'expériences comparables. Une estimation est faite sur la base de la théorie de la poutre supposant des rotules plastiques.

ZUSAMMENFASSUNG

Am Beispiel einer durch Injektionsarbeiten überbeanspruchten Tunnelinnenschale werden die Umlagerungsvorgänge studiert. Aus der Nachrechnung mit Hilfe der FEM können einige Schlüsse auf das Tragverhalten und den Verlauf der Umlagerungsvorgänge gezogen werden. Die Nachrechnung liefert ein gutes Modell zur Erklärung der aufgetretenen Schäden, ebenso zeigt sich eine gute Übereinstimmung mit Ergebnissen aus vergleichbaren Versuchen. Zum Vergleich wird eine Abschätzung auf der Basis der Stabtheorie unter Annahme von plastischen Gelenken durchgeführt.



1. DESCRIPTION OF THE SITUATION

Water seepage was observed to occur over large regions of a tunnel between slurry trench walls, shown in figure 1. In order to rectify this the leaking regions were impregnated with waterproofing agent by the PU-method. During the injection work the appearance of horizontal cracks in the region about the middle of the wall was observed upon which the injection work was stopped. The assessment of the damage showed that cracks of up to 1.6mm in width had occurred over a length of 30m and that the wall had bowed out to up to 17mm. The largest crack widths correlated approximately with the largest deflexion. The uncompressed wall had an average accuracy of $\pm 3\text{mm}$. The damage can be assumed to be caused by exceeding the permissible injection pressure combined with the growing of a gap between the inner wall and the slurry trench wall.

2. THE PROBLEM

What was aimed for was:

- .) a more exact explanation of the damaging process and cracking as well as a value for the highest injection pressure.
 - .) an estimation of the damage sustained by concrete and reinforcement on the outer side of the wall which is obscured from view.
- From the calculations one could expect to be able to draw conclusions concerning the redistribution process.

The chosen example seemed especially advantageous due to the following:

- .) The calculation procedure for an existing situation with unambiguous loading history limits the width of the spectrum of possible interpretations.
- .) The different reinforcement strengths and effective heights do not correspond to the stress resultants occurring under elastic conditions and consequently can be expected to cause large redistributions of the inner forces.




Fig. 1 Cross section of tunnel with cracked region




Fig. 2 Cross section with reinforcement




Fig. 3 Ultimate load: FE-mesh and deformation

3. FINITE ELEMENTE ANALYSIS

3.1 Fundamentals

There are a great number of numerical models used for reinforced concrete (see e.g. /1,2/).

The material model for reinforced concrete used in the present work is based on the following assumptions:

a) Restrictions of crack width and crack spacing require a minimum reinforcement distributed over the whole structure. This reinforcement is imagined to be smeared. Consequently reinforced concrete is treated as a compound material.

b) In compression the material is mathematically described by a 3-D plastic-isotropic hardening model based on a formulation of Shareef and Buyukozturk /3/ (fig. 4a)

c) The hardening function follows closely the parabola of the Austrian Standards - ÖNORM. (fig. 4b). For uni-axial compression ideal plasticity is assumed after 2‰ total strain.

d) Below tensile strength the model behaves linear elastically. If one or both principal stresses reaches the tensile strength cracking is assumed. From then on no additional load can be applied until the reinforcement is able to carry the load (fig. 4c).

Above 2.4‰ total tensile strain, again ideal plasticity assumed.

e) Concentrated reinforcement, e.g. as may occur in beams or panels, is modelled by additional bar elements or plane elements and a bi-linear stress-strain relationship for steel.




Fig. 4a Fracture envelope in the $\sigma_1 - \sigma_2$ plane




Fig. 4b Stress-strain diagram of the FE-model and of ÖNORM under uni-axial compression





Fig. 4c Stress-strain diagram of reinforced concrete under uni-axial tension

The model parameters are: the compressive and tensile strengths of concrete and the directions, cross-section areas and yield stresses of the reinforcement. The model has been tested on a series of simple examples with comparison to some well known experiments /4,6/. Also, a number of RC-beams have been analyzed. The collapse load as well as the type of failure agreed excellent with experience and analytical calculations according to the Austrian Standards. Details are described in /7/.

3.2 Results of the calculations

The finite Element calculations were carried out using the experiences from /7/. Summarizing, there are no extra restraints for the mesh layout necessary due to the nonlinear material behaviour. The chosen mesh is shown in fig. 3. The material parameters are for concrete: $\sigma_p = 37,5 \text{ N/mm}^2$, $\sigma_{cr} = 3,75 \text{ N/mm}^2$; for steel $\sigma_f = 510 \text{ N/mm}^2$.



a) cracked regions

b) Strains ϵ_{by}

Fig. 5 Status of overloading deformation at "m":
14.9 mm

According to the FEM calculation the injection pressure at collapse is slightly greater than 600 kN/m^2 .

At this load the largest strain on the inside of the wall is 2.1%, which would have caused crack widths of about 0.4 to 0.6 mm with the observed distances of 20 to 30 cm between the cracks. Conversely, from the observation of the largest crack widths of 1.0 to 1.5 mm one can conclude that the largest strains at these points are about 5%. Therefore, during the injection process the pressure must briefly have been substantially higher. Due to the movement of the wall the volume of the gap increased and the pressure was relieved. However, this caused the reinforcement to yield and so the cracks in the highly strained tensile regions of the concrete opened wide.

In order to assess the damage caused by overloading calculations using the FEM were continued up to a load of 650 kN/m^2 , i.e. just beyond the ultimate load. With a deflexion of 14.9 mm a strain of 4.4% occurred in the middle of the innerside of the wall. Figure 5 shows the occurring strains and the cracked zones. The reinforcing steel is so heavily strained in the crosssections "a", "m" and "b" that a further increase in stress is no longer possible. However, the largest strain of 13.6% in "a" is much lower than strains that have been measured in comparable experiments. In the crosssection "b" the concrete is strained about 2%. This is the highest level ever reached, which is also within permissible limits.

The redistribution process: In figs. 6 and 7 the process of deflexion, the concrete stresses and the steel stresses are plotted versus the applied load.




Fig. 6 a) Characteristic results on the regions of compression

b) Deflexion of "m"




Fig. 7 Characteristic results in the tensile regions

- (1) calculated ultimate load $p_u \sim 620 \text{ kN/m}^2$ ($600 < p_u < 650$)
- (2) calculated service load $p_s = 620/1.7 = 365 \text{ kN/m}^2$
- (3) cracking ($\epsilon_b \geq 0.1\%$) above $p_c = 230 \text{ kN/m}^2 \cong 620.3|8$
- (4) forces in reinforcement increase above $p_r = 460 \text{ kN/m}^2 \cong 620.3|4$

The numerical results show that from a load of 300 kN/m^2 onwards (just under half the ultimate) the first signs of a non-linear behaviour are evident. At the three most stressed points, "a", "m" and "b", the edge strains are greater than 0.1% , at these points the concrete starts to crack. At a load of 400 kN/m^2 (this approximately represents the permissible service load) the formation of cracks is so advanced that the reinforcement in "m" starts to sustain considerable tension. This situation diverges heavily from a linear elastic analysis where the bending moments in the edges of a clamped beam are twice as high as in the middle of the beam.




Fig. 8 cracked regions under service load

Figure 8 shows the distribution of cracked zones at service load.

At the ultimate load the inner forces are re-distributed such that they represent approximately the actual carrying capacities of the individual crosssections.

Comparison with experiments: The results of the calculations correspond with the experimental results of other published sources /8,9,10/. Redistribution starts immediately with the onset of cracking of the concrete and proceeds in continuity up to the ultimate load. Even with a further increase in deformation after reaching the ultimate load the strains that occur stay well under the permissible values. Plastic hinges in the sense of beam theory with actual rotations do not occur.

4. COMPARATIVE CALCULATION

As a control a comparative calculation was carried out based on beam theory. This was done using the assumption of plastic hinges and following /11/. The system and the individual load steps up to the occurrence of a failure under kinetic conditions are shown in figure 9.

Taking the effective span as reference length we obtain a value of 590 kN for the maximum possible pressure of injection. This represents a value barely under the load obtained via the FEM.

An important element in this method is the reaching of a value for the permissible rotation and a comparison of this with the rotation occurring in practice. In the given problem with prescribed deformation this is only possible via an estimate of the deflexion. In the given case the permissible rotation is not reached; not even if one takes into account the violation of Bernoulli's Hypothesis. However, this can only be seen as a rough estimate based on the geometrics of the situation.




Fig. 9 Comparative calculation based on plastic hinges: system will bending moments and load steps



5. SUMMARY

With this example of a single instance of damage due to forced deformation the FE analysis proved to be a powerful tool in understanding the mechanism of the load redistribution. The remaining insecurities are substantially less important than those associated with an estimate based on the occurrence of plastic hinges.

This example also shows, that load redistribution is, above all, a consequence of cracking of the concrete in the tensile regions already beginning with low load levels. An obvious rotation as would be expected cannot be observed; the strains stay below permissible values.

Literatur

- /1/ CHEN, W.F.: Plasticity in reinforced concrete. McGraw Hill 1982.
- /2/ MANG, H.A., J.E. EBERHARDSTEINER: Collapse Analysis of RC Shells Based on an New Fracture Criterion. Proc. of FE Analysis of RC Structures. Tokyo, Japan, 1985.
- /3/ SHAREEF S.S., O. BUYUKOTURK: Constitutive Modelling of Concrete in Finite Element Analysis. MIT Report No. R 83-16, 1983.
- /4/ KUPFER, H.: Das Verhalten des Betons unter mehrachsiger Kurzzeitbelastung unter besonderer Berücksichtigung der zweiachsigen Beanspruchung. DAST-Heft 229, 1973.
- /5/ LIN, T.C.Y., A.H. NILSON, O.F. SLATE: Biaxial Stress- Strain Relations for Concrete. ASCE Vol 98, ST 5. (1025-1034) 1972.
- /6/ FALKNER, H.: Zur Frage der Rißbildung durch Eigen- und Zwängsspannungen infolge Temperatur in Stahlbetonteilen. DAST-Heft 208, 1969.
- /7/ HAUGENEDER, E., M. MEHL: Nichtlineare Berechnung von Stahlbeton mit Finiten Elementen. Forschungsbericht des BMfBT, Österreich. In Vorbereitung.
- /8/ WOIDELKO E.-O., SCHÄFER K., SCHLAUCH J.: Nach Traglastverfahren bemessene Stahlbeton-Plattenbalken. Beton- und Stahlbetonbau 1986, S.197-201, 214-248.
- /9/ SCHLAICH J., STEIDLE P.: Tragfähigkeit und Verformbarkeit von Stützen bei großen Verschiebungen der Decken durch Zwang. Beton- und Stahlbetonbau 1986, S. 230-235.
- /10/ BIEGER K.-W., MO Y.-L.: Zur Momentenumlagerung in Stahlbeton-Rahmentragwerken. Beton- und Stahlbetonbau 1985, S. 94-99, 137-140.
- /11/ DILGER W.: Veränderlichkeit der Biege- und Schubsteifigkeit bei Stahlbetontragwerken und ihr Einfluß auf Schnittkraftverteilung und Traglast bei statisch unbestimmter Lagerung. Deutscher Ausschuß für Stahlbeton, Heft 179, Berlin: W. Ernst & Sohn, 1966.