

Zeitschrift: IABSE reports = Rapports AIPC = IVBH Berichte
Band: 57/1/57/2 (1989)

Artikel: Fatigue resistance of a steel railway bridge
Autor: Bogaert, Philippe van
DOI: <https://doi.org/10.5169/seals-44272>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 21.02.2026

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>

Fatigue Resistance of a Steel Railway Bridge

Résistance à la fatigue d'un ponts-rail

Ermüdungswiderstand einer Eisenbahnbrücke

Philippe VAN BOGAERT

Dr. in applied sciences
Belgian Railway Co.
Brussels, Belgium



Philippe Van Bogaert, born 1951, graduated in civil engineering at RUG — Ghent University in 1974, and PhD in appl sc RUG in 1987. For one year he was assistant at Ghent University, and since 1977 he is employed by SNCB's Bridge Department, and largely concerned with the design of both steel and concrete railway bridges.

SUMMARY

The paper describes different designs and optimization of a tied arch railway bridge. The design criterium for fatigue damage due to the several loading spectra, was chosen to be the spectrum corresponding to the largest local stress variation. In the case of a completely optimized structure, fatigue resistance becomes more limiting than ultimate limit state of load-carrying capacity.

RÉSUMÉ

Différents projets, ainsi que l'optimisation d'un pont-rail en bowstring sont décrits. Le critère du dommage causé par la fatigue due aux différents spectres de chargement, est choisi en fonction de la variation de contrainte locale maximale. Dans le cas d'une structure totalement optimisée, la résistance à la fatigue est un critère plus contraignant que l'état limite ultime de résistance.

ZUSAMMENFASSUNG

Dieser Beitrag beschreibt verschiedene Entwürfe und die Optimierung einer Stabbogen-Eisenbahnbrücke. Als Bemessungsbedingung wurde aus verschiedenen Ermüdungslastfällen derjenige mit dem grössten lokalen Spannungsunterschied ausgewählt. In einem vollständig optimierten Tragwerk wird die Ermüdungsfestigkeit und nicht die Tragsicherheit massgebend.



1. INTRODUCTION

Prevention of fissuration by fatigue is important, especially in the design of steel bridges that are to support large live loads. The numerous fatigue design codes [1] [2] are concerned with the analysis of fatigue details, which are mostly due to the welding of the bridge-elements. Therefore these details are only known at the actual construction stage. Hence, the designer has to estimate fatigue damage, aiming to avoid, but not being fully able to exclude all fatigue-sensitive construction details.

While designing the railway bridges at Landegem (Belgium), it seemed possible, with moderate success, to account for fatigue, and to draw some conclusions concerning stress limits to adopt. The tied arch bridges that are discussed further were built to suppress a local narrowing in the deviation canal of the river Lys. First two single track bridge decks are constructed on both sides of an existing bridge, the latter being replaced afterwards by a double track bridge.

2. BRIDGE DESIGNS

Different solutions were examined for the superstructure. Among them, the first classical solution consisted of the construction of two pillars on both future canal shores, supporting a central steel bridge deck with 4 m high plane web girders. Two side spans of steel-concrete girders would complete the bridge. For various reasons, such as the presence of existing buttress-walls at the location of the piles, it was decided that three 86 m one-span steel decks were to be preferred. From experience-exchange with Deutsche Bundesbahn [3], the construction of tied arches with vertical suspension hangers was examined (fig.1). A prelimi-




Fig 1 Tied arch with vertical suspension hangers




Fig 2 Triangulated hangers

nary analysis, based on the principles that are emphasized further, showed that total weight of construction steel for the three bridges would be about 1455 tons



lations being reversed. For design purpose, it was assumed that the determining spectrum for the deck's main girders, corresponds to an influence length equal to the distance between suspension nodes. These girders consist of flange plates welded to webs, to which are again welded the webs of transverse stiffeners. Consequently they belong to ECCS-class 112. Using Wöhler's curve, the allowable stress variation for the adapted design spectrum becomes $\Delta\sigma_{AD} = 125 \text{ N/mm}^2$. Hence, during design the additional local bending between transverse deck stiffeners and the overall extension of main girders were disregarded.

In a similar way, it was assumed that the arch's box section (ECCS-class 100) spectrum corresponds to the total arch length, thus disregarding any local variation due to suspension node's reactions. Both assumptions were found to be

design	1	2	3
arch $\Delta\sigma$ (dam.)	151.2 (1.345)	136.1 (0.899)	78.67 (0.115)
deck $\Delta\sigma$ (dam.)	123.2 (0.947)	102.3 (0.472)	114.9 (0.729)

Table 1 Stress variations and damage

accurate since, after complete analysis of each structure the stress variations (in N/mm^2) from table 1 were found, the numbers between brackets being the total fatigue damage due to all stress spectra.

Table 2 summarizes the values of δ_m , the material's partial safety factor for ultimate limit state, that was determined for both cases of steel quality Fe37 and Fe42.

design	1	2	3
Fe37 deck	1.050	0.942	0.914
arch	1.017	0.868	1.319
Fe42 deck	1.290	1.183	1.147
arch	1.249	1.090	1.655

Table 2 Safety factor u.l.s.

As can be seen from table 2 Fe42 had to be used in the final design. However as it was emphasized in member 2, a more accurate choice of the deck's sections lengths would have permitted the use of Fe37, thus making predominant the criterion of fatigue.

More important fatigue details are present in the shorter elements of the bridge deck, namely the orthotropic plate with closed section stiffeners. Evidently, obtaining the same safety for an equal lifetime, will submit these elements to a




Fig 5 Main girder and continuous closed section stiffener

many larger number of loading cycles. The stiffeners have delicate welding details, such as the joining of their webs with the deck plate (joint I), and the continuous passage through the transverse stiffener's web (joint II). The latter was shaped as a cardioid [6] to avoid stress concentration. The welding length of joint II is determined by the allowable stress variation amplitude. Both joints I and II belong to ECCS-class 80, the local spectrum allowing a stress variation of 60 N/mm^2 . During design it was assumed that the local bending stress variation spectrum is predominant. A full analysis showed the damages summarized in table 3. Hence, although there appears some greater importance of the local spectrum, the contribution of damage due to general effects cannot be neglected.

joint	local bending	general bending	total damage
I	64%	24%	88%
II	31%	21%	52%

Table 3 total damage closed stiffener joints

scale specimen of the orthotropic deck plate was tested on fatigue. A sample, shown in fig.6, of 3.6 m length, consisting of a deck plate with 2 closed section stiffeners, was submitted to pulsating bending. In all critical details strain gages were attached. A stress variation of 60 N/mm² was realized in these points.




Fig 6 Fatigue test

Consequently, the design values for the local spectrum have to be chosen very low. In the case that was discussed 60 N/mm² proved to be an accurate choice.

4. FATIGUE TEST

In order to verify the welding quality and the accordance with theory, a 1/1

In order to verify the welding quality and the accordance with theory, a 1/1 scale specimen of the orthotropic deck plate was tested on fatigue. A sample, shown in fig.6, of 3.6 m length, consisting of a deck plate with 2 closed section stiffeners, was submitted to pulsating bending. In all critical details strain gages were attached. A stress variation of 60 N/mm² was realized in these points. Transverse weldings were present and the passage through the transverse girder's web was simulated by the welding of stiffening plates 8 mm of thickness. Stresses' variations went up to 160 N/mm² at the mid-section's bottom. As the test was performed at constant amplitude, and since the critical spectrum of an element of 3.6m is far beyond the damage limit, no fissuration whatsoever might appear. Since, according to ECCS, beyond 5 10⁶ cycles no damage does occur, a safety of 1.5 was adopted, the test was stopped after 7.5 10⁶ loading cycles. No damage or fissuration was detected after this test.

5. CONSTRUCTION

This paper does not deal with the actual construction of the three bridges. However, it should be mentioned that the bridges

were assembled by placing first the decks, followed by the arches, to which the suspension hangers were already bolted. The gaps between the deck's nodes and hangers, due to the deflection caused by self-weight, were compensated by regulating the level of temporary bearings on construction towers.

One of the completed single-track bridges can be seen from photo 1. As yet, a testing programme for the completed bridges has not taken place. In the future some interesting data may be expected from it.

6. CONCLUSIONS

It was implied that, while designing even moderate sized steel railway bridges,



Photograph 1 Completed single-track bridge

fatigue resistance plays an important role.

Accurate use of verification codes, based on the most wide spectra enables to choose the allowable stress variations for different bridge elements. In those cases where optimized structure geometry has been achieved, prevention of fissuration caused by fatigue, becomes a more strict criterion than ultimate carrying capacity at limit state.

REFERENCES

1. ECCS Recommendations for the fatigue design of steel structures. ECCS, may 1985.
2. UIC Leaflet 778-1 R Recommandations relatives aux facteurs de fatigue à considérer lors du dimensionnement des ponts métalliques de chemin de fer 1st Ed Union Internationale des Chemins de Fer, jan 1981
3. KONRATH H. u JANCKE K., Stählerne Eisenbahn-Stabbogenbrücke über den Main in Frankfurt-Niederrad. Bauingenieur 54 1979
4. UIC Leaflet 702-0 Schéma de charges à prendre en considération dans le calcul des ouvrages sous rail sur les lignes internationales 3d Ed. Union Internationale des Chemins de Fer, jan 1976
5. VIRLOGEUX M. et al, Le pont-rail du Moulin (Nord). Travaux, oct 1984
6. HAIBACH E. u PLASIL I., Untersuchungen zur Betriebsfestigkeit von Stahlleichtfahrbahnen mit Trapezhohlsteifen im Eisenbahnbrückenbau. Der Stahlbau, sept 1983