Zeitschrift: IABSE reports = Rapports AIPC = IVBH Berichte

Band: 60 (1990)

Artikel: Stress transfer from steel beams to reinforced concrete columns

Autor: Nishimura, Yasushi / Minami, Koichi

DOI: https://doi.org/10.5169/seals-46511

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Mehr erfahren

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. En savoir plus

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. Find out more

Download PDF: 27.11.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch

Stress Transfer from Steel Beams to Reinforced Concrete Columns

Transfert de contraintes des poutres d'acier vers les poteaux en béton armé

Kraftübertragung von Stahlriegeln auf Stahlbetonstützen

Yasushi NISHIMURA

Lecturer Osaka Inst. of Technology Osaka, Japan



Graduated from Osaka Institute of Technology, Japan, 1973. Since 1984, he has been Lecturer at Osaka Institute of Technology. His search interests are analysis of beamcolumn joints, column bases and column joints in composite structures.

Koichi MINAMI

Assoc. Prof. Osaka Inst. of Technology Osaka, Japan



Graduated from Osaka Institute of Technology, Japan, in 1964, and received Dr. Eng. ceived from Kyoto Univ. in 1985. Since 1985, he has been Assoc. Prof. of Osaka Inst. of Technology. His research interests are analysis beams, columns, walls, joints, and frames in RC and composite structures.

SUMMARY

Use of structural system composed of steel beams and reinforced concrete columns has been thought to be more economical and flexible in structural design. This paper describes the mechanism of stress transfer from the steel beams to reinforced concrete columns through the joint. In this mechanism, the principle of prying action of the steel beam embedded in reinforced concrete column was applied to estimate the ultimate strength of joint, because of its simplicity and reasonable accuracy.

RÉSUMÉ

L'emploi de structures composées de poutres d'acier et de poteaux en béton armé s'est avéré nécessaire pour obtenir davantage d'économie et de flexibilité dans les projets de structures. Cet article décrit le mécanisme de transfert de contraintes au niveau des joints, des poutres d'acier vers les poteaux en béton armé. Le principe d'effet de pince à levier a été appliqué, dans ce mécanisme, sur la poutre d'acier noyée dans le béton du poteau, afin d'évaluer la résistance ultime du joint de liaison; ceci pour une raison de simplification et de précision acceptable.

ZUSAMMENFASSUNG

Tragsysteme aus Stahlriegeln und Stahlbetonstützen sind kostengünstiger und erlauben eine flexiblere Projektierung. Dieser Beitrag beschreibt die Kraftübertragung von Stahlriegeln auf die Stahlbetonstützen. Dabei wird die Spaltwirkung des im Beton eingebetteten Bewehrungsstabes zur Abschätzung der Knotentragfähigkeit herangezogen, da dies zu einer einfachen und vernünftig genauen Lösung führt.



I. INTRODUCTION

Recently in Japan, structural system composed of steel beam and reinforced concrete column is proposed. Reinforced concrete columns have excellent axial capacity and steel beams have excellent strength and ductility against bending and shear load. Therefore, it is reasonable to construct a building using reinforced concrete columns and steel beams. However, very little information is available on the stress transfer from the steel beam to the reinforced concrete column through the joint. The object of this study is to make the stress transferring mechanism of the joints clear theoretically and experimentally.

2. STRESS TRANSFERRING MECHANISM

Fig. 1 shows the mechanism of the stress transfer from the embedded steel beam to the reinforced concrete column through the interior composite beam-column joint. The mechanisms are illustrated by the free body diagrams of each members. As shown in Fig. 1, the forces acting in the steel beam consist of the bearing forces $x_b b \lambda F_c$ for below the bottom flange and above the top flange of embedded steel beam, the frictional forces Prc1/h and external load Prc. In this paper, this force system is called the prying mechanism. On the other hand, the system of acting in the lower and forces upper reinforced concrete columns consist of the bearing force, the frictional force $P_{rc}1/h$, tensile force $_{r}T_{y}$ of the longitudinal bars and external load $P_{\mbox{\scriptsize rc}}1/h$ and $N_{\mbox{\scriptsize rc}}.$ In this mechanism, the longitudinal bars in the joint




Fig. ! Stress Transferring Mechanism.

act for transmitting the bearing forces to the lower and upper columns.

3. ULTIMATE STRENGTH OF INTERIOR BEAM-COLUMN ASSEMBLY

The ultimate strength +m of interior beam-column assembly is given as,

$$t^{m} = \min. (m^{m}, p^{m})$$
 (1)

where $_{m}m$ and $_{p}m$ are the flexural capacities of the members and the shear capacity of the joint, respectively. The shear capacity of the joint is not dealt in this paper, because the object of this study is to estimate the mechanism of stress transfer from the steel beam to the reinforced concrete column through the joint.

The flexural capacities $_{m}$ m are estimated as,

$$m^{m} = \min. \left(b^{m}, c^{m}, be^{m} \right) \tag{2}$$

where $_{bm}$ and $_{cm}$ are the resisting moment of the beam and column, respectively. $_{bem}$ is the resisting moment for the prying mechanism of the embedded steel beam. $_{bm}$ and $_{cm}$ can be estimated by the superposed strength method easily. Therefore, a method for predicting the resisting moment capacity for the prying mechanism is discussed in this paper.

The steel beam is assumed to be rigid. As shown in Fig. I, The compressive stress block on the top and bottom flanges of the embedded steel beam has a uniform stress of $\lambda F_{\rm C}$, where $\lambda F_{\rm C}$ is the bearing strength of the concrete. The effective width of the concrete is assumed to be equal to the width of the




Fig. 2 Prediction of ultimate strength

embedded steel beam. On the base of these assumptions, the relationships between the resisting moment M and axial compression N of the concrete section at the top and bottom flanges of the embedded steel beam are given as,

$$m = n (1 - n / \lambda_1) / 2$$
 (3)

where m = $M/B_cD_c^2F_c$, n = $N/B_cD_cF_c$, λ_1 = $_bb\lambda/B_c$. These relationships are shown as N - M interaction curve $_{be}I_c$ in Fig. 2 (a). In eq. 3, the effect of frictional strength between the steel beam and concrete is not considered.

Interaction straight line beIr for the longitudinal bars is given as,

$$n = -2 \left(r p_t \cdot r \sigma_y / F_c \right) = -2 \cdot r \mu_t \tag{4}$$

where $_{r}p_{t}$ and $_{r}\sigma_{y}$ are the tension reinforcement ratio and the yield stress of longitudinal bars, respectively. Interaction line $_{be}I_{r}$ is shown in Fig. 2 (a).

N - M interaction curve $_{be}I_{rc}$ for the prying action can be obtained from using superposed method of interaction line $_{be}I_{r}$ on the interaction curve $_{be}I_{c}$. Accordingly, as shown in Fig. 2 (b), the resisting moment capacity is given by the following expressions:

$$n_0 \le n \le n_1$$
, $m = (n + 2 \cdot_r \mu_t) \{ 1 - (n + 2_r \mu_t) / \lambda_1 \} / 2$ (5)

$$n_1 \le n \le n_2, \qquad m = \lambda_1 / 8 \tag{6}$$

$$n_2 \le n \le n_3$$
, $m = n (1 - n / \lambda_1) / 2$ (7)

where,
$$n_0 = -2 \cdot_r \mu_t$$
, $n_1 = \lambda_1 / 2 - 2 \cdot_r \mu_t$, $n_2 = \lambda_1 / 2$, $n_3 = \lambda_1$.

As shown in Fig. 2 (c), using interaction curve $_{be}I_{rc}$, the resisting moment for prying action of embedded steel beam under axial compression n_a is obtained as $_{be}m$. In Fig. 2 (c), $_{b}I_{b}$ and $_{c}I_{rc}$ denote the interaction curves of the beam and column, respectively. Using these interaction curves, the resisting moment of the beam and the column under axial compression n_a is given as $_{b}m$ and $_{c}m$, respectively.

4. TEST PROGRAM AND TEST RESULTS


Table 2 Test and theoretical results

Specimen	Applied Axial Load N(kN)	Flexural Cracking Load P _{f1} (kN)		Diagonal Tension Cracking Load P _{cr} (kN)		Maximum Load P (kN)		Theoretical Values		
								Ptheo.(kN) Pmax./Ptheo.		
		P.L.	N.L.	P.L.	N.L.	P.L.	N.L.	P.L. N.L.	max. theo.	
ION	0	18.8	21.2	26.7	14.6	41.4	39.5	32.8	1.26	1.20
12N	514	32.4	42.0	32.4	45.5	50.5	48.4	32.8	1.54	1.48

P.L.: Positive Loading. N.L.: Negative Loading.

To verify this proposed mechanism of stress transfer and the method capable of predicting the ultimate strength of the joint, two interior steel beamreinforced concrete column assemblies were tested under reversed cyclic loading. Details of test specimens are shown in Fig. 3. The dimension of specimen and cross sections are identical for each specimen. Experimental variable was the applied axial load. The applied axial load was 0 and 20 % of the ultimate compressive strength $N_{\rm O}$ of the column. The mechanical properties of materials $\,$ are listed in Table 1.


Fig. 4 shows a hysteresis loop for each specimen. The ordinate represents the applied load at end of beam. The abscissa gives the deflection of the P2 beam relative to the column at the point of application of load. bP denotes the calculated ultimate flexural strength of steel beam. For each specimen, the hysteresis loop shows the reversed S-shape small with very energy dissipation. After the attainment of the maximum load, the strength reduction due to reversed for specimen I2N is remarkable. The strength reduction was caused by the crushing of concrete on the top and bottom flanges of the embedded steel as shown in Fig. 5. The above situation of confailure crete is similar to failure concrete block




(a) Overall dimensions, loading and cross sections.

(b) Detail of steel beam.

Fig. 3 Details of test specimens.





Hysteresis loops. Fig. 4

Fig. 5 Failure mode. for Specimen ION.

that is tested to investigate the bearing strength.

5. PREDICTION OF TEST RESULTS

N - M interaction curves according to the present analysis are shown in Fig. 6. The ordinate and abscissa present the axial load n and resisting moment m, respectively. be^{I}_{rc} , b^{I}_{b} and c^{I}_{rc} denote anism of embedded steel beam, steel beam $F_c: Compressive Strength. F_t: Splitting Strength of embedded steel beam, steel beam$

Table 1 Properties of materials.

		Steel			Reinforcing Bar				Concrete	
	σ_{y}	σ_{max} .	ϵ_{u}		$\sigma_{\mathbf{y}}$	σ_{max}	. ε _u	F_{C}	Ft	
	(N/mm ²)			(N/mm ²)				(N/mm²)		
£ 5.5	367	443	0.201	6 ø	181	288	0.290			
£ 8	319	424	0.259	D13	360	525	0.148	28.6	2.68	
R. 16	264	434	0.304	D16	378	554	0.189			




Fig. 6 Predictions (a) Details of test specimens.(b) Bearing strength.
of test results. Fig. 7 Bearing test.

and reinforced concrete column, respectively. The open circle shows experimental values. The coefficient λ of 1.5 was adopted, based on tests to simulate the bearing zone under a steel beam as shown in Fig. 7. The comparisons of predictions with test results are listed in Table 2. The predictions are good agreement with the test results.

6. APPLICATION TO JOINTS WITH ADDITIONAL REINFORCEMENT

This proposed method was applied to estimate the ultimate strength of steel beam — reinforced concrete column joints containing additional reinforcement; shear studs and reinforcing bars welded to the outside faces of the embedded steel beam, and steel beam — composite column joints. In predicting the ultimate strength of joints with additional reinforcement, the ultimate strength $P_{\text{theo.}}$ of the joints was given as,

$$P_{\text{theo.}} = P_{u} + \Delta P_{u} \tag{8}$$

where P_u is the ultimate strength obtained by eq. 5 - eq. 7. ΔP_u is an additional strength provided by additional reinforcement.

Figs. 8 (a) compares predictions with the test results of specimens with shear studs or reinforcing bars conducted by author [2]. In this test, shear studs were intended to increase the frictional strength between the steel beam and concrete. On the other hand, reinforcing bars were intended to increase the resisting moment capacity for prying action. In case of these specimens with shear studs, additional strength ΔP_u was given as $n \cdot Q_{st} \cdot pd / 1$, where n is the number of the shear stud at the above or bottom flange of embedded steel beam, Q_{st} (= $0.5 \cdot sta / E_c \cdot F_c$) is the strength per shear stud, sta is cross-sectional




Fig. 8 Application of proposed method

Reference	Specimen	Experimental Value	Theoretical Value						
	эрестиен	P _{exp} .(kN)	$P_{\text{theo.}}(kN)^{*)}$	P _u (kN)	$\Delta P_{\mathbf{u}}(\mathbf{k}\mathbf{N})$	Pexp./Ptheo			
	WS0002N	49.1	41.8	32.8	9.01	1.18			
2	WS0000N	50.0	41.8	32.8	9.01	1.20			
	WH0002N	58.2	43.2	32.8	10.5	1.35			
	NO-Ms 10	86.3	62.3	43.3	18.9	1.38			
	NO-Ms25	170.8	86.7	43.3	43.3	1.28			
3	N40-Ms 10	91.2	62.3	43.3	18,9	1.46			
	N40-Ms25	105.9	86.7	43.3	43.3				
	NO-Ms 50	152.0	111.8	43.3	68.2	1.36			
	A-01	314.8	285.4**)	_	_	1.10			
4	A-01R	337.3	285.4	-	=	1.18			
	A-04	329.5	285.4	-	-	1.15			
	A-001	282.4	285.4	_	-	0.989			

Table 3 Comparison of predictions with test results

*) $P_{theo.} = P_u + \Delta P_u$ $P_u : Ultimate strength for prying mechanism of embedded steel beam.$ $\Delta P_u : Additional strength obtained by additional reinforcement.$ **) Flexural strength of steel beam.

area , E_c and F_c is elastic modulus and compressive strength of concrete, respectively. On the other hand, $\Delta P_{\rm u}$ of specimens with reinforcing bars was given as $2 \cdot_{re} \cdot_{re} \sigma_y \cdot_{rd} / 1$, where σ_{re} is cross-sectional area of tension reinforcing bars welded at the above or bottom flange of embedded steel beam, $\rm re^O_y$ is the yield stress of the reinforcing bar. Figs. 8 (b) compares predictions with the test results of interior steel beam – composite column joints [3, 4]. In this case, N - M interaction curve be I src for the prying mechanism of embedded steel beam was obtained by means of superposition of the interaction curve ${}_{c}\mathrm{I}_{s}$ for the steel column section on the interaction curve ${}_{be}\mathrm{I}_{rc}$ obtained by eq. 5 - eq. 7. In these figures, the ordinate and abscissa represent the test results and predictions, respectively. The comparisons of predictions with test results are listed in Table 3. The predictions were shown to be in good agreement with the test results.

7. CONCLUDING REMARKS

The following remarks can be drawn from the discussion presented above.

- 1) The mechanism of stress transfer from the steel beam to reinforced concrete column was clarified experimentally and theoretically. In this mechanism, the principle of prying action of the steel beam embedded in reinforced concrete column was applied.
- 2) On the basis of this mechanism, a method capable of predicting the ultimate strength of joint was developed. The predictions were in good agreement with the test results.
- 3) This proposed method could be applied to estimate the ultimate strength beam-reinforced concrete column joints containing additional reinforcement and steel beam-composite column joints.

REFERENCES

- 1. NISHIMURA Y. and MINAMI K., Stress Transferring Mechanism in Interior Steel Beam-Reinforced Concrete Column Joint. Transactions of AIJ, No.401, 1989.7, pp.77-85. (in Japanese)
- 2. UEOKA T., HUKUDA T., NISHIMURA Y. and MINAMI K., Effects of Reinforcement on Strength of Beam-Column Joints in Mixed Construction. Summaries of Technical Papers of Annual Meeting, AIJ, 1986, pp.1309-1310. (in Japanese)
- 3. TANAKA T. and NISHIGAKI T., Experimental Studies on Steel Beam-Composite Summaries of Technical Papers of Annual Meeting, AIJ, 1972, Column Joint. pp.1505-1506. (in Japanese)
- 4. HASEGAWA N., HIJIKATA K. et al., Experimental Study on Steel Beam to SRC Column Connections (part 1) - (part 4). Summaries of Technical Papers of Annual Meeting, AIJ, 1987, pp.1221-1228.(in Japanese)