

Zeitschrift: IABSE reports = Rapports AIPC = IVBH Berichte
Band: 64 (1991)

Artikel: Testing for seismic stability using high power explosions
Autor: Ronin, V.Z.
DOI: <https://doi.org/10.5169/seals-49280>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 12.03.2026

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>

Testing for Seismic Stability using High Power Explosions

Essais de la résistance antisismique au moyen d'une explosion de grande puissance

Erdbebensicherheitsprüfung mittels einer Explosion grosser Leistung

V.Z. RONIN

Engineer

All-Union Scient. Res. Inst. of Transp. Constr.
Moscow, USSR

Tests for seismic stability of a full-scale model of the bridge section consisting of the frame- and massive-type piers mounting a 16 m long span structure (see Fig.1) have been carried out. The frame-type pier of 17 m elevation above the foundation edge is a three-dimensional structure consisting of four reinforced concrete posts joined at the top by a cast-in-place packing, and at the bottom with a foundation on the natural semi-rock base. The massive-type pier is of a traditional construction consisting of two rectangular-section reinforced concrete blocks. A metal packet loaded with concrete blocks is used as the span structure. The span structure has the total weight of 215 t.




Fig.1. General view of the railway bridge section model

The main purpose of tests was to check actual seismic stability of the frame-type railway bridge pier.

The seismic loads were simulated by explosion effects. Three explosion fields located on one side of the bridge section model and representing the totality of the well rows, were prepared. The number of wells amounted to 99 pieces. Well depth - 20 meters. From 300 to 637 kg of explosives were placed in each well of the explosion fields. The total weight of explosives used in the tests made 46.7t. The explosions were started from Fig.1. General view of the rows most remote from piers (see Fig.2). Duration of the explosion effect is 1.6 s.



Fig.2. Explosion effect

Oscillations of the bridge section and adjoining ground sections were registered by the standard engineering-seismomentering equipment with galvanometric recording. Data on displacement, speed and acceleration of the pier foundations, posts and packings of the frame pier, lower and upper blocks of the massive pier and span structure were fixed. Evaluation of the ground oscillation intensity proved it to be close 9 numbers of the MSK scale (ground accelerations reached 0.4 g). As a result of tests, a large amount of full-scale data was obtained making it possible to assess the errors of the employed methods of pier calculations receive information on the actual seismic stability of the structures under tests. The test results have proved the possibility of simulating the seismic effects of 9 numbers in force by a high power explosion. Analysis of the instrumental data obtained made it possible to make a conclusion of a high seismic stability of the frame-type pier.