Zeitschrift: IABSE reports = Rapports AIPC = IVBH Berichte

Band: 71 (1994)

Artikel: Aircraft maintenance hangar, Cardiff, Wales

Autor: Luke, Steven

DOI: https://doi.org/10.5169/seals-54147

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Mehr erfahren

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. En savoir plus

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. Find out more

Download PDF: 26.11.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch



Aircraft Maintenance Hangar, Cardiff, Wales

Hangar pour l'entretien des avions, Cardiff, Wales Hangar für die Flugzeugunterhaltung, Cardiff, Wales

Steven LUKE
Civil and Structural Eng.
Ove Arup & Partners
Cardiff, UK

1. INTRODUCTION

A new British Airways 3-bay hangar is sited at Cardiff Wales International Airport (Fig 1.) and provides an outstanding facility for the heavy maintenance of Boeing 747 aircraft. The £75M project encompasses a double and single bay 22,000m² hangar with a 6,000m² mezzanine floor, a 15,000m² support building, an aircraft ground run pen and a 35,000m² concrete apron. The hangar (Fig 2.) is equipped in each bay with full aircraft access docking, overhead cranage, aircraft undercarriage lifting platforms and specialist ground support services fundamental to the effectiveness of the maintenance operations.

The profile of the building steps down to suit the function within each part of the facility. The height of the hangar was reduced by utilising external tubular triangular shaped trusses (Fig 3). This structural form minimised the enclosed volume and heating costs. The approach also reduced the impact of the hangar on the surrounding area by softening the roof profile and providing an industrial facility of some distinction.

2. HANGAR FRAME CONCEPT

From the commencement of the project the supply and erection of the hangar steelwork was identified as a critical element of the works. Consequently, the

frame concept was developed to allow elemental fabrication and erection of the main steelwork members. Full space structures would have provided a lighter structural solution but minimum weight in this instance did not achieve minimum cost or programme.

3. STRUCTURAL DETAILS

In the hangar the main members are two continuous tubular steel space truss girders. One located over the hangar doors is 9m deep x 5m wide, and the spine girder located at the step between the high and low level roof areas is 14.5m deep and 8m wide. These girders



Fig. 1 - Aerial View Feb 1993



weigh 600 tonnes and 1000 tonnes respectively and are 232.5m long with spans of 153.75m and 78.75m. The total weight of structural steelwork in the hangar is 4000 tonnes and on the project as a whole is approximately 6000 tonnes.

The infill low level roof structure is formed with steel hollow section trusses two way spanning and supported by externally exposed triangular girders. The high level roof is formed with single span trusses. A detailed review of the structural systems is given in a paper by S. Luke [1].

4. CONSTRUCTION

The lifting procedure chosen by the steelwork fabricator for the main girders provided a notable event since both were lifted into position supported at two points approximately 200m apart using hydraulically operated lifting towers (Fig 4.). It is believed the structural roof members are the longest to be lifted by this method in Europe.

Construction commenced in May 1991 and was complete in April 1993. Following the Client fit out the first aircraft arrived for a maintenance check on the 1 June 1993, 38 months after commencement of the design, as planned at the beginning of the project.

5. CONCLUSION

The Cardiff base is a 'state of the art facility' and is designed to make sure that the highly skilled workforce achieves maximum efficiency. When an aircraft enters the hangar, the power-operated docking platforms (Fig 5.) close around it, so that the engineers can reach every part. As a result, overhaul work can begin within 20 minutes and this has been made possible by careful integration of design with maintenance operations.

Reference

1. LUKE S.J. British Airways Maintenance Hangar, Cardiff Wales Airport Proc. Instn Civ Engrs Structs and Bldgs 1993, 99, Nov, 439 - 453




Fig. 2 - Plan




Fig. 3 - Hangar Section



Fig.4 - Door Girder Lift Jan 93



Fig. 5 - Access Docking