

Zeitschrift: IABSE reports = Rapports AIPC = IVBH Berichte
Band: 75 (1996)

Artikel: Static and dynamic testing of structures with semi-rigid connections
Autor: Zdravkovi, Slavko / Milievi, Mili / Dreni, Dragoljub
DOI: <https://doi.org/10.5169/seals-56904>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 20.11.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>

STATIC AND DYNAMIC TESTING OF STRUCTURES WITH SEMI - RIGID CONNECTIONS

Zdravković Slavko, Professor
Milićević Milić, Professor
Drenić Dragoljub, Professor
Zlatkov Dragan, Assistant
Civil Engineering Faculty, Niš
Yugoslavia



Slavko Zdravković

Zdravković Slavko: b. 1947; C. Eng. 1972;
Dr. Sci. 1981; prof. 1992; Expert of Fed.
Min. of Sci., Tech. and Devel.
Milić Milićević: b. 1934; C. Eng. 1959; Dr.
Sci. 1980 ; prof. 1986 ; Chief of depart. for
Tech. mech. & Teor. of Struct.
Drenić Dragoljub: b. 1948; C. Eng. 1972;
Dr. Sci. 19881; prof. 1993.
Zlatkov Dragan: b. 1958; C. Eng. 1983.

Summary

The influence of semi-rigid structural connections on the static effects and dynamic characteristics of typic prefabricated construction "MINOMA", developed at the Civil Engineering Faculty in Niš, Yugoslavia, is discussed in this paper, based on the results of experimental testing and theoretical analysis.

Experimental tests has been carried out under static and dynamic load separately. This results are in close agreement with obtained analytical values.

1. Introduction

Researches carried out on the Civil Engineering Faculty in Niš, Yugoslavia lasting several Years have led to quite new system of typic reinforced concrete prefabricated structure called "MINOMA".

This construction includes all advantages of prefabricated construction system, but is more economical than similar ones known up to nowadays. As it is designed based on a new concept with semi-rigid connections and prestressing by means of a tie, it requires extensive investigations of long duration, both theoretical and experimental. Precision of some mathematical model parameters can be verified only by testing of considered structure. So, aforementioned structure has been tested under static and dynamic trial load and the results are presented in this paper.

2. Basic characteristics of structure type "minoma"

Carring structure is formed of straight precast concrete members wich are fixed in joints by means of either steel or aluminum connectors. The typic frame is supported so that the columns are fixed into prefabricated footings. The main characteristic of "MINOMA" structure is that joint stiffness is a little bit higher concerning the member stiffness.

Columns and beams are prestressed by adhesion, made of appropriate strength clas of concrete, with shaped crossection, reinforced byribbed bars.



The tie is made of high-quality steel wire according to IMS system (tendons $6 \Phi 7$ or $12 \Phi 5$ mm). Distance between frames is from 3m up to 6m, while columns length is changeable and depends on hall purposes.

Roof covering can be of durisol, gas-concrete or classic one consisting of concrete, timber or steel purlins.

Up to now, it has been investigated construction types: "MINOMA-1" span 12 m, "MINOMA-2" maximal span 20m and "MINOMA-3" up to maximal span 28 m.

3. Testing under the static load

Test under static load are based on Yugoslav code *JUS U. M1. 047*. Structure tests at the site have been carried out through two phases.

1st phase: Test up to elastic limit (serviceability limit).

2nd phase: Test up to failure (test of some members and substructures up to failure).

Static test have been performed through three phases of loading. Load which simulates dead load $q=253 \text{ daN/m}$ was applied by means of ties which were fixed into reinforced concrete floor and into the contra-beam constructd in the plane of the frame. The tie forces were observed by measuring strips with automatic temperature compensation. Initial force in the system tie was 83 kN.

Also, designation and disposition of measured cross-sections are shown in Fig. 1. and description of the construction is given in [7].




Fig. 1. Designation and distribution of measured cross-sections for static test

Measuring points along the frame were chosen at the sections with maximal static effects in order to be possible to observe them under trial load. Measuring instruments are placed according to principle "encircling of the section" although the cross-section is symmetrical one. Deflections were observed by means of survey instruments as well as by the following measuring instruments:

- measuring strips LY 10/120 and 100/120 Hottinger Baldwin
- deformeters with base $L=250\text{mm}$, $p=4,0 \times 10^{-6} \text{ mm/mm}$
- dilatometers with base $L=190\text{mm}$, $p=5,1 \times 10^{-6} \text{ mm/mm}$
- klinometers with scale precision $p=1 \text{ s}$
- deflectometers with scale precision $p=0,01 \text{ mm}$




Fig. 2 Designations and distribution of measuring instruments at the cross-sections

3.1 Results of static testing

The results about stresses, and deflections based on the measuring data are given in [8]. Bending moment diagram obtained on the base of test data is included in Fig. 4.

These values are also calculated according to slope-deflection method by use of STRESS-program and compared with corresponding obtained by testing. Agreement is not satisfying, in addition to everything else, constitutive equations of slope-deflection method according to STRESS-program do not include elasticity of connections of some members in joints.

So, according to expressions of mentioned refined theory derived in [8], based on experimentally determined fixing degrees of connections column-foundation and column-beam, bending moments due to dead load and applied load are calculated for the structure shown in Fig. 3 taking in account the real stiffness of these connections.

Effects of uniformly distributed load with intensity $q=253 \text{ daN/m}$ and applied tensile force into the tie $S=0,80Z=66,40 \text{ kN}$ are calculated separately and after that they are summed. Initial force in tie $83,0 \text{ kN}$ is reduced 20% because of loss during prestressing of the structure. According to previously given measuring data, fixing degree of connection column-to-foundation is $\mu_{ik}=0,4$ and of connection column-to-beam $\mu_{ik}=1,0$. Bending moments diagrams with analytically obtained values are given in Fig. In the final bending moments diagram, values calculated on the base of test data are given in brackets.




Fig. 3 The structure subjected to applied load and to the tie force




Fig. 4 Bending moment diagrams due to: a) applied load, b) tie force, c) summ under a) and b).

4. Testing under the dynamic load

The purpose of dynamic testing of structures is to define its real dynamic characteristics, i. e. resonant frequencies of basic modes in horizontal and vertical direction, shapes of vibrations at this frequencies, as well as corresponding coefficient of viscous damping. All of these parameters are the base for each mathematical modeling of a structure.

Experimental testing of dynamic characteristics of typic prefabricated structure "MINOMA-3" has been carried out applying the following experiment types:

1-Experiments with forced harmonic excitation

2-Free-vibration experiments

3-Experiments with ambient vibrations

Equipement for dynamic testing of structures in full scale consists of two basic systems that have to be compatibil each to other in the sense of diapason of frequent and amplitude composition. These two systems are: system for vibration excitation (Mechanical or electrohidraulical and registration system).

In the case of experiments with forced harmonic excitation, it was used the following equipment: Function Generator HP-3310A, Power Amplifier Model-114, Electrodynamic Shaker Model-113, as well as Kistler Accelerometer Model-305A, Kistler Amplifier Model-515, Spectrum Analyser Hp-3582A, Ploter Hp-7045B.




Fig.5 Functional presentation of measuring procedure of forced harmonic vibrations and free vibrations

Free vibrations have been generated in two different ways, so these experiments can be accomplished as:

- experiments with initial displacement,
- experiments when the external harmonic force is switched off.

In the case of experiments with ambient vibrations it was used the following equipment: Ranger Seismometer Model SS-1, Signal Conditioner Sc-1, Tape recorder HP-3960, Spectrum Analyzer HP-3582A I Ploter HP-7045B.




Fig.6 Functional presentation of measuring procedure of ambient vibrations

4.1 Results of dynamic testing

In the scope of detailed researches program, listed types of experiments have been performed. The results are given as time records of motion of material points of the structure and their mathematical processing in the form of amplitude spectrum (Furie transformation).

4.1.1 Experiment with forced harmonic excitation:

Functional presentation of the measuring procedure, applied equipment for measuring and generating of harmonic excitation are given in Fig. 5.

Obtained mode shape for horizontal direction of frame vibrations in plane is given in Fig. 7.




Fig. 7.



Time record of dynamic structure response and amplitude spectrum for horizontal direction is given in Fig. 8.




Fig. 8

Time record of harmonic decreasing functions and their amplitude spectra for horizontal vibration direction is shown in Fig. 9. and Fig. 10. This test was performed by sudden switching off the tie previously in the frame ridge.




Fig. 9




Fig. 10

4.1.2 Experiment with ambient vibrations:

Functional presentation is shown in Fig. 6.

In Fig. 11 it is shown time record of ambient vibrations and their amplitude spectrum for horizontal direction and in Fig 12 For vertical direction of vibrations in the plane of frame.




Fig. 11




Fig. 12

4.2 Calculating of frequencies for horizontal and vertical vibration direction

On the base of experimentally determined fixing degrees of connection column to foundation ($\mu_{ki} = \eta = 40\%$) and connection column to beam ($\mu_{ik} = \xi = 100\%$) bending moments are calculated, as well as circle frequencies for horizontal and vertical vibration direction, taking in account real rigidity of connections.




Fig. 13. Dynamically model of frame

Calculated values of circle frequencies are: for horizontal direction $\omega_h = 16.26 s^{-1} = 2,58 Hz$, for vertical direction $\omega_v = 22,56 s^{-1} = 3,59 Hz$.

5. Conclusion

It can be concluded from obtained results that fixing degree should not be neglected, both in static and in dynamic design, and particularly it should be paid attention about that, in analysis of prefabricated constructions. At static and dynamic testing, prefabricated construction "MINOMA" has shown complex behavior whose details are not presented here. Experimental researches and numerical analysis of considered structure have confirmed already known data, but also have pointed out new ones, particularly in the case of prestressing by the tie, as well as in the case of design of structure with semi-rigid connections of members. Calculated values of circle frequencies, based on dynamic model



of the frame (Fig. 13), are very closed to measured values for both directions of vibration ($\omega_{h,1} = 2,58\text{Hz}$ I $\omega_{v,1} = 3,59\text{Hz}$).

Obtained experimental results for dynamic characteristics represent the base for further experimental and analytical researches that would be carried out in order typical prefabricated system "MINOMA" security attest for all types of loading and influences according to available technical regulation. The first that follows will be testing of joints up to failure, as well as defining of design seismic characteristics (design spectra and design earthquake time histories of ground motion). Taking in consideration that in world literature and periodicals data about damping force (expressed in term of viscous damping) are poor for similar typic prefabricated structures, obtained results represents basic values for structural analysis under strong earthquake ground motions and for estimate of global seismic security.

The authors think that it is to be pointed out to the former circumstances in the corresponding regulations and supporting documents (comments or suggestions) because of missing the appropriate technical regulations for design and construction of the structures with members elastical fixed in joints at seismic regions.

References:

- [1] M. Milićević: Design of systems with semi-rigid connections by use of slope-deflection method. 17th Yugoslav congress of theoretical and applied mechanics, Zadar 1986. (in Serbian)
- [2] M. Milićević, S. Zdravković: Significance and part of semi-rigid connected members in joints at static, dynamic and problem of structure stability. 2nd Congress of Serbian Civil engineering constructors, Aranđelovac 1993. (in Serbian)
- [3] M. Milićević, S. Zdravković: Statics, dynamics and stability of linear girders with semi-rigid connections. Conference: Modeling, designing and testing of structures, Monograph, Niš, 1993. (in Serbian)
- [4] M. Milićević: Dynamic design of structures with semi-rigid connections. 1st congress of Serbian Civil engineering constructors, V. Banja 1986. (in Serbian)
- [5] M. Đurić, M. Milićević: Equations of forced damped vibrations of frame structures in plane. 14th Yugoslav congress of theoretical and applied mechanics, Portorož, 1978. (in Serbian)
- [6] M. Milićević, S. Zdravković, D. Zlatkov: Matrix analysis of systems with semi-rigid connections of members. Proceeding of 21st Yugoslav congress of theoretical and applied mechanics, Niš, 1995. (in Serbian)
- [7] S. Zdravković, M. Milićević, D. Drenić, H. Kapsarov: Determining of dynamic characteristics of "MINOMA" construction experimentally in real size and calculating using the model. Conference: Modeling, designing and testing of structures, Monograph, Niš, 1993. (in Serbian)
- [8] D. Drenić, S. Zdravković, M. Milićević: Influence of elastic connections of members in joints of the structure "MINOMA" on test results under static load. Conference: Modeling, designing and testing of structures, Monograph, Niš, 1993. (in Serbian)
- [9] M. Milićević, S. Zdravković, R. Folić, D. Zlatkov: Theoretical basis and dynamic design of the systems with semi-rigid connections of members with joints. 11 WCEE, Acapulco, Mexico, 1996. (in preparation)
- [10] S. Zdravković, M. Milićević, R. Folić, D. Zlatkov: Significance and part of elastic connections of members with joints in earthquake engineering. 11 WCEE, Acapulco, Mexico, 1996. (in preparation)
- [11] M. Milićević, S. Zdravković, R. Folić, D. Zlatkov, B. Kostadinov: Static and dynamic design of structures with semi-rigid connections. ABSE Colloquium, Istanbul, September 1996.