**Zeitschrift:** IABSE reports = Rapports AIPC = IVBH Berichte

**Band:** 999 (1997)

**Artikel:** Shear resistance of stud connectors with profiled steel sheeting

Autor: Hu, Xiamin / Wei, Chengjian / Zhao, Rongfei

**DOI:** https://doi.org/10.5169/seals-1071

# Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Mehr erfahren

#### **Conditions d'utilisation**

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. En savoir plus

#### Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. Find out more

**Download PDF: 27.11.2025** 

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch

# Shear Resistance of Stud Connectors with Profiled Steel Sheeting

# Xiamin HU Assoc. Prof. Nanjing Arch. & Civil Inst. Nanjing, China

Xiamin Hu, born 1958, Associate Professor at Nanjing Architectural Civil Engineering Institute. His research interests include composite structures reinforced, concrete structures and neural networks.

# Chengjian WEI Assoc. Prof. Naniing Arch. & Civil Inst.

Nanjing China

Chengjian Wei, born 1957, Associate Professor at Nanjing Architectural Civil Engineering Institute. His interests include neural networks, evolutionary computation, fuzzy system and artificial life

# Rongfei ZHAO

Engineer Nanjing Arch.& Civil Inst Nanjing China

> Rongfei Zhao, born 1968, Computer Engineer at Nanjing Architectural Civil Engineering Institute. His interests include neural networks, evolutionary computation, fuzzy system and artificial life

#### **Summary**

In this paper, based on the backpropagation model of neural networks, the details of the neural network methodology are presented to predict ultimate shear resistance of stud connectors with profiled steel sheeting. The analysed results show that the neural network predictions have a better agreement with the experimental data of the push-out tests than the predictions using other conventional methods.

#### 1. Introduction

The use of mechanical shear connectors is essential for ensuring composite action in the composite beams. The head stud is the most widely used type of connector in composite construction, especially in composite floors system with profiled steel sheeting. The direct shear strength of connectors may be evaluated by using a representative model test known as the push out test (Fig. 1). In the last two decades years many researchers have conducted the push-out test on studs with profiled steel sheeting and found that specimens that included the profiled steel sheeting reduced both the strength and stiffness of the connection. But since the structural behavior of the stud connectors with profiled steel sheeting is quite complicated and not amenable to simple calculations, until now no accepted calculation model has been developed to predict the shear strength resistance of stud connectors with profiled steel sheeting.

This paper investigates the feasibility of using neural networks to evaluate the ultimate shear strength of stud connectors with profiled steel sheeting. A neural network is an information processing system that essentially mimics the structure and function of the brain. The neural networks are particularly useful for evaluating systems with a multitude of nonlinear variables, but no predefined mathematical relationship between the variables is given. In this paper, based on the backpropagation model of neural networks, details of the neural network methodology are presented to predict ultimate shear resistance of stud connectors with profiled steel sheeting. Where the compressive strength and modulus of the concrete, the tensile strength of the stud material, the size of the stud, the geometry of the profiled sheeting are chosen as the critical factors of the nonlinear variables. The analysed results show that the neural network predictions have a better agreement with the experimental data of the push out tests than the predictions using other conventional methods.

#### 2 Neural Networks

Neural networks are computational models of many nonlinear processing element arranged in patterns similar to biological neuron networks. A typical neural network has an activation value associated with each node and a weight value associated with each connection. An activation function governs the firing of nodes and the propagation of data through network connection in massive parallelism. The network can be learned with examples through connection weight adjustment.




Fig. 1 Push-out test

# 2.1 The computational model of neuron

McCllock and Pitts<sup>[1]</sup> proposed a binary threshold unit as a computational model for an artificial neuron. This mathematical neuron computes a weighted sum of its n inputs signals,  $x_j = 1,2,...n$ , and generates an output of 1 if this sum is above a certain threshold u. Otherwise, an output of 0 results. Mathematically

$$y = f\left(\sum_{j=1}^{n} w_{j} x_{j} - u\right)$$

where f(.) is a unit step function, and  $w_j$  is the synapse weight associated with the jth input Using sigmoid function replace the Mccllock-Pitts neuron's threshold we get a generalized neuron model. The sigmoid function is a strictly increasing function that exhibits smoothness and has the desired asymptotic properties. The standard sigmoid function is the logistic function, defined by

$$g(x) = 1/(1 + \exp(-\beta x))$$

where  $\beta$  is the slope parameter. The computational model of neuron is  $\frac{w_1}{v_2}$ 

Fig. 2 Model of neuron

# 2.2 Network Architectures and Learning

illustrated in Fig 2.

Neural networks can be viewed as weighted directed graphs in which artificial neurons are nodes and directed edges are connections between neuron outputs and neuron inputs. Based on the connection pattern, neural networks can be grouped into two categories

- feed -forward network, in which graphs have no loops, and
- recurrent networks, in which loops occur because of feedback connection

A learning process in the neural networks context can be viewed as the problem of updating network architecture and connection weights so that a network can efficiently perform a specific task. The network usually must learn the connection weights from available learning patterns.

# 2.3 Multilayer feed-forward networks

Fig. 3 shows a typical three-layer perceptron. In general a standard L\_layer feed-forward network consists of an input stage, (L-1) hidden layers, and an output layer of units successively connected fully in a feed-forward fashion with no connections between units in the same layer and no feedback connections between layers.




Fig. 3 Typical tree-layer perceptron

The most popular class of multilayer feed-forward networks is multiplier perceptions in which each computational unit employs the sigmoid function. The development of the backpropagation learning algorithm for determining weights is a multilayer perceptron has made these networks the most popular among researchers and users of neural networks. The backpropagation learning algorithm is an iterative gradient algorithm designed to minimize the mean square error between the actual output of a multilayer feed-forward perceptron and the desired output. It requires continuous differentiable nonlineararities.

The BackPropagation Learning Algorithm as follows:

step 1 Initialized weights and offsets set all weights and node offsets to small random values.

step 2 Present Input and Desired outputs present a continuous valued input vector  $x_1, x_2, \dots x_n$  and specify the desired outputs  $d_1, d_2, \dots, d_m$ 

step 3 Calculate Actual Outputs use the sigmoid function to calculate outputs  $y_1, y_2, \dots, y_m$ 

step 4 Adapt weights

Use a recursive algorithm starting at the output node and working back to the first hidden layer. Adjust weights by

$$w_{ij}(t+1) = w_{ij}(t) + \eta \delta_{j} x_{i}^{'} + \alpha(w_{ij}(t) - w_{ij}(t-1))$$

where  $0 < \alpha < 1$ ,  $w_{ij}$  is the weight from hidden node *i* or from an input node to node *j* at time *t*,  $x_i$  is either the output of node *i* or is a an input,  $\eta$  is a gain term, and  $\delta_j$  is and error term from node *j*, if node is an output node then

$$\delta_i = y_i (1 - y_i)(d_i - y_i)$$

where  $d_j$  is the desired output of node j and  $y_j$  the actual output.

if node j is an internal hidden node, then

$$\delta_{j} = x_{j}'(1 - x_{j}') \sum_{k} \delta_{k} w_{jk}$$

where k is over all nodes in the layers above node j, internal node thresholds are adapted in a similar manner by assuming they are connection weights on links from auxiliary constraint-valued inputs.

step 5 Repeat by going to step 2

# 3. Prediction of the shear resistance

#### 3.1 Learning of the neural network

A total of 65 push-out test specimens reported by Bode and Hu <sup>[2]</sup> are used here to demonstrate the performance of the backpropagation model in the prediction of the shear resistance of stud connectors with profiled steel sheeting. All these tests were carried out in Gemany and originally reported by Roik and Buehrkner <sup>[3,4]</sup>, Roik and Lungeshausen <sup>[5]</sup>, Bode and Kuenzel <sup>[6,7]</sup>, Roik and Hanswille<sup>[8]</sup>. In these tests the holes were cut out in the decking and the stud connectors were welded through the holes to the beam beneath. For a given geometric configuration of a stud with profiled stud sheeting, the ultimate shear strength of the connection P depends on the strength and the size of the stud, on the strength and the stiffness of the concrete, on the geometry of the profiled steel sheeting and on the number of studs per rib. Therefore the following expression is gotten:

Mapping 
$$T: f(f_c', E_c, f_u, d, h-h_p, h_p, b_u, b_o, N_r) \rightarrow P$$

where  $f_c$  and  $E_c$  represent the compressive strength and modulus of the concrete,  $f_u$  is the tensile strength of the stud material, d is the diameter of the shank of the stud, h is the height of the stud.  $h_p$  is the over depth of the profiled sheeting.  $b_u$  and  $b_o$  represent the bottom width and top width of the profiled sheeting,  $N_r$  is the number of studs per rib.

Learning of the neural network is essentially carried out through the presentation of a series of example patterns of associated input and observed output values, and some preprocessing of the data is usually required before presenting the input patterns to the neural network. This usually involves scaling or normalization of the input patterns to values in the range 0-1. In this study, the learning example patterns consisted of 40 typical push-out test specimens collected by Bode and Hu<sup>[2]</sup>.

The neural network learned is constructed here with nine-nods in input layer, seventeen-nods in first hidden layer, twelve-nods in second hidden layer, fifteen-nods in third hidden layer and one node in output layer.  $\eta$  and  $\alpha$  are taken as 0.5 and 0.4. The following expression was used to normalize data

$$Normalized\ value = \frac{Actual value - Minimum value}{Maximum value - Minimum value}$$

Learning is carried out iteratively until the average sum squared errors over all learning patterns are minimized based on the above backpropagation model .This occurred after about 1552 cycles of learning.

# 3.2. Comparison of predicted values with experimental data

On the satisfactory completion of the learning phase, verification of the performance of the neural network is then carried out using patterns that were not included in the learning set. Push-out test specimens that only broadly resemble the data in the learning set were used to verify whether the neural network can generalize correct responses. Details of the testing pattern and the neural network predictions are summarized in table 1. A comparison of the predicted values  $P_p$  and experimental values  $P_e$  indicate that the neural network is capable of generalization and gave reasonable predictions. Using the ratio of experimental data to neural network predictions as an indicator, the mean and standard deviation of this ratio for the 25 specimens are 1.04 and 0.069, respectively, as shown in table 1.

Prediction using the expressions of Bode and Hu<sup>[2]</sup> and the expressions of Roik and Lungeshousen<sup>[9]</sup> were also carried out to compare with the neural network approaches. The average of experimental shear strength to predicted strength ratios given by Bode and Hu's expressions and Roik and Lungeshausen's expressions are 1.06 and 1.07, while the corresponding standard deviations are 0.073 and 0.131, respectively. The coefficients of correlation of experimental versus predicted results are 0.976 (neural network approach), 0.975 (Bode and Hu's expressions), and 0.951(Roik and Lungeshausen's expressions). This indicates that the neural network approach is more reliable than the conventional methods.

It is to be noted that EC4 methods were here not compared because the equations in EC4 are not suitable for the predictions of stud connectors with pre-punched decking<sup>[2]</sup>.

# 4. Conclusions

In this paper, a neural network for prediction of ultimate shear strength of stud connectors with profiled steel sheeting is presented. The study has demonstrated that the neural network can

Table 1 Comparison of Experimental Shear Strength  $P_e$  to Predicted Shear Strength  $P_p$ 

Specimen	$P_e$ , kN	Bode and Hu		Roik and		Neural Network		reference
				lungeshausen			·	
-		$P_p$ , kN	$P_e/P_p$	$P_p$ , kN	$P_e/P_p$	$P_{p}$ , kN	$P_e/P_p$	
7.1	74.0	75.71	0.99	76.56	0.97	72.28	1.02	3
7.2	78.0	75.71	1.03	76.56	1.02	72.28	1.08	3
2.1	44.5	39.93	1.12	41.22	1.08	41.84	1.08	4
2.2	38.0	39.93	0.95	41.22	0.92	41.84	0.92	4
3.1	82.0	76.89	1.07	68.86	1.19	77.65	1.06	4
3.2	78.5	76.89	1.02	68.86	1.14	77.65	1.01	4
5.1	42.0	39.09	1.07	37.71	1.11	41.30	1.02	4
5.2	49.0	39.09	1.25	37.71	1.30	41.30	1.19	4
8.1	79.0	73.09	1.08	62.66	1.26	75.84	1.04	4
8.2	85	73.09	1.16	62.66	1.36	75.84	1.12	4
11.1	84.5	76.89	1.10	68.86	1.23	76.93	1.06	4
11.2	85.0	76.89	1.11	68.86	1.23	76.93	1.07	4
SH0-1	75.5	78.81	0.96	80.63	0.94	76.32	0.99	6
CS0-1	77.1	78.95	0.98	85.04	0.91	82.60	0.93	6
<b>H</b> 1	114.0	111.65	1.02	118.14	0.97	111.35	1.02	7
H2	107.0	111.65	0.96	118.14	0.91	111.35	0.96	7
<b>H</b> 3	114.0	111.65	1.02	118.14	0.97	111.32	1.02	7
H4	130.0	111.65	1.16	118.14	1.10	111.32	1.17	7
H5	111.0	111.65	0.99	118.14	0.94	111.35	1.00	7
<b>H</b> 6	115.0	111.65	1.03	118.14	0.97	111.35	1.03	7
<b>H</b> 7	122.0	111.65	1.09	118.14	1.03	111.31	1.10	7
H8	123.0	111.65	1.10	118.14	1.04	111.31	1.11	7
D1	107.0	96.8	1.11	101.94	1.05	104.47	1.02	8
D2	96.5	96.8	1.00	101.94	0.95	104.47	0.92	8
D3	106.0	96.8	1.10	101.94	1.04	104.47	1.01	8
mean			1.06		1.07		1.04	<del>.</del> ,
Standard deviation			0.073		0.131		0.069	

effectively generalize correct responses that only broadly resemble the data tin the learning set. The predictions should be reliable, provided the input values are with the range used in the learning set. As new data becomes available, the neural network models can be learned readily with patterns that include these new data. The analyzed results indicate that the neural network has powerful capacity of dealing with inherent noisy or imprecise data. The neural network model was found to be more reliable than other conventional methods.

# References

- [1] Richard P. L.: An introduction to computing with neural nets. IEEE ASSP, 1987(4): 4-22
- [2] Bode H.; Hu Xiamin. Untersuchungen zur Schubtragfaehigkeit von Kopfbolzenduebeln. Forschungsbericht, Universitaet Kaiserslautern, August 1993
- [3] Roik, K.; Buerkner, K-E.: Beitrag zur Tragfachigkeit von Kopfbolzenduebeln in Verbundtraegern mit Stahlprofilblechen. Der Bauingenieur 56, S. 97-110, 1981
- [4] Roik, K.; Buerkner, K-E.: Untersuchungen des Tragerverbundes unterverwendung von Stahltrapezprofilen mit einer Hoehe >80mm. Studiengesellschaft fuer anwendungstechnik von Eisen und Stahl e. V., Projekt 40 ,Duesseldorf, 1980
- [5] Roik,K.; Lungershausen,H.: Verbundtraeger mit Stahltrapezprofilblechen mit Rippenhoehe >80mm. Studiengesellschaft fuer Anwendungstechnik von Eisen und Stahl e.V.,Projekt 99,Duesseldorf,1988
- [6] Bode, H.; Kuenzel, R.:Zur Anwendung der Durchschweißtechnik im Verbundbau. Forschungsbericht 2/1991, Universitaet Kaiserslautern, Maerz 1991
- [7] Bode, H.; Kuenzel, R.: Steifigkeit und Verformbarkeit von Vermitteln in Hochbau. International Symposium, Composite Steel Concrete Structures, vol. I Bratislava 132/1987
- [8] Roik, K.; Hanswille, G.: Gutachten fuer die Holorib GmbH zur Frage der Tragfaehigkeit von Kopfbolzenduebeln bei auf dem Verbundtraegerobergurt gestobenen Profilblechen. Bochum, Juli 1988
- [9] Roik, K.; Lungeshausen, H.: Zur Tragfaehigkeit von Kopfbolzenduebeln in Verbundtraegern mit unterbrochener Verbundfuge (Trapezprofildecken); Der Stahlban, H.58, 1989, S.269-273