Zeitschrift:	IABSE reports = Rapports AIPC = IVBH Berichte
Band:	999 (1997)
Artikel:	Health and safety monitoring of composite structures
Autor:	Wenzel, Helmut
DOI:	https://doi.org/10.5169/seals-1080

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. <u>Siehe Rechtliche Hinweise</u>.

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. <u>Voir Informations légales.</u>

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. <u>See Legal notice.</u>

Download PDF: 22.05.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch

Health and Safety Monitoring of Composite Structures

Helmut WENZEL Dr.-Ing. Vienna Consulting Eng. Vienna, Austria



Helmut Wenzel is a member of WC V of IABSE. He earned a PhD in Bridge Construction from the University of Vienna in 1978 and is the Managing Director of VCE, with offices in Vienna, Taiwan and Korea. Dr. Wenzel also teaches Bridge Design and Construction at the University of Vienna.

SUMMARY

Structures show a typical dynamic behaviour which may be addressed as "Vibrational Signature". Changes in a structure such as all kinds of damages leading to decrease of load-carrying capacity have effects on the dynamic response. This suggests the use of the dynamic response characteristic for evaluation of structural integrity. Monitoring or measurements of the dynamic response of structures makes it possible to get very fast knowledge of their actual condition.

1. THE BRIDGE MONITORING SYSTEM BRIMOS



Figure 1 : Typical signal and spectrum of the Nordbrücke in Vienna (composite structure)

Condense, Ston, Auduitation Coldulates a 89%. 9. Resaud Dr., Balliwito H., Componitation J., and Sprata fully an Alexanova Alexanova matalate bona - Randos en dato - dat grafinitor dago antosa fully no control (control) 16. (3.36.) Externo Chevascher 1916.

jaj - Edenie SMEL P. Gradu (ortski 2012) 61. Ortou (1946) 71. Scottusa (ortous ortous ortous ortou Ermediard (1848), m.s. A Seria edanisti - Ersko (1947) (1977) ortou (2015) (1978) For the purpose of **"System Identification"** a monitoring set-up was created, that enables quick an efficient recording as well as signal processing and report generation. The basis is the measurement of acceleration in a well determined layout of relevant locations of a structure. This provides data for the FFT analysis to generate the desired spectra. In addition data of the actual displacement of the structure is collected by infrared laser to gather information on the static behaviour and its relation to the dynamic action.

2. DATA PROCESSING

The collected data are processed to provide an informative report, which shall contain information on the signals itself in the desired units, the power spectrum of the readings, raw and smoothened, the drift of the readings and the relevant displacements. In a further step the readings of the various locations are combined to get an averaged spectrum and the related displacements. This is the basis for the animation of the Eigenform of the structure and the visualisation of it.



Figure 3 : First Eigenform calculated and measured of the Nordbrücke in Vienna

3. CONCLUSION

Due to the fact, that this bridge was monitored during 3 different stages, before, during and after the rehabilitation, valuable information was gained about the influence of the state of the structure on the response spectrum. From this basis it is tried to develop further tools to assess the quality of structures using data from dynamic monitoring.

