**Zeitschrift:** IABSE reports = Rapports AIPC = IVBH Berichte

**Band:** 999 (1997)

**Artikel:** Connection of steel beams to concrete-filled tubular columns

Autor: Shakir-Khalil, Hassan

**DOI:** https://doi.org/10.5169/seals-1093

### Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Mehr erfahren

#### **Conditions d'utilisation**

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. En savoir plus

#### Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. Find out more

**Download PDF:** 01.12.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch

878 POSTER

## Connection of Steel Beams to Concrete-Filled Tubular Columns

Hassan SHAKIR-KHALIL Division of Civil Engineering University of Manchester Manchester, England



Hassan Shakir-Khalil received
his BSc and MSc degrees in Civil
Engineering from the University
of Cairo, Egypt. He obtained his
PhD degree from the University of
Cambridge, England, UK. He has been
researching in the field of concrete-filled
tubular columns for the last 15 years.

### **Summary**

Tests have been carried out on 36 full scale beam-to-column connections. The connections were manufactured by connecting steel beams to concrete-filled tubular columns through either finplate or T-cleat connections. The columns used were either circular or rectangular (CHS & RHS) hollow steel sections. Except for the last eight specimens, all the other test specimens were symmetrically loaded.

# **Experimental Work and Numerical Analysis**

Table 1 gives a summary of all 36 specimens tested in this experimental investigation. The column tubing of all specimens is 2.8m long, and the column lengths have 15mm thick end plates. The side beams connected to the test specimens of series A-E were symmetrically loaded. However, the eight specimens of series 'F' had either one side beam, or their side beams were unsymmetrically loaded. The webs of the side beams of series A-D were bolted to 10mm thick finplates which had been welded to the columns. Finplates were replaced by T-cleats in series E&F as a result of the large out-of-plane deformations of the RHS walls to which the finplates were welded. Both types of connections are shown in Fig 1.

Figure 2 shows a schematic view of the test rig and test specimen. The rig consists of a base and an upper cross-head connected together by four vertical ties of steel hollow section. The rig is self contained, and the base is securely bolted to the laboratory strong floor. The rig has a head room of about 3m. The loads applied to the side beams by the hydraulic jacks are transferred to the beams through a platform and load cells. The loading platform was used in order to maintain the location of the jacks and at the same time to be able to apply the beam loads at any required eccentricity by simply moving the load cells to the new locations. The beam loads were applied at varied distances from the centre of the column. The beam and column loads, P<sub>2</sub> and P<sub>1</sub>, were increased proportionately, and the beam-to-column load ratio was mainly taken either 1:8 or 1:5.

The rig was originally designed for testing the symmetrically loaded specimens of series A-E, and was thus provided with no lateral bracing. A triangulated, stiff in-plane bracing, not shown in Fig. 2, was therefore welded between the vertical ties in order to ensure the lateral stability of the test rig before testing the unsymmetrically loaded beam-to-column connections of test series F. During the test procedure, all specimens were also laterally restrained at mid-




Fig.1 Finplate and T-Cleat Connections

height as shown by '7' in Fig. 2. This lateral restraint was connected at its other end to a stiff bracing system which was securely connected to the strong floor.

The test specimens were provided with electric resistance strain gauges and displacement transducers. The displacements were measured in the plane of loading and also transverse to the loading plane. Displacement transducers were also placed against the column end plates to record the column shortening and end rotations. The strain measurements were carried out over distances equal to three times and twice the lateral dimension of the steel hollow section above and below the finplate/T-cleat positions respectively, an arrangement that was found to be satisfactory.

The ABAQUS software package was used to model the test specimens of series 'F'. It can be seen from the numerical model shown in Fig. 3, that the side beams were not modelled, and neither were the bolt holes in the connection. The T-cleat stem was extended to model the beam, and the numerical model was only used to

Series		Column Size	Type of Connect.		Connect. Loading
A	168	.3x5CHS	Finplate	8	e2=e1
В	150x150x5RHS		,,	8	••
C	219	.1x6.3CHS	,,	2	,,
D	200	x200x6.3RHS	,,	2	,,
E	150	x150x5RHS	T-Cleat	8	••
FI	150	x150x5RHS	,,	4	e2=0.0
FII	150	x150x5RHS	**	4	e2 <e1< td=""></e1<>

Table 1 Sumary of Test Series




Fig.2 Test Rig and Specimen

Fig.3 Num. Model

predict the overall column failure. The boundary conditions at the top of the numerical model were similar to the experimental end conditions in which the top end of the column was fixed in position, and was allowed to rotate freely only in the plane of loading. However, the central nodes at the lower end of the model, and also at its mid-height, were allowed to move vertically, thus allowing for column shortening.

The numerical model has 48 concrete brick elements (C3D20), 96 steel shell elements (S8R) for the RHS steel tube, 16 steel shell elements (S8R) for the T-cleat flanges, 32 steel shell elements (S8R) for the T-cleat stems and 8 rigid brick elements (C3D20) for the end loading plates. In all, the model has 200 elements and 1081 nodes.