

**Zeitschrift:** IABSE reports = Rapports AIPC = IVBH Berichte  
**Band:** 999 (1997)  
  
**Artikel:** Evaluation of seismic resistivity of CFT steel pillar  
**Autor:** Murata, Kiyomitsu / Ikeda, Manabu / Yasuhara, Masato  
**DOI:** <https://doi.org/10.5169/seals-1111>

### **Nutzungsbedingungen**

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

### **Conditions d'utilisation**

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

### **Terms of use**

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

**Download PDF:** 05.09.2025

**ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>**

## **Evaluation of Seismic Resistivity of CFT Steel Pillar**

**Kiyomitsu MURATA**

Chief Engineer  
Railway Technology Research Institute  
Tokyo, Japan

**Masato YASUHARA**

Engineer  
Railway Technology Research Institute  
Tokyo, Japan

**Manabu IKEDA**

Engineer  
Railway Technology Research Institute  
Tokyo, Japan

**Masanori KINOSHITA**

Senior Researcher  
Nippon Steel Corporation  
Chiba, Japan

### **Summary**

Aiming at establishment of a new seismic design method in which ductility is taken well into account, a series of alternating bending tests under constant axial compressive force with Concrete Filled Tubular, called CFT, steel pillar models were carried out. The study based on experimental results enabled the quantitative evaluation of seismic resistivity of CFT pillars. The fruits obtained through this study will be reflected in Model Code for Railway Hybrid Structure Design to be made public by Japan Ministry of Transport in 1997.

### **1. Introduction**

Newmark's energy preservation rule is well known as a concept of the seismic design, where the ductility of pillars is taken into consideration. This idea is to check the bending yield point capacity to horizontal seismic load as corrected according to the ductility of pillars. In order to apply such a seismic design method to CFT pillars, it is necessary to establish the method of quantitatively evaluating the yield point load, yield point displacement and also relationship between the limit plastic displacement and the pillar components. Therefore, the study was done according to the following steps.

- Step1 Alternating bending test with CFT pillar models
- Step2 Analytical study on yield point load and yield point displacement
- Step3 Statistical study on quantitative evaluation of ductility

## 2. Alternating bending test on CFT pillar models


The alternating bending test under axial compressive force with 1/3 models of CFT pillars was executed. The experimental parameters are diameter-thickness ratio, axial compressive force, concrete strength, and steel pipe strength.

## 3. Analytical study on yield point load and yield point displacement


The yield point load and yield point displacement were calculated with a fiber element model dominated by elasto-plastic stress-strain relationship of steel and concrete materials. *Figure 1* shows the comparison between the experimental values and the calculated ones.

## 4. Statistical study on quantitative evaluation of ductility

The expression of quantitatively evaluated ductility was induced from the recurrence analysis based on experimental results as well as on analytical ones. *Figure 2* shows the comparison between the calculated ductility and experimental one.



*Fig 1* Yield Point Load & Displacement



*Fig 2* Ductility

## 5. Conclusions

The quantitative evaluation expression for seismic resistivity of CFT pillars was induced. As a result, a more rational and accurate evaluation of yield point load, yield point displacement, and ductility necessary for the seismic design of CFT pillars has been made possible.