Zeitschrift:	IABSE reports = Rapports AIPC = IVBH Berichte
Band:	77 (1998)
Artikel:	Dynamic in situ tests on a damaged historical building
Autor:	Zabel, Volkmar / Bucher, Christian
DOI:	https://doi.org/10.5169/seals-58178

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. <u>Mehr erfahren</u>

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. <u>En savoir plus</u>

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. <u>Find out more</u>

Download PDF: 08.07.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch



Dynamic in Situ Tests on a Damaged Historical Building

Volkmar ZABEL Research Assistent Bauhaus-University Weimar, Germany

Volkmar Zabel, born 1968, received his civil engineering degree from the University of Architecture and Building Science Weimar, Germany, in 1996. He is currently working at the Institute of Structural Mechanics at the Bauhaus-University Weimar on the field of structural dynamics.



Christian BUCHER Professor Bauhaus-University Weimar, Germany

Christian Bucher, born 1956, received his Ph.D. from the University of Innsbruck, Austria, in 1986. He is teaching courses in Engineering Mechanics, Structural Dynamics, Dynamic Stability and Stochastic Finite Elements. His research interests include stochastic dynamics, full-scale dynamic testing of structures and software development.



Summary

The numerical description of the structural behaviour of an existing, damaged structure is a challenging engineering task. The basis for the solution of this problem is the evaluation of the actual behaviour on site using advanced experimental and numerical techniques. In this study, the severely damaged bell tower of the church of Krölpa (Thuringia) was investigated. By utilizing an FEM-package several natural frequencies with the corresponding vibration modes, transfer functions and modal damping ratios were obtained from the measurement data. It became obvious that the dynamic behaviour of the structure depends not only on the frequency but also on the amplitude and direction of the exciting force. The presented methods appeared to be suitable tools for the identification of dynamic system properties even though difficulties in the numerical description of the nonlinear effects remained.

Keywords:

structural dynamics, system identification, structural damage, experimental testing, nonlinear dynamics

1. Investigations on site



Fig. 1 : The bell tower, view from south-west

The appearance of the medieval Krölpa church tower is significantly characterized by its inclination which was caused by an uneven settlement of the ground. Today the tower is about 2.2 degrees out of the vertical and shows deep vertical cracks in the masonry of its four walls. These damages gave the reason for an investigation of the dynamic structural behaviour of the tower in its current state. It was intended to identify dynamic system properties as well as to model the structure with its specifics numerically.

The *in situ* tests were carried out in May 1997. A servo-hydraulic vibration generator was posed in the former place of the belfry in order to produce a harmonic exciting force. The frequency of the force was increased incrementally from 0.3 Hz to 9.7 Hz. The experimental programme consisted of several test series with the exciting force acting in different directions and with different amplitudes. The response of the system was registered by accelerometers which were placed in the corners of the tower in three levels.



2. Identification of system properties

From the stored time histories of the measured accelerations and the exciting force, the complex transfer functions were calculated as the ratio of the Fourier transform of the reaction and that of the excitation. Problems which are connected with the Fast Fourier Transformation algorithm were avoided by using an alternative method for the computation of the Fourier transforms.







Fig. 3: First four identified mode shapes

The phase angles were directly determined from the complex transfer functions. The obtained curves allowed the identification of four resonances. Modal damping ratios for the resonance frequencies could be deduced from the phase angles at resonance.

A finite element model of the tower was created. By means of the method of dynamic condensation and the deflections obtained by integrating the accelerations twice four modes of vibration, which correspond to the resonances, were identified.

The results of the test series showed several nonlinearities in the dynamic behaviour of the bell tower. The resonance frequencies decreased with an increased amplitude of the exciting force. It could also be observed that the occurence of resonances depends on the direction of excitation.

3. Conclusion

about diagonals

Structural damages can lead to changes of the structural system and significantly alter the dynamic behaviour of a structure. The described techniques can be considered as a suitable method for the identification of dynamic system properties.

A number of nonlinear effects in the behaviour of the damged bell tower was observed. It can be concluded that the properties and the behaviour of the investigated structure strongly depend on the frequency, the magnitude and the direction of a load imposed on it. The numerical modelling of these phenomena remains the subject of further research.