

New system for aerodynamic stability of suspension bridge

Autor(en): **Yoshimura, Toshihiro**

Objektyp: **Article**

Zeitschrift: **IABSE reports = Rapports AIPC = IVBH Berichte**

Band (Jahr): **79 (1998)**

PDF erstellt am: **22.06.2024**

Persistenter Link: <https://doi.org/10.5169/seals-59929>

Nutzungsbedingungen

Die ETH-Bibliothek ist Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Inhalten der Zeitschriften. Die Rechte liegen in der Regel bei den Herausgebern.

Die auf der Plattform e-periodica veröffentlichten Dokumente stehen für nicht-kommerzielle Zwecke in Lehre und Forschung sowie für die private Nutzung frei zur Verfügung. Einzelne Dateien oder Ausdrucke aus diesem Angebot können zusammen mit diesen Nutzungsbedingungen und den korrekten Herkunftsbezeichnungen weitergegeben werden.


Das Veröffentlichen von Bildern in Print- und Online-Publikationen ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Die systematische Speicherung von Teilen des elektronischen Angebots auf anderen Servern bedarf ebenfalls des schriftlichen Einverständnisses der Rechteinhaber.

Haftungsausschluss

Alle Angaben erfolgen ohne Gewähr für Vollständigkeit oder Richtigkeit. Es wird keine Haftung übernommen für Schäden durch die Verwendung von Informationen aus diesem Online-Angebot oder durch das Fehlen von Informationen. Dies gilt auch für Inhalte Dritter, die über dieses Angebot zugänglich sind.

New System for Aerodynamic Stability of Suspension Bridge

Toshihiro YOSHIMURA
Civil Eng.
Chodai Co. Ltd
Tsukuba, Japan



Toshihiro Yoshimura has experience in design and construction of major bridges at Honshu-Shikoku in Japan. He is currently a resident engineer for construction management of Yongjon Grand Bridge in Korea.

Summary

Aerodynamic stability is one of major issues to be considered in designing long span bridge with more than 3,000 meter of cable span length.

In this paper an attempt is made to discuss the use of cable formers for the system with four main cables, each of which is located at certain distance from others cables. The effectiveness of the new system for 3 span suspension bridge as well as 5 spans suspension bridge was examined by means of dynamic analysis.

It was found that the new system shall improve the torsional rigidity of suspension bridge and also increase the frequency of the torsional vibration.

1. Concept of the New System

Strait-crossing bridges with more than 3,000 meter of span length are now being planned all over the world. Among them include Messina Crossing (Italy), Gibraltar Strait (Spain-Morocco) and Tugaru Strait (Japan). These longer span bridges, if implemented, will encounter the difficulty in maintaining the stability against drag forces.

The Key to solve this problem is to use main cables and let the torsional strength have an effect on the drag resistance, in order to improve the torsional rigidity of the suspension bridge. The feature of torsional vibration is explained by the forces which drag the right and left cables in the opposite direction. Therefore keeping the constant distance of cables was estimated to increase the frequency of torsional vibration (See Fig.1).



2. Result of the Vibration Analysis

In this paper cable formers were set up to keep the constant distance of cables and height of the cables. The initial finding is that cable formers were effective to increase the aerodynamic stability. After the vibration analysis, the effects of the new system are summarized as follows;

- 1) Installation of cable formers increased the frequency of torsional vibration(See Fig.2)
- 2) Difference of the height improved the efficiency
- 3) New system increased the torsional rigidity, up to the same level as that of the stiffening girder(See Fig.3)

Applying the Selberg's equation, it was found that the critical wind velocity for flutter can be increased more than 20% by using this system, without increasing additional weights of stiffening girder.




Fig.1 Illustration of the New System




Fig.2 Influence of span-length on torsional vibration




Fig.3 Magnification of torsional rigidity to stiffening girder