

Zeitschrift: IABSE reports = Rapports AIPC = IVBH Berichte
Band: 82 (1999)

Artikel: Stay cable technology: overview
Autor: Ito, Manabu
DOI: <https://doi.org/10.5169/seals-62102>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 10.12.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



Stay Cable Technology: Overview

Manabu ITO
Prof. Dr
Takushoku University
Hachioji, Japan

Manabu Ito, graduated in 1953 and given Dr. Eng. degree in 1959 from the University of Tokyo, had engaged in teaching and research of bridge engineering at his alma mater. After the retirement in 1991, he moved to Saitama and Takushoku universities. He has been involved in many large bridge projects in Japan, while he is a former vice-president of IABSE.

Abstract

1. Introduction

The stay cables are required to have superb mechanical properties (such as high tensile strength, high elastic modulus and satisfactory fatigue resistance), sectional compactness and excellent corrosion resistance, as well as easiness of handling and installation, and naturally not to be costly.

2. Types of Stay Cable

Helical wire ropes including locked coil ropes were widely used in the earlier steel cable-stayed bridges and have been long adopted on many European bridges. On the other hand, parallel wire or parallel strand cables have better mechanical properties than helical wire ropes, although inferior in easiness of handling. Among them, the parallel strand ropes consisting of the seven-wire strands have been prevalent in prestressed concrete (PC) cable-stayed bridges, and recently further in steel and steel/concrete hybrid bridges. The parallel wire cables covered by a high density polyethylene (HDPE) tube and provided with HiAm anchor sockets have been also popular in both PC and steel cable-stayed bridges. In Japan the shop-fabricated parallel wire strands (PPWS) extensively used on suspension bridges had been preferred for steel cable-stayed bridges until being taken the place by "New PWS".

The New PWS is an ultra-long lay cable strand being composed by 7mm wires. Twisting up to 4° enables the wire bundle to ease reeling and make the strand self-compacting under axial tension without spoiling the mechanical properties. The similar idea was applied to HiAm-SPWC in Europe. The New PWS is also featured by extruding HDPE cover directly onto the wire bundle so that no void will exist between the wires and the surrounding cover. Bar stay cables covered by a steel pipe and filled with cement grout are scarcely used on stay cables, in particular for large cable-stayed bridges.

3. Corrosion Protection

Today the multiple-barrier corrosion system is routine for the stay cables. They consist of at least two barriers: the internal barrier immediately adjacent to the main tension element and the exterior barrier or covering. The wires are mostly zinc-galvanized or coated by epoxy, but non-galvanized wires are used when hydrogen brittlement caused by reaction with grouted cement mortar is feared. The wires of helical wire ropes are galvanized. In addition, voids of spiral ropes are filled with a sealing compound such as metalcoat. On the other hand, recent practice for a locked coil rope stay is to fill the inner voids with polyurethane with zinc dust or linseed oil with red lead, and to coat the outer surface of the rope by polyurethane.



Covering the strand or cable as the exterior barrier is now common to other types of stay cables than helical wire strands. The covering by a metal tube made of steel, stainless steel or aluminum alloy has been prevalent in PC cable-stayed bridges. In case of the steel pipe, coating is required. Anyhow, the installation of metal pipes is to be done at the erection site, and their stiffness may cause some difficulty in handling when a cable is long.

Use of a fiber reinforced plastic or HDPE tube are more popular. The latter is either shop-fabricated or site-fabricated. In case of New PWS and seven-wire strands, the covering is completely shop fabricated by a directly extruded HDPE sheath after executing the internal barrier. Although the original color of the PE covering is black, cable coloring techniques are now available. Supplementary wrapping with colored Tedler tapes is an alternative.

The typical blocking compound filled between the main tension member and the outer sheathing is cement mortar. But the chemical reaction with zinc and the occurrence of cracks are feared. Use of polymer cement or cement grout plasticized with polyurethane may improve the situation. Synthetic resin material based on polybutadiene was once used on Japanese bridges. These alternatives are, however, more costly. Grease and wax are also the blocking compound for PWS and prestressing strands in combining use with other measures.

4. Preventive Measures against Wind-Induced Vibrations

The stay cables has become vulnerable to wind-induced vibrations since the introduction of multi-stay system with thin cables covered by polyethylene sheath having smooth surface. Particular care should be taken for vortex excitation, wake galloping and rain-wind-induced vibration. Preventive measures can be classified into mechanical and aerodynamic means. It must be borne in mind that the exciting mechanisms of different phenomena differ.

Occurrence of wake galloping depends on the spacing of neighboring cables. Small spacing not larger than two times or quite wide spacing more than six times the cable diameter can remarkably moderate the response. Otherwise the cable vibration can be suppressed by connecting the both cables by a few spacers or small mechanical dampers.

One of the common mechanical means being used for all the vibration types are the secondary thin cables connecting the stay cables and often terminating at the deck. But care must be taken on the rupture of the secondary cables and the fatigue failure of the connection fittings due to repeated loading. On the other hand, seemingly the most effective and prevalent measure is to install viscous dampers between the cable and the bridge deck. First recommendation is to place such damping materials as neoprene ring or high-damping rubber between cable and steel exit pipe at pylon and deck anchorage. Further additional damping can be provided by the hydraulic dampers or shear-viscous dampers near the anchorage at the deck. Aesthetic consideration is desirable at this time. However, it is not easy to make compromise between the requirement to lower the dampers and the efficacy of the damper. The classical Stockbridge type tuned-mass damper that once used on a few European bridges may spoil the appearance of the structure.

The aerodynamic means for the round cables are to modify the cable surface. Helical fins are used to suppress vortex excitation if the appearance is not spoiled. The measures developed for preventing rain-wind-induced vibration are the axial protuberances in the form of longitudinal ribs or grooves and pattern-indented surface with roughness applied disorderly in a convex or a concave pattern. Attention should be paid on the increase of drag coefficient in these cases.