Zeitschrift: IABSE reports = Rapports AIPC = IVBH Berichte

Band: 82 (1999)

Artikel: The design and construction of Lockmeadow Footbridge, Maidstone

Autor: Firth, lan P.T.

DOI: https://doi.org/10.5169/seals-62127

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Mehr erfahren

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. En savoir plus

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. Find out more

Download PDF: 10.12.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch



The Design and Construction of Lockmeadow Footbridge, Maidstone

Ian P.T. FIRTH
Partner,
Flint & Neill Partnership
London,
England.




Ian Firth graduated from the University of Bristol in 1979 and obtained a Master's degree in Structural Steel Design at Imperial College in 1982. He has been responsible for many bridge projects with Flint & Neill Partnership, including the Poole Harbour Bridge in England. He is also responsible for the design of two other footbridges soon to be constructed in Maidstone.

Abstract

The construction of this unusual twin span cable stayed footbridge is due to be completed in the Spring of 1999. The design is the winning entry in an invited design competition held by Maidstone Borough Council in early 1997, and is an elegant response to what has been described as one of the most sensitive sites for a bridge anywhere in England.

The bridge crosses the River Medway at a bend adjacent to the Grade 1 listed Archbishop's Palace at a location where historical and archeaological issues predominate. Slenderness and lightness became the governing design criteria, and the bridge solution adopts a unique and very shallow aluminium deck system in a direct response to these factors.




The bridge spans both the river and the adjacent floodplain on one side, and is 90 metres long overall. The sculpted form of the central concrete support cuts the floodwaters like the bow of a boat and carries a stair on its back. This "cutwater" pier stands on one bank of the river and supports twin skeletal steel masts inclined outwards in a wide V shape from which galvanised steel locked coil ropes support the lightweight deck.

The aluminium deck is formed from a series of longitudinal 300 mm deep extrusions assembled together and prestressed transversely with stainless steel bars. The outermost extrusion accommodates a novel carbon fibre and stainless steel parapet, and the top



flanges of the extrusions are ribbed and cross-cut to form an attractive slip-resistant aluminium surface. In this way there is no need for secondary structure or any added finishes, as the aluminium extrusions are the primary structure and the finishes all in one, and this leads to greater economy. There is no need for added corrosion protection, except to the steel masts and stays, and the design has been conceived and developed with minimum maintenance in mind.



The modular system of assembly and the light weight of the structural components has led to greater simplicity in the construction method, and this was part of the original concept. The bridge is being built with close co-operation between the parties, and the client has taken a share of the risk in certain aspects of the construction in order to achieve greater economies.

This paper will address the environmental issues and the visual design as well as the technical design and construction aspects, and will examine ways in which this innovative aluminium deck system can be adapted for footbridges and other applications elsewhere.