/ing
•

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. <u>Mehr erfahren</u>

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. <u>En savoir plus</u>

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. <u>Find out more</u>

Download PDF: 06.08.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch



Nonlinear Dynamic Analysis of Cable-Stayed Bridges Excited by Moving Vehicles

Raid KAROUMI Researcher, Dr. Techn. Dept. of Structural Eng. Royal Inst. of Technology Stockholm, Sweden

www.struct.kth.se raid.karoumi@struct.kth.se



Raid Karoumi, born 1964, received his M.Sc. degree in Civil Engineering in 1990 and his Dr. Techn. degree in 1999 from the Royal Institute of Technology in Stockholm. Between 1990 and 1993 he worked as a consultant and was involved in a variety of special projects.

Abstract

The dynamic response of bridges subjected to moving vehicles is complicated. This is because the dynamic effects induced by moving vehicles on the bridge are greatly influenced by the interaction between the vehicles and the bridge structure. Although several long span cablestayed bridges are being build or proposed for future bridges, little is known about their dynamic behavior under the action of moving vehicles. As cable-stayed bridges are getting longer, lighter, and more slender, accurate procedures need to be developed that can lead to a thorough understanding and a realistic prediction of the structural response due to traffic loading. It is well known that large deflections and vibrations caused by dynamic tire forces of heavy vehicles can lead to bridge deterioration and eventually increasing maintenance costs and decreasing service life of the bridge structure.

In this paper, a method for modeling and analysis of the nonlinear dynamic response of cablestayed bridges excited by moving vehicles is presented. The bridge structure is discretized utilizing the nonlinear finite element method and the dynamic response is evaluated using a combined Newton-Newmark algorithm. A beam element, which includes geometrically nonlinear effects and is derived using a consistent mass formulation, is adopted for modeling the girder and the pylons. Whereas, a two-node catenary cable element derived using exact analytical expressions for the elastic catenary, is adopted for modeling the cables. All sources of geometric nonlinearity and other important factors that significantly influence the dynamic response, such as bridge damping and bridge-vehicle interaction, are considered.

The vehicle model used in this study is a so-called suspension model that includes both primary and secondary vehicle suspension systems. As the vehicle equation of motion is coupled to the bridge equation of motion through the interaction force existing at the contact point of the two systems, an iterative procedure is adopted to solve these two sets of equations.



Figure 1: Cross section of bridge girder with a tuned mass damper, TMD



As energy dissipation in cable-stayed bridges is very low and may often not be enough on its own to suppress vibrations, the efficiency of a so-called tuned mass damper on controlling traffic-induced vibrations, is investigated. A tuned mass damper is a vibration absorber tuned to a particular mode of the bridge and consists of a mass, a viscous damper and a linear spring, see Figure 1.

A simple cable-stayed bridge model is analyzed to highlight the dynamic effects and to show the influence of vehicle speed, bridge damping, and a tuned mass damper on the bridge dynamic response.