

Zeitschrift: IABSE reports = Rapports AIPC = IVBH Berichte
Band: 82 (1999)

Artikel: Deformability of long-span cable-stayed bridges for railways
Autor: Bruno, Domenico / Grimaldi, Antonio / Leonardi, Angelo
DOI: <https://doi.org/10.5169/seals-62153>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 07.02.2026

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



Deformability of Long-Span Cable-Stayed Bridges for Railways

Domenico BRUNO
University of Calabria
Cosenza, Italy

Antonio GRIMALDI
University of Rome
Tor Vergata, Rome, Italy

Angelo LEONARDI
University of Rome
Tor Vergata, Rome, Italy

Abstract

Cable-stayed bridges have been of great interest in recent years, particularly with respect to the fan-shaped scheme as a valid and alternative solution to suspension bridges for long spans.

Troitsky (1) and Gimsing (2) have reviewed the problems and advantages of cable-stayed bridge solutions and reported on the latest and most interesting projects.

For long-span bridges one of the most important problems is related to the deformability under live loads. In the case of bridges carrying both road and railway traffic, and for spans greater than 1000 m, this aspect can seriously influence the design and the feasibility of the structure. In this work an analysis of the static and dynamic behaviour of the bridge is developed, modeling the train passage as a dynamical action or an equivalent static load.

Como *et al.* (3) analyzed the static behaviour of long span stayed-cable bridges showing the prevailing truss behaviour of the bridge. Bruno and Grimaldi (4) investigated the nonlinear static behaviour of cable-stayed bridges using both a continuous and a discrete model of the bridge, and showed the strong influence of nonlinearities for long spans. Moreover, the dynamic behaviour of cable-stayed bridges has been investigated by Bruno (5) analyzed the effects of moving loads, and by Bruno, Maceri and Leonardi (6) who analyzed aerodynamic instability problems.

In the above studies fan-shaped cable-stayed bridges were studied using both a continuous and a discrete model of the bridge, and the dominant truss behaviour of the bridge was found. In particular, the influence of the dynamic properties and geometric nonlinearities of towers are included in the analysis.

In this paper the continuous model proposed in the previous works is employed to develop static and dynamic analyses. In addition a discrete model is also applied to give some useful comparisons between analytical and numerical results.

The aim of the paper is to give same results and conclusions related the main geometric and mechanical parameters able to influence or control the bridge deformability.

In particular, the geometric aspect ratio L/H between the main span length and the tower height, the loads ratio p/g between live and dead loads, the relative flexural stiffness between girder and stays, are taken into account.

Obtained results show the strong influence of the rail load on the midspan deflection and on the girder slopes. As well known these last quantities in many cases represent the main parameter which have to be considered in deformability control.