

Zeitschrift: IABSE reports = Rapports AIPC = IVBH Berichte
Band: 83 (1999)

Artikel: Anchorage of 90-degree hooked beam bars in exterior RC joints
Autor: Joh, Osamu / Goto, Yasuaki
DOI: <https://doi.org/10.5169/seals-62902>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 05.02.2026

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



Anchorage of 90-Degree Hooked Beam Bars in Exterior RC Joints

Osamu JOH

Professor

Hokkaido University

Sapporo, Japan

Yasuaki GOTO

Associate Professor

Hokkaido University

Sapporo, Japan

Osamu Joh, born 1943, received his Dr.Eng. from Hokkaido Univ. 1971. Research field is seismic design of RC structures and their rehabilitation.

Yasuaki Goto, born 1958 received his D.Eng. from Hokkaido Univ. 1996. Research interest is RC beam-column joints by experiment & computing.

Summary

This study experimentally investigated anchorage performances for raking-out failure mode of 90-degree hooked beam bars in exterior beam-column joints to be used in a middle story, using forty column-shaped specimens with various arrangements of L-shaped beam bar anchorage. Based on the test results, a formula for accurate estimation of anchorage strength was proposed.

Keywords: anchorage; 90-degree hook; beam-column joint; ultimate strength; development length; concrete cover thickness; axial stress; lateral reinforcement.

1. Introduction

In the previous paper, we divided the anchorage failure of 90-degree hooked bars in exterior beam-column joints in a middle story into three modes: side split failure, local compression failure and raking-out failure. Most of the current structural design codes require that hooked bars be designed according to certain specifications, such as minimum requirements of concrete cover thickness, bar bend radius and location of the bend in a joint (in order to avoid the three anchorage failure modes, respectively) rather than according to theoretical calculations of strength. In the same paper[ACI, SP-157, pp.97-116, 1995], we also proposed a formula for estimating anchorage strength of 90-degree hooked bars with raking-out failure mode. In the present paper, we have proposed a modified formula that can estimate anchorage strength more accurately and can be applied to various designs of hooked bars anchored in a joint.

2. Experiment

Specimens, about half normal size, had 90-degree hooked beam bars anchored into an exterior beam-column joint situated at the midpoint of the column height. Two series of specimens were tested: an inward and an outward hook series, in which the tails of the beam bars were directed to the joint side and the column side, respectively. We tested eleven variables, including horizontal development length (L_{dh}), moment arm of beam (j_b), thickness of concrete cover, lateral reinforcement ratio, axial stress (σ_0), as shown in the table. A schematic of the dimensions and bar arrangement of the specimens is shown in Fig.1. One tensile load, P_1 , was applied horizontally to the beam bars, where reactions R_1 and R_2 were supported, and another tensile load, P_2 , was applied at the top of the column to generate the same shear force in both columns.

3. Estimation of Anchorage Strength

Fig. 2 is a schema showing a typical crack pattern in the inward hook series at the final loading stage. The main cracks related to anchorage strength were in a chain of ⑦-③-④-⑥.

The failure plane slid heavily along cracks ④-⑥ so that concrete slippage on this plane worked as a part of horizontal resistance, and the main cracks opened widely at the ultimate stage so that the hoops crossing the failure plane worked as the remainder of the horizontal resistance. The following modified formula was proposed for estimating anchorage strength with raking-out failure:

$$calTu = kn (calTc + calTw), \quad (1)$$

where $calTc$ (horizontal concrete resistance) = $H / jb \cdot calTao$ for inward hooks, $calTc = H / (H - jb) \cdot calTao$ for outward hooks, and H is story height. The value of $calTao$ is analytical horizontal resistance of the failure plane and is defined by the equation $calTao = kc \cdot bce \cdot Lc \cdot \sigma_e$, where kc is a coefficient that takes into account tail direction, bce (effective column width) = $S + 0.53 bc$, bc is the total concrete side cover thickness for beam bars, Lc is the length of horizontal straight bar length minus concrete cover thickness, and σ_e (concrete sliding strength) = $\sqrt{\sigma_B}$. In Equ.(1), $calTw$ is the horizontal resistance of hoops and is defined by the equation $calTw = kw \cdot kb \cdot aw \cdot \sigma_{wy}$, where kw (effective hoop stress factor) is 0.8 for inward hooks and 0.9 for outward hooks; kb (effective concrete cover thickness factor) is 1 at $C_0 \leq 0.8Ldh$, $3 - 2.5C_0/Ldh$ at $0.8 < C_0/Ldh < 1.2$, and 0 at $1.2 \leq C_0$; aw is the total sectional area of hoops within the effective zone; and σ_{wy} is the yield stress of the hoops.

The axial stress modification factor (kn) has to be used to estimate the fact that the column axial stress increased the anchorage strength, but there is an upper limit to the strength-enhancing effect of axial stress. Therefore, kn is defined as follows: in the case of inward hooks, $kn = 1 + 0.205 \sigma_{os}$, where σ_{os} is the minimum between σ_o and $0.08 \sigma_B$; and in the case of outward hooks, $kn = 1 + 0.153 \sigma_{os}$, where σ_{os} is the minimum between σ_o and $0.16 \sigma_B$. The average of the ratio of observed strength $expTu$ to $calTu$ for 40 specimens was 1.01, and the standard deviation was 0.091. As can be seen from the relation between $expTu$ and $calTu$ plotted in Fig. 3, the new estimations appear to be highly accurate.

4. Conclusions

The following conclusions were drawn on the basis of the results.

- 1) The anchorage strength of outward hooks is less than that of inward hooks.
- 2) Our previous method for estimating horizontal concrete resistance and hoop resistance in anchorage strength was extended to outward hooks as well as inward hooks.
- 3) A new equation for estimating the anchorage strength of 90-degree hooked bars in exterior beam-column joints was derived from our previous equation. Our experimental results confirmed that estimations using this new equation have a high level of accuracy.