Zeitschrift:	IABSE reports = Rapports AIPC = IVBH Berichte
Band:	83 (1999)
Artikel:	Virtual prototyping in the construction industry
Autor:	Feijo, Bruno / Scheer, Sérgio
DOI:	https://doi.org/10.5169/seals-62946

#### Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Mehr erfahren

#### **Conditions d'utilisation**

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. <u>En savoir plus</u>

#### Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. <u>Find out more</u>

### Download PDF: 22.07.2025

ETH-Bibliothek Zürich, E-Periodica, https://www.e-periodica.ch



# Virtual Prototyping in the Construction Industry

Bruno FELJO Professor PUC-Rio & Uerj Rio, RJ, Brasil

Bruno Feijó, born 1951, received his Aeronautics engineering degree from ITA (1975) and PhD degree from Imperial College (1988). He works in the areas of CAD, computer graphics and Information Technology. Sérgio SCHEER Professor CESEC, UFPR Curitiba, PR, Brasil

Sérgio Scheer, born 1957, received his civil engineering degree from UFPR (1980) and PhD degree from PUC-Rio (1993). He works in the area of CAD systems for civil engineering and mechanics.

# Summary

The aim of virtual prototyping is to build a full virtual artifact in such a way that design and manufacturing problems are anticipated and discussed within a cooperative work environment This paper presents virtual prototyping as the most adequate technology for the construction industry in the next decade.

Keywords: CAD, virtual prototyping, integrated design

# 1. Introduction

Virtual prototypes (*i.e.* complete 3D models) have been using in the mechanical industry for many years. Perhaps the most recent and impressive example is the Boeing 777 almost entirely represented by a 3D CAD model. Nevertheless, a virtual prototype is much more than a complete 3D model of the artifact. Virtual prototyping requires 3D models that are able of integrating several sectors of a company and demands high-end technology for virtual reality environments, virtual humans and distributed environments. Moreover, a virtual prototype works as a spatial database that can be queried by anyone in the enterprise through the computer network.

# 2. Virtual Prototyping

The objects of the virtual artifact have several types of attributes, such as geometric attributes, design intent attributes, manufacturing attributes, cost attributes, pointers to part numbers and documentation references. It is clear from Fig. 1 that the virtual prototype is distributed over several networks with different platforms, operating systems and design teams.

Virtual prototyping should consider geometry buses and object-distributed computing. A Geometry Bus allows designers to use different CAD programs in the network. ACIS [1] and CORBA have been proposed as a geometry bus and distributed object architecture for integrated CAD systems respectively [2].

Essentially, the Product Structure shown in Fig.1 is a collection of pointers to 3D models and 2D drawings. The data exchange format STEP can be used to present components as a text description or a 3D object. STEP files can be browsed in the intranet.

Virtual prototyping requires VR technology. Virtual Reality systems provide <u>immersive</u> <u>environments</u> where the user experiences a sense of immersion. This is the case of using a headmounted display (HMD) or a BOOM (Binocular Omni-Orientation Monitor). Fig. 1 illustrates an



Fig. 1 Example of a distributed virtual prototype

immersive environment where a designer incorporates an avatar (*i.e.* a virtual copy of the user) using the system Jack for virtual humans. Designers can use virtual humans in a number of ways, such as: accident simulation, workplace assessment, human strength analysis, and check of maintenance procedures in areas of difficult access.

A more rigorous definition of virtual environments and a practical guide for engineers who want to explore the possibilities of the VR technology can be found elsewhere [3].

### 3. Conclusions

The search for quality in structural engineering in the

coming decade should consider its manifold activities, which are integrated amongst themselves, such as design, planning, construction, operation and maintenance. This integration should be considered during the design phase and the practice of virtual prototyping seems to be the most adequate approach to this question. Virtual prototypes also



Fig. 2 Planning – 4<sup>th</sup> month

### 4. References

allow visibility to the public in real time through the internet – an important concern when environmental, social, human and aesthetic factors are critical.

Several previous experiences by the authors support the recommendations presented in this paper. For instance, the authors had a stimulating experience with a large Brazilian construction company (CBPO), where they developed a computer system integrating 3D models with planning networks [4]. This system revealed more adequate construction methods for a factory of metallic cans and lead to a schedule two months shorter than the one obtained by the conventional planning methods, as shown in Fig. 2.

- [1] Spatial Technology, ACIS 3D Toolkit Version 2.1, Spatial Technology Inc., USA, 1996.
- [2] Regli, W. C., "Intranet-enabled Computer-Aided Design", *IEEE Internet Computing*, Vol. 1, No. 1, Jan-Feb 1997, pp. 39-50. [Also in http://www.computer.org/ internet/ backissu.htm].
- [3] Feijo, B., "Virtual Environments for CAD Systems", In C. Tasso, E.R. Arantes e Oliveira (eds.), *Development of Knowledge-based Systems for Engineering*, Springer-Verlag, Udine, Italy, 1998, pp. 183-200.
- [4] Feijo, B., P.C.R. Gomes, J. Bento and S. Scheer, "CAD for process innovation in the construction industry", *Structural Engineering and Mechanics*, Techno-Press, Taejon, Korea, Vol. 4, No. 6, 1996, pp. 717-729.