

Zeitschrift: IABSE reports = Rapports AIPC = IVBH Berichte
Band: 83 (1999)

Artikel: High performance concrete in the Argentinean West Central Area
Autor: Morandi, Javier O. / Rio, Olga / Uliarte, Ricardo José
DOI: <https://doi.org/10.5169/seals-62834>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 01.04.2026

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



High Performance Concrete in the Argentinean West Central Area

Javier O. MORANDI

Professor
Mat. and Soils Inst. – UNSJ
San Juan, Argentina

Javier Morandi, received his Civil Eng. Degree from the Univ. of San Juan. He obtained a Master in Construction in Spain. He has been working as professor in the UNSJ.

Olga RIO

Doctor in Civil Engineering
Eduardo Torroja Institute
Madrid, Spain

Olga Río, received her Civ. Eng. Degree from the Univ. of Tucumán; and her Doctorate degree at Univ. of Madrid. She has been working at the E. Torroja Inst. for the past 16 years.

Ricardo José ULIARTE

Professor
Mat. and Soils Inst. – UNSJ
San Juan, Argentina

Ricardo Uliarte, received his Civil Eng. Degree from the Univ. of San Juan. He obtained a Master in Structures in Chile. He has been working as lecturer in the UNSJ.

Keywords: HPC, additives, natural pozzolan, pozzolanic activity, mechanical properties.

Abstract

Active mineral additions, as components of concrete, make possible the enhancement of the mechanical resistance of the concrete. Besides, it allows preparing concrete with better durability properties, i.e. resistance against aggressive agents and lower development of hydration heat. Anyway, it is possible to get significant energy savings and design purpose made mixtures for specific structures located in special areas. This preparation of mixtures is what we call in this work HPC.

A lot of research works exist in relation to the use of active mineral additives (micro-silex, fly ashes, metha-kaolin, etc.) in the elaboration of HPC. Physic-chemistry properties of these additions are variable and the action mechanism is controlled by the pozzolan reaction. The mechanical properties of the HPC, also depend on the characteristic of the granular materials used. There are considerable differences on the mechanical behaviour of HPC, inclusive with the same resistance, depending on these variables and on where they are been manufactured^[1]. The characterisation of natural pozzolan of volcanic origin and diatomaceous ground extracted from local quarries, of the area of the Andes mountain range (San Juan and Mendoza provinces) in the region of "Cuyo", (the region of Cuyo is located in the Argentinian West Central area) with the purpose of being employed, as active mineral additives, is shown in this work. Preliminary geologic surveys, specimen collection and tests for physical chemical characterisation were also carried out.

The most interesting samples were selected to investigate the effect of fineness and granulometry on the pozzolanic activity. In addition, some concrete samples were made to evaluate traction and compression mechanical properties and their evolution in time. All the results of these samples are also presented. The work presented in this paper is part of a greater research project which aim is the evaluation of the technical and economical possibilities for using this HPC, made with local materials, in building structures of the Argentinian West Central area. This area is, on the other hand, the zone of maximum seismic risk in this country.



Nevertheless, it is necessary to investigate further in the optimisation and study of structural elements under different load patterns, in order to use this HPC in the Cuyo region. As we mention before this is a high seismic region. The following conclusions of the first results can be pointed out:

- The pozzolanic activity of the samples studied has been tested and proved.
- The addition of active raw materials from the geographic area can be considered to be apt to elaborate concrete of especial properties. For instance, durability, i.e. sulphate attack resistance, and to control the hydration heat dissipation.
- Despite of having a lower efficiency than concrete prepared with microsilex, still it is possible to use the Pozzolan to make HPC.
- The cost of the quarry is around \$2 per ton. From the economic point of view is very interesting and can be considered to be apt.
- The fresh concrete has a slightly higher viscosity compared with the ones without pozzolan, but nevertheless is apt to be placed through difficult access places.
- Hardened shows increasing resistance up to one year, with a higher increase in the beginning due to the type of cement used.

Aknowlegments

The authors want to thanks, the other people of the Department of Structures and Soils of the University of San Juan, involve in the project, for their collaboration. Thanks also to Dr. Javier Turrillas and Soledad Alvarez for their technical and linguistic advice.

References

- [1] L. Coppola, "Design of Reiforced High Strength Concrete Structures", Mario Collepari Symposium on Advances in Concrete Science and Technology. P. K. Metha Ed. 1997.
- [2] Hanna, E; Luke, K; Perraton, D and Aitcin, P. C.; "Rheological Behaviour of Portland Cement Pastes in the Presence of a Superplasticizer", ACI SP 119. 1989.
- [3] Metha, P. K.; Aitcin, P. C.; "Microstructural Basis of Selection of Materials and Mix Proportions for High Strength Concrete". Second International Symposium on "Utilisation of HSC". May 1990. Berkeley. California.
- [4] Uliarte, R. J., Morandi J., "Utilización de hormigones especiales y dispositivos de disipación de energía en estructuras ubicadas en zona de alto riesgo sísmico". Primer Congreso Internacional de Tecnología del Hormigón. Buenos Aires - Argentina, Junio de 1998.