

Zeitschrift: L'Enseignement Mathématique
Herausgeber: Commission Internationale de l'Enseignement Mathématique
Band: 27 (1981)
Heft: 1-2: L'ENSEIGNEMENT MATHÉMATIQUE

Artikel: TOWARDS A COMPLEXITY THEORY OF SYNCHRONOUS PARALLEL COMPUTATION
Autor: Cook, Stephen A.
Kapitel: 5. Hardware Modification Machines
DOI: <https://doi.org/10.5169/seals-51742>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 19.08.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>

Proof sketch: It suffices to show that SATISFIABILITY is in the second class given it is in the first class. Reasoning as above, the Turing machine M can check whether a candidate aggregate β'_n correctly tells whether a propositional formula F is satisfiable by making β'_n produce a satisfying assignment bit by bit, by plugging in partial truth assignments to F and asking β'_n about the result. The trouble is M cannot remember the partial assignments in small space. However, the problem of whether “the i -th bit is 1 in the lexicographically first assignment which β'_n says satisfies F” is in P. Thus by theorem 4.2 this bit can be determined in space $O(\log n \cdot \log \log n)$, and M can determine whether this assignment satisfies F in small space.

5. HARDWARE MODIFICATION MACHINES

As mentioned in the introduction, there is a need to define a parallel model which is more powerful than an aggregate, in that it can modify its circuits, but less powerful than existing parallel RAM models, in that each unit of hardware can only perform a bounded amount of work in one step. We shall call the new machine a *hardware modification machine* (HMM), since it is intended to be the parallel analog of the storage modification machine. An HMM consists of a finite collection of finite state machines connected together as in a conglomerate. At each step, each machine may, in addition to assuming a new state and transmitting output signals, modify its input connections. Specifically, it may detach any of its inputs and re-attach it to a new machine which it brings into the HMM, or it may re-attach it to an output of any machine which can be reached by a path of length at most two traced backwards from the input.

One advantage of an HMM over circuits, aggregates, and conglomerates is that there is no question of uniformity. The machine is uniform because it constructs itself.

An HMM can execute an algorithm like the one described in [FW] to simulate a deterministic S space bounded machine in time $O(S)$, and HMM time S can be simulated in deterministic space $O(S^2)$. Thus the inclusions (1.2) apply.

The theory of HMM's is developed in [D1].