

Zeitschrift: L'Enseignement Mathématique
Herausgeber: Commission Internationale de l'Enseignement Mathématique
Band: 27 (1981)
Heft: 1-2: L'ENSEIGNEMENT MATHÉMATIQUE

Artikel: ALTERNATION AND THE ACKERMANN CASE OF THE DECISION PROBLEM
Autor: Fürer, Martin
Kurzfassung
DOI: <https://doi.org/10.5169/seals-51744>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 19.08.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>

ALTERNATION AND THE ACKERMANN CASE OF THE DECISION PROBLEM¹

by Martin FÜRER²

ABSTRACT. The Ackermann prefix class is the set of all formulas of predicate calculus (first order logic without function symbols) with quantifier prefix $\exists \dots \exists \forall \exists \dots \exists$. This is one of the few prefix classes for which satisfiability is decidable. Lower bounds for the computational complexity of this decision problem and the $\forall \exists$ sub-problem are presented. The tool to get the main result is the alternating Turing machine. An introduction to alternating Turing machines is given, because they are probably the most remarkable new subject of automata theory, and are well known only to computer scientists.

1. INTRODUCTION AND HISTORICAL BACKGROUND

From the beginning of this century to the thirties, the problem of deciding universal validity of first order formulas, moved slowly to the center of interest of mathematical logic. Especially Hilbert considered it to be a fundamental problem. As it seemed too hard to solve the decision problem (or *Entscheidungsproblem*) in general, the main approach was to restrict the class of formulas (for which a decision algorithm should work) by very simple syntactic criteria. An earlier example of this kind of restriction was the decidability result of Löwenheim [29] for the monadic (only unary predicate symbols) predicate calculus. Later the main such criterion was the form of the quantifier sequence for formulas in prenex form (see [14], [28], [43] for other syntactically defined classes). There is a duality between universal validity and satisfiability. A closed formula (i.e. a formula of predicate calculus without free variables) is universally valid, iff its negation is not satisfiable. Around 1930 the decidability of the satisfiability

¹⁾ Presented at the *Symposium über Logik und Algorithmik* in honour of Ernst SPECKER, Zürich, February 1980.

²⁾ This work was supported by the British Science Research Council and by the Swiss National Fonds.