

Zeitschrift: The Swiss observer : the journal of the Federation of Swiss Societies in the UK

Herausgeber: Federation of Swiss Societies in the United Kingdom

Band: - (1981)

Heft: 1777

Artikel: Pioneers in the propeller era [To be continued next month]

Autor: Muser, Alfred

DOI: <https://doi.org/10.5169/seals-687720>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 15.02.2026

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>



Pioneers in the propeller era

By Swissair captain
Alfred Muser

the Federal Air Office placed a ban on the use of single-engined aircraft for such operations.

Luckily Swissair had already tackled the task of modernising its flight equipment in the previous year, during which five twin-engined Douglas DC-2s had entered service. The standard crew complement on aircraft of this type consisted of one pilot, one radio operator and one stewardess.

For the first time, too, the cockpit was equipped with an automatic pilot (known as the "robot"), which was able to hold the aircraft on a specific course.

Unlike the equivalent devices of today, these autopilots could also be used for take-off in poor visibility, provided (according to the instructions) that the pilot exerted "full negative pressure for six minutes" to make sure the pneumatic gyro was operating at the necessary RPM rate.

Soon flying on instruments became a routine affair, though the procedure was somewhat complicated and lengthy. The radio operator received radio bearings from the ground station which he then wrote down and held in front of the pilot so that the latter could undertake any course correction that might be necessary.

If the message "ZZ" was received it meant that the

aircraft had flown over the listening post on the airfield boundary and could thus begin its descent.

On one particularly foggy day a pilot reported he had only been sure of reaching the airfield after glimpsing the silhouette of a stationary aircraft on the ground.

As a result, the authorities at Dübendorf airfield toyed with (but eventually rejected) the idea of leaving an aircraft on the ground at all times during severe weather conditions of this sort.

While the navigational aids and cockpit instruments of these early days were greatly inferior in terms of precision to those in use today, the slow approach airspeed of the aircraft, together with the large and open character of airfields at that time, poor visibility landings were made which were not improved upon in scheduled services until the second half of the seventies.

In the ZZ approach procedure the pilot had to rely completely on the data transmitted to the plane from ground stations. All this changed with the introduction of the Standard Beam Approach (SBA).

In this procedure the pilot was able to make his descent along a specific approach route in the direction of the airfield with the help of acoustic signals and instrument readings generated

by a system of localizer beams.

The cockpit was also equipped with a glide slope indicator, but this was rather a hit-and-miss affair so that pilots usually made their descent in distinct stages after flying over certain specific signals.

By the end of 1935 winter operations had become a reality, although the DC-2 aircraft were not equipped with proper de-icing systems. These were first in the form of pneumatic de-icing "boots" for the leading edges of aerofoil surfaces and a de-icing solution for the propellers on the DC-3, which made its debut at Swissair in 1937.

With the advent of this aircraft the early pioneering days were destined to pass into history. It even became possible to operate a scheduled air transport services on a more secure profit-making basis for the first time.

The six-year break in commercial air transport caused by the Second World War was followed by a period of intense growth and development, both in terms of aircraft technology and traffic volume.

Swissair's pilots, traditionally rather conservatively inclined at this time, attempted to prevent the introduction of radio telephony, which threatened to deprive radio operators of their jobs.

Though the delay achieved was minimal, for several years the DC-3 was flown by one pilot only in addition to a radio operator in charge of the radio telephonic devices on board. The two-pilot cockpit for the DC-3 was not introduced until 1954.

To be continued
next month

SWISSAIR came into existence at a time when "blind flying" – that is, flying on instruments alone without visual reference to the terrain below – was just beginning to make headway in Europe.

The 'old guard' pilots inherited from Balair and Ad Astra spent a large part of the winter months, during which air transport went into hibernation, in somewhat reluctantly getting the feel of flying "blind", using what was known as a "needle and ball" (gyrostabilized turn and bank indicator), in an effort to lessen the dependence of scheduled flight operations on weather conditions.

Then Swissair ordered two US Lockheed-Orion speed-planes. Nothing could have been calculated to make the infant airline better known or more popular.

Reports of the high cruising speeds which these aircraft were capable of had reached European shores, but had been received with little more than incredulity, especially by aviation experts.

When they proved to be true on runs between Zurich and Munich and Berlin, there were no bounds to the general astonishment, nor to the publicity aroused.

For the pilots, though, the Orion was something of a step backwards. They flew alone in a half-open cockpit, operating a single-engined airplane without a radio operator or flight engineer and entirely dependent on visual ground contact. Yet, nonetheless, exceptional standards of regularity were achieved.

The next US plane to be delivered, the Clark CA-43, was also a single-engined craft, but because it was equipped with radio (plus radio operator) and an artificial horizon, it could also be operated on night and instrument flights.

On May 5, 1936, however,

A glide slope indicator was rather a hit-and-miss affair