

Zeitschrift: Swiss express : the Swiss Railways Society journal
Herausgeber: Swiss Railways Society
Band: 3 (1991-1993)
Heft: 5

Artikel: Swiss signals. Part IX, Signals on rolling stock
Autor: Jesson, John
DOI: <https://doi.org/10.5169/seals-855192>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)

Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 16.09.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>


Signals on Rolling Stock

by John Jesson

Continued from page 21, December 1991 Swiss Express

Marking of the working locomotive in a train


Loco travelling forwards:



At the head of the train, three white lights in a triangle.

(On a loco which is not at the head of a train, the lights at the front of the loco are unlit.)

Loco setting back:




One white light at bottom right. (Back-up light.)

(If more than one loco is coupled in multiple, only the last loco displays the white light.)


A push-pull train is treated the same as a locomotive. On a locomotive providing power for a push-pull formation, the lights at the end coupled to the coaches are unlit.

Marking of the end of a train


The last vehicle carries at its rear end an end-of-train signal:



By day a red/white striped lantern with a red glass.




By night a red light (normally flashing).




On trains which run only in daylight hours, and

not over routes with long tunnels, instead of a lantern, a red/white striped plate may be carried.




On vehicles with built-in lights, the end of the train is marked by two red lights at the same height, or with one red light to the right.

A locomotive travelling alone displays, at bottom right:




One red light.



In certain cases, during the day, a red/white striped plate over the lamp with red light.

Warning signal

The train displays:



Three lights in a triangle.

Marking of propelled train.

At the leading end of the propelled train, no signal is displayed by day. At night, and in tunnels, a white light from the lantern of the person accompanying the movement is displayed at the leading end.

The last coupled vehicle displays the normal tail light.

Marking of unattached assisting locomotive

An unattached assisting locomotive displays, whilst assisting on the running line, and also when returning to the station in the rear after completing the assisting move:


Forwards - three white lights in a triangle.

Backwards - one white light at the lower right.

Marking of works trains and transport

Works trains and transport display:


a) on a powered vehicle



White

Forwards:

Two white lights at the same height



White

Backwards:

One white light (back-up light)

On powered vehicles that are not at the head of the train, the lights in the forward direction are extinguished.

The warning signal is as previously described.

b) on a wagon

Forwards:

By day, the person accompanying the movement stands on the left side of the leading vehicle. No lights are displayed.

At night, the person accompanying the movement stands on the left side of the leading vehicle, displaying a white hand signal. Also, the vehicle displays a white light on the right.

Backwards:

By day, no indication.

By night, one white light on the right.

Exceptions:

Works trains and transports without a planned stop between sections, or travelling between several stations, display the normal tail light on the last vehicle.

Transports comprising small motorised vehicles and their trailers (wheeled ladders, lorries, etc.) carry the signals only on the motorised vehicle if it is not feasible for them to be mounted on the trailer.

Working rail-grinding trains, which pass to and fro over a section of track, display two white lights at the same height on both ends of the train.

The same display can be carried, when appropriate and when permitted by the signalman, by a test train.

Small motorised vehicles which are unable to display the usual lights:

By day - no signal at front or rear.

By night - one or two white lights at the same height at the front; one red light at the rear.

Rail/Road vehicles which are unable to display the usual lights:

At the front of the vehicle:

Two white lights at all times, irrespective of the direction of travel.

At the rear of the vehicle:

When travelling forward - two red lights.

When travelling backwards - two red and one or two white lights.


Marking of a shunting locomotive

A train locomotive carrying out shunting movements before the departure, or after the arrival of a train normally displays the signals previously described. A locomotive engaged solely in shunting carries the signals described below.

At a large station, local instructions may describe the use of the headlights to indicate the destination of the locomotive (eg depot, passenger station, shunting yard, stabling sidings etc.).


A shunting locomotive displays:

At the front:



By day:

In the centre upper position an unlit white V.



White

White

At night:

In the centre upper position an illuminated white V and two white lights over the buffers.

At the back:

By day:

No signal.

At night:

Two white lights over the buffers.


The diagram number is carried on both ends, but only at locations where several shunting locomotives are in use.

Fahrberechtigungssignal

This is a Travel entitlement signal. On single

track routes it is displayed by a train which has been authorised to proceed beyond a timetabled crossing point without having "crossed" the train in the opposite direction. On double track routes which are not signalled for two way working it is displayed by trains travelling on the "wrong" track.

The locomotive at the head of the train displays:



At the centre, upper position, one red light and, below left and right, two white lights.

If it is not possible to display the centre, upper red light, then the lower right light displays red.


Marking of vehicles which must not be moved

Vehicles which must not be moved, such as those under repair, or tank wagons being filled or emptied, are marked by a red disc, as shown below.


These signals are positioned before the start of work; on platform tracks on the entrance side, on shunting or storage tracks on the side most easily seen by shunting staff. Normally, they are placed on the wagon concerned but can, where necessary, be placed on other vehicles or at the end of a group of vehicles or train.

Should the correct marker not be available then a portable STOP sign (March 1991 Swiss Express, p.12) may be used, positioned several metres from the vehicle(s) to be protected.


Pre-heating indicator board



Black



By day:



Vehicles which are being heated, either by means of a fixed land-line or an unmanned locomotive, are marked by a yellow board.

The board is positioned, prior to the start of heating, on the end vehicle which other movements can approach (eg at a terminal platform, the end furthest from the buffers). Push-pull trains have a board at each end. The board is positioned as for the "Not-to-be-moved" indicator (above).


The pre-heating board prohibits connection and disconnection of the heating jumpers. A careful approach, without moving the vehicle(s), as well as connection of the main coupling and brake pipes, is permitted.

Vehicles which are connected to a fixed power line for other reasons than pre-heating are similarly protected.

By night:

Marking of an occupied Postal vehicle


Orange



Occupied Postal vehicles not formed in a train are identified by an orange pennant on both sides of the vehicle. At night, the interior lights are lit.

Brake shoe warning board

Yellow



(White logo)

An orange brake shoe warning board indicates that the vehicle carrying it is prevented from movement by brake shoes (scotches).

Next instalment: Overhead power supply signs.