

Zeitschrift: Swiss express : the Swiss Railways Society journal
Herausgeber: Swiss Railways Society
Band: 6 (2000-2002)
Heft: 5

Artikel: Steam around Switzerland. Part 4, Südostbahn mixed traffic locomotive type Ed 4/5
Autor: Hardy-Randall, Malcolm
DOI: <https://doi.org/10.5169/seals-854903>

Nutzungsbedingungen

Die ETH-Bibliothek ist die Anbieterin der digitalisierten Zeitschriften auf E-Periodica. Sie besitzt keine Urheberrechte an den Zeitschriften und ist nicht verantwortlich für deren Inhalte. Die Rechte liegen in der Regel bei den Herausgebern beziehungsweise den externen Rechteinhabern. Das Veröffentlichen von Bildern in Print- und Online-Publikationen sowie auf Social Media-Kanälen oder Webseiten ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. [Mehr erfahren](#)

Conditions d'utilisation

L'ETH Library est le fournisseur des revues numérisées. Elle ne détient aucun droit d'auteur sur les revues et n'est pas responsable de leur contenu. En règle générale, les droits sont détenus par les éditeurs ou les détenteurs de droits externes. La reproduction d'images dans des publications imprimées ou en ligne ainsi que sur des canaux de médias sociaux ou des sites web n'est autorisée qu'avec l'accord préalable des détenteurs des droits. [En savoir plus](#)


Terms of use

The ETH Library is the provider of the digitised journals. It does not own any copyrights to the journals and is not responsible for their content. The rights usually lie with the publishers or the external rights holders. Publishing images in print and online publications, as well as on social media channels or websites, is only permitted with the prior consent of the rights holders. [Find out more](#)

Download PDF: 05.08.2025

ETH-Bibliothek Zürich, E-Periodica, <https://www.e-periodica.ch>

PART 4 - SÜDOSTBAHN MIXED TRAFFIC LOCOMOTIVE TYPE Ed 4/5



Ed 4-5 No 21, Works photo. Courtesy: SLM

THE RAILWAY COMPANY.

The Schweizerische Südostbahn was formed, in 1890, by the amalgamation of the Wädenswil-Einsiedeln Bahn and the Zürichsee-Gotthardbahn. The primary function of this new railway was to connect Wädenswil - and in 1901 Pfäffikon - to the Gotthard line at Arth-Goldau. When the WEB was formed passengers from Zürich were brought to Wädenswil aboard the company steamers *Wädenswil* or *Speer*. The route with its ruling gradient of 50‰ and minimum radius of 130 metres presented quite a problem for the motive power. Cantonal Engineer Kaspar Wetli designed a rack system for the WEB line, which comprised diagonally placed rails formed into a large "V" installed in the steepest section of the track. However, trials with adhesion only locomotives proved to work well so the plan was not developed. The new SOB line also proved taxing on the motive power as it too had gradients up to 50‰.

THE LOCOMOTIVE.

The locomotive manufacturer SLM in Winterthur was requested in 1909 to supply two

locomotives able to haul a trailing load of 120 tonnes at 30 km/h over the route from Rapperswil to Arth-Goldau. The 49 km long route consisted of, for the main part, level track or gradients up to 30‰ but 7.5 km of the route was at 40‰ and a further section measuring 13.9 km was at the maximum gradient of 50‰.

SLM produced, in 1910, a tank locomotive with four coupled axles measuring 11 000 mm in length able to develop 880 HP at 25 km/h. The inside frame consisted of folded 28 mm thick steel plate. Water storage was in two small side tanks - capacity 5.2 m³ - located just in front of the drivers cab and the 1.6 tonnes of coal stored in a bunker on the rear bulkhead of the cab. Sand stored in a large dome on top of the boiler behind the steam dome, was fed to the centre two axles.

The 4 000 mm long boiler operated at 12 bars and was protected by two pop valves located just in front of the driving cab. Superheated steam at 300° C was fed from the 18-tube Schmidt superheater via a double slide-valve regulator which supplied two horizontally mounted cylinders. The cylinders measuring 500 mm in diameter with a stroke of 600 mm were controlled by Walschaerts valve gear and powered the third of the four coupled driving axles.

Speed indication was according to the Hasler system, the brakes operated on all driving axles via a screw handle or the double action Westinghouse air-brake system. The locomotive proved to be very economical in that it consumed just 55 kg of coal per 1 000 gross-tonne-kilometres, which was superior to that of the smaller SOB E 3/3 locomotive. After many years of satisfactory service the SOB requested SLM to draw up plans for an improved locomotive in order that heavier trains could be hauled over the line to Arth-Goldau. In 1934 SLM responded with two proposals, one based on the Ed 4/5 in the form of a 1-C-1 and the other was based on a Thunersee Bahn loco and was designated as 1-D-1. However progress overtook the plans as electrification came on to the scene and the SOB had chosen to proceed along that path rather than spend money on more steam locomotives.

The service life of number 21 ended in 1939 due to the electrification of the route with number 22 following in 1940. The locomotives were placed on the market and sold to Krupps of Germany in 1941. On the 26th February 1941 along with several of their sister locomotives from the Class E 3/3 they were hauled by SBB locomotive C 5/6 No.2961 to Basel Badischer to be handed over to the DR. In 1949 both locomotives were sold by Krupps Steel to the Osthannoverschen Bahnen [East Hannover Railway] for service on passenger traffic where they served until 1961 [22] and 1963 [21]. After that they were sent for scrap.

References used:-

- *Der Dampfbetrieb der Schweizerischen Eisenbahnen. 1847 - 1922. Moser.*
- *Die Südostbahn, Geschichte einer Privatbahn. Gerhard Oswald.*
- *SOB Documents.*



*Ed 4-5 Near Rabennest Tunnel.
Courtesy: Hurlimann/SOB*

LOCOMOTIVE DATA.

Type Ed 4/5, 1-D
Nos 21 - 22
Built by SLM Winterthur **Works No** 2091-2
Date built 1910
Power HP880 @ 25 km/h kW647 @ 25 km/h
T/E at wheel rim. 9 500 kN
Date in Service-1910 **Date out of service**-1940
Max. Speed 50 km/h
Speed Indicator Hasler
Driving wheels
 Diameter 1 130 mm
 Wheelbase Rigid 2 650 mm Total 6 810 mm
 Overall length 11 000 mm Height 4 300 mm
Loco weight
 Empty 48.0 Tonnes Service 59.4 Tonnes
 Adhesion 52.0 Tonnes
 Water capacity 5.2 m³ Coal capacity 1.6 Tonnes
Brakes
 Mechanical-Screw Automatic-Westinghouse double action
Cylinders
 Number High pressure 2
 Bore 500 mm Stroke 600 mm
Boiler
 Operating pressure 12 Bars Length 4 000 mm
 No. of Tubes 112
 Firebox 27.5 m² Grate area 2.1 m²
 Superheater type-Schmidt No. of Tubes 18
Trailing load
 Gradient 50‰ 120 tonnes @ 30 km/h
Construction
 Cost SFr 74 100



Above: 2 x Ed 4-5. At Rothenthurm 1915

Photo: Courtesy SOB

Below: Ed 4-5 No21-22 Hauling an express at Samstagern.

Photo: Courtesy SOB

