

Swiss railways' double track Aar Bridge at Ruppoldingen / SO

Autor(en): **Herzog, M.**

Objektyp: **Article**

Zeitschrift: **IABSE structures = Constructions AIPC = IVBH Bauwerke**

Band (Jahr): **3 (1979)**

Heft C-7: **Structures in Switzerland**

PDF erstellt am: **30.04.2024**

Persistenter Link: <https://doi.org/10.5169/seals-15778>

Nutzungsbedingungen

Die ETH-Bibliothek ist Anbieterin der digitalisierten Zeitschriften. Sie besitzt keine Urheberrechte an den Inhalten der Zeitschriften. Die Rechte liegen in der Regel bei den Herausgebern.

Die auf der Plattform e-periodica veröffentlichten Dokumente stehen für nicht-kommerzielle Zwecke in Lehre und Forschung sowie für die private Nutzung frei zur Verfügung. Einzelne Dateien oder Ausdrucke aus diesem Angebot können zusammen mit diesen Nutzungsbedingungen und den korrekten Herkunftsbezeichnungen weitergegeben werden.

Das Veröffentlichen von Bildern in Print- und Online-Publikationen ist nur mit vorheriger Genehmigung der Rechteinhaber erlaubt. Die systematische Speicherung von Teilen des elektronischen Angebots auf anderen Servern bedarf ebenfalls des schriftlichen Einverständnisses der Rechteinhaber.

Haftungsausschluss

Alle Angaben erfolgen ohne Gewähr für Vollständigkeit oder Richtigkeit. Es wird keine Haftung übernommen für Schäden durch die Verwendung von Informationen aus diesem Online-Angebot oder durch das Fehlen von Informationen. Dies gilt auch für Inhalte Dritter, die über dieses Angebot zugänglich sind.

14. Swiss Railways' double track Aar Bridge at Ruppoldingen / SO

Owner and project management: Swiss Federal Railways,
Region 2 (Lucerne)

Designer and resident engineer: Dr. Max Herzog, Aarau
(collab. B. Fent)

Contractor: Locher & Cie AG, Zürich, and Rüeegg Bau AG,
Olten, in joint-venture

Dimensions:

length: 320 m

spans: 32 + 40 + 46 + 62 + 80 + 60 m

width: 10.7 m

Superstructure: six span continuous single-cell box-girder
with variable height above the river

Substructure: slender piers with elliptic cross-section and
box-type abutments

Foundations:

— southern abutment and land piers on stepped footings in
shallow depth

— river piers each on two bored piles of 3.0 m diameter and
40 m length

— northern abutment on two bored piles of 1.75 m diameter
and 18 respectively 38 m length

Quantities:

excavation: 3'000 m³

formwork: 11'500 m²

concrete: 5'000 m³

reinforcement: 620 t

prestressing steel: 180 t

sheet piling: 1'800 m²

years of construction: 1977 – 1978




Fig. 4 Construction phase




Fig. 1 Plan




Fig. 2 Longitudinal section

Introduction

To permit the realization of a rigid time-table on Switzerland's main line a new line has to be built between Olten and Rothrist. The Ruppoldingen Bridge is situated immediately southwards of the Born Tunnel and crosses the Aar River near Aarbrugg at about 45 degrees skew. The bridge as-built was chosen from a design competition among five consulting engineers.

Design and Construction

Special features worth mentioning are:

Slurry piles of 3.0 m diameter were a first in the country (concrete cube strength 40 N/mm² at 90 days)

The river piers' cross-section was verified in hydraulic model tests

Instead of steel bearings concrete hinges were built (cube strength 100 N/mm² at 90 days, extreme working stress 70 N/mm²)

Jumbo tendons (system VSL) consisting of 33 normal strands with 0.6" diameter ($0.65 \beta_z \cdot A_s = 5600$ kN) and of 37 compact strands with 0.6" diameter (7500 kN) respectively Construction of the box-girder in several steps with section lengths of 20 - 45 m (southern half in 1977 and northern half in 1978):

- 1) Bottom slab of constant thickness in transverse direction (0.30 - 0.70 m) and webs of constant thickness (0.70 m) on normal scaffolding only as wide as the box-section
- 2) Top slab of variable thickness in transverse direction (0.30 - 0.50 m)
- 3) After construction of all box-sections for half the bridge length the tendons were pushed into previously cast ducts and the shrinkage gaps were closed. Five days later 50 per cent of the final prestressing force were applied
- 4) Cantilever slabs were cast with help of an overhead travelling formwork
- 5) After construction of the cantilever slabs for half the bridge length the full prestressing force was applied and the tendon ducts were grouted

There is a full splice of tendons between the two halves of the superstructure

Specified concrete cube strength of 50 N/mm² at 28 days (60 N/mm² at 90 days) was reached under strict control

The bridge has no fixed bearings. It is elastically restrained by the piers' bending stiffness

The design was checked against the most recent developments in the understanding of variable-amplitude fatigue loading and strength

Measurements

Because of the bridge's importance a large program of measurements is under way. Besides the usual deflections also

- temperature distributions in several cross-sections
- reinforcement strains under prestressing and different loadings to obtain information on the local strain distribution in the box-girder's cross-sections next to the piers
- displacements of the superstructure and ground-relaxation under longitudinal forces
- concrete hinge rotations

and other values are measured systematically.




Fig. 3 Cross-sections



(M. Herzog) Fig. 5 Completed bridge